

VELUX ACTIVE indoor climate control KIX 300

VELUX®



VELUX ACTIVE with NETATMO indoor climate control uses sensors to continuously measure temperature, humidity and CO2 levels in your home to ensure a healthier indoor climate. Based on indoor climate measurements and external weather data, VELUX ACTIVE automatically operates connected VELUX electric products for ventilation and sunscreening when necessary. It also enables control of VELUX electric products using the smartphone app or voice control assistants.

- Automatically activates your windows and accessories based on indoor climate sensor measurements and weather data.
- Conveniently control your windows and monitor your indoor climate from anywhere on your smart phone. The App can be downloaded from AppStore (iOS) and Google Play (Android) for free.
- Activates your VELUX electric and solar shutters, awnings or blinds to protect your home from overheating.
- Your windows will automatically activate when the indoor climate in the room is deteriorating.
- Rest assured that your home is ventilated a minimum of three times a day.
- Activates your roof window for cooling when it's too hot inside.
- Rest assured that your solution is protected thanks to the high levels of security encryption.

Technical information

VELUX ACTIVE indoor climate control KIX 300	Material and colour	VELUX ACTIVE gateway: ABS plastic, white (NCS S 1000-N) VELUX ACTIVE indoor climate sensor: ABS plastic, white (NCS S 1000-N) VELUX ACTIVE departure switch: ABS plastic, white (NCS S 1000-N)
	Size and weight description	Gateway: 93x93x28 mm, 125g Departure switch: 81x81x15 mm, 39g Indoor climate sensor: 116x80x18 mm, 62g
	Installation and use	Indoor installation at max 40 °C. The gateway must be placed at a central location in the home ensuring wireless connection to both VELUX products and WiFi router. The bracket is to be used for fixation on the wall. The sensor KLA 300 is to be installed in the room 90-170 cm above floor level for measuring the indoor climate. The departure switch KLN 300 is to be installed next to the entrance door of the home for safe departure. Radio frequency range: 300 m free field. Depending on building construction, the indoor range is approx 30 m. However, constructions with reinforced concrete, metal ceilings and plaster walls with steel members may reduce the range. See also installation instructions. The daily operation of the VELUX electric products is performed from the app VELUX ACTIVE with NETATMO. The app is also used for setting personal preference to the ACTIVE control. Additional operation is possible via the indoor climate sensor KLA 300 and departure switch KLN 300. The indoor climate sensor KLA 300 has 3 buttons which can be used to operate (up/down/stop) all products of the same type within the room (e.g. roof windows). The departure switch KLN 300 has 2 buttons (lock and unlock buttons) which can be used to set the 'safe mode'. This limits or enables full automatic operation of roof windows.
	Power consumption	VELUX ACTIVE gateway 3LG: 230/240 V a.c. – 50-60 Hz / 2.5 W
	Compatibility	iPhone, iPad or iPod touch with iOS 9.0 or later Smart phone / tablet with Android 5.0 or later Apple HomeKit Google Assistant (only voice control) VELUX electric products (except KRD 100 adaptor plug & KRA 100 frame light) Connected VELUX electric products: Maximum 200 Connected sensor switches (KLA 300): Maximum 10 Connected departure switches (KLN 300): Maximum 5
	Connection	Wireless connection: 868.0 - 870.0 MHz (io-homecontrol®) 863.0 - 870.0 MHz (RF sub GHz) 2400 - 2483.5 MHz (Wi-Fi 802.11 b/g/n -2.4 GHz). Security standard: Open/WEP/WPA/WPA2 (TKIP and AES) Physical connection: The VELUX ACTIVE gateway is equipped with a 1.5 m 2-core cable with mains plug for connection to the mains supply.
Departure switch	Materials	ABS plastic, white (NCS S 1000-N)
Gateway	Materials	PC plastic, white (NCS S 1000-N)
Indoor climate sensor	Materials	ABS plastic, white (NCS S 1000-N)
Departure switch	Size and weight description	80 mm x 80 mm x 10 mm (WxHxD), 0.065 kg.
Gateway	Size and weight description	95 mm x 95 mm x 25 mm (WxHxD), 0.125 kg.
Indoor climate sensor	Size and weight description	80 mm x 115 mm x 15 mm (WxHxD), 0.165 kg.
Departure switch	Installation and use	The departure switch is for indoor use only, between a minimum ambient temperature 5 °C and a maximum ambient temperature 45 °C. It can be used in a dry or humid environment (such as a hall or an entrance). Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.

Gateway	Installation and use	The gateway is for indoor use only, between a minimum ambient temperature 5 °C and a maximum ambient temperature 45 °C. It can be used in a dry environment (such as a living room or a bedroom). Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
Indoor climate sensor	Installation and use	The sensor switch is for indoor use only, between a minimum ambient temperature 5 °C and a maximum ambient temperature 45 °C. It can be used in a dry or humid environment (such as a living room, a bedroom or a bathroom). Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
Departure switch	Power consumption	2 x Alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 2 years.
Gateway	Power consumption	230/240 V a.c. – 50-60 Hz / 2.5 W
Indoor climate sensor	Power consumption	3 x Alkaline AA (1.5V) batteries Expected battery lifetime: Up to 2 years.