

VELUX roof window VLT 025/029/033 1000

VELUX®

Glazing 00H



The window can be installed in roof pitches between 20° and 60°.



VELUX roof window VLT 1000 is designed for use in uninhabited rooms where light and ventilation is needed. Can be mounted either side-hung or top-hung depending on the variant. Side-hung variants can open to the left or right depending on preferred use. Comes with timber frame and integrated metal flashing. Available in five sizes. Sizes 025, 029 and 033 are right-hinged and can be changed to left-hinged.

- Three ventilation positions enable you to secure a constant low-level air flow in uninhabited areas.
- Maintain a nice traditional look with the pine wood frame in natural lacquer.
- Patented opening restrictor securely holds the window open at 90-degrees.
- Opens outwards to the left or the right for easy access to the roof.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the folded aluminium sash.
- Large assortment to match every need.

Available sizes and daylight area

	450	850
550	VLT 025 (0.21)	
730	VLT 029 (0.28)	
850		VLT 033 (0.65)

All measurements are in mm. () = Effective daylight area, m²

Glazing features

Glazing 00H		U_g =
	<p>Heat insulation The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.</p>	
	<p>Solar gain In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.</p>	
	<p>Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.</p>	
	<p>Security Thicker laminated inner glass increases resistance to manual attack (burglary).</p>	
	<p>Safety lamination Prevents glass from falling into the room in case of accidental breakage.</p>	
	<p>Toughened glass Adds strength to the outer glass surface to protect from wayward balls and extreme weather such as heavy storms and hail.</p>	
	<p>UV filter Protects your interior furnishings from fading due to the sun's harmful UV rays.</p>	
	<p>Rain noise reduction Rain noise reduction creates a barrier between the window and the weather outside for undisturbed moments during rainy days – or nights.</p>	
	<p>Easy-to-clean Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view.</p>	
	<p>Anti-dew The anti-dew coating significantly reduces the days with dew on the outer glass and thus gives you a clear view.</p>	

Glazing structure

Glazing unit	Composition (from inside to outside)
Double-glazed	3 mm float glass - 10 mm Air - 3 mm float glass

Interior finish

Material Description	Clear lacquer Finished with double coat.
Colour code NCS, inner surface	No colour code
Colour code nearest RAL, inner surface	No colour code

Exterior covers

Material Description	Aluminium, dark grey Dark grey
Colour code NCS, outer surface	S 7500-N
Colour code nearest RAL, outer surface	7043

Guarantee period

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.