

# VELUX glass rooflight electric exit CXU



Glazing 20, double-glazed



Glass rooflight electric exit CXU offers easy access to the roof for repair or maintenance. A safety and ventilation switch kit is mandatory and will always be delivered together with the CXU. The safety and ventilation switch kit ensures safe exit to the roof by offering entrapment and fall-through protection. The kit makes it simple for the user to open and fix the glass rooflight at 60 degrees when exiting, and to close the window when on the roof. Furthermore, the kit is uniquely designed with an integrated rain sensor that automatically closes the glass rooflight in the event of rain. To ensure proper operation of all key functionalities – including entrapment control, fall-through protection, and rain sensor responsiveness – the CXU must be used in combination with KES 305.

- The unique and innovative VELUX safety and ventilation switch kit with entrapment control and fall-through protection enables a safe exit to the roof and the ability to close the window when on the roof.
- The glass rooflight electric exit automatically opens to 60 degrees when used as roof exit for hassle-free access to the roof.
- With its glass-to-edge slim profile, the glass rooflight electric exit shares a strong design aesthetic with the other VELUX glass rooflights.
- This trustworthy and durable solution is easy to install with the same installation principles as other VELUX glass rooflights.
- In daily use, the glass rooflight electric exit can easily be opened at the touch of a button for fresh air and ventilation.
- Unlike many other flat roof exit windows, the glass rooflight electric exit CXU is designed for the complete range of VELUX flat roof window blinds.
- Enjoy a quieter indoor environment and very good thermal insulation from our energy-efficient two-layer insulating glass unit

