

# VELUX roof window VLT 024 1000

**VELUX®**

Glazing 00H



The window can be installed in roof pitches between 20° and 45° to the horizontal.



---

VELUX roof window VLT 1000 is designed for use in uninhabited rooms where light and ventilation is needed. Can be mounted either side-hung or top-hung depending on the variant. Side-hung variants can open to the left or right depending on preferred use. Comes with timber frame and integrated metal flashing. Available in five sizes. Size 024 is top-hung, the other four sizes are side-hung.

- Three ventilation positions enable you to secure a constant low-level air flow in uninhabited areas.
- Maintain a nice traditional look with the pine wood frame in natural lacquer.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.
- Top-hung window with harmonic and symmetric aesthetics when opened.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the folded aluminium sash.
- Large assortment to match every need.











## Available sizes and daylight area

---

	900
480	VLT 024 (0.38)

All measurements are in mm. ( ) = Effective daylight area, m<sup>2</sup> [ ] = Geometric free area, m<sup>2</sup>

## Glazing features

Glazing 00H		
	<b>Heat insulation</b> The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.	$U_g = 3.0$
	<b>Solar gain</b> In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.	<b>0.79</b>
	<b>Solar protection</b> In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.	★★☆☆
	<b>Security</b> Thicker laminated inner glass increases resistance to manual attack (burglary).	<b>N/A</b>
	<b>Safety lamination</b> Prevents glass from falling into the room in case of accidental breakage.	
	<b>Toughened glass</b> Adds strength to the outer glass surface to protect from wayward balls and extreme weather such as heavy storms and hail.	
	<b>UV filter</b> Protects your interior furnishings from fading due to the sun's harmful UV rays.	
	<b>Rain noise reduction</b> Rain noise reduction creates a barrier between the window and the weather outside for undisturbed moments during rainy days – or nights.	
	<b>Easy-to-clean</b> Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view.	
	<b>Anti-dew</b> The anti-dew coating significantly reduces the days with dew on the outer glass and thus gives you a clear view.	

### Glazing structure

Glazing unit	Composition (from inside to outside)
Double-glazed	3 mm float glass - 10 mm Air - 3 mm float glass

## Interior finish

---

Material Description	Clear lacquer Finished with double coat.
Colour code NCS, inner surface	No colour code
Colour code nearest RAL, inner surface	No colour code

## Exterior covers

---

Material Description	Aluminium, dark grey Dark grey
Colour code NCS, outer surface	S 7500-N
Colour code nearest RAL, outer surface	7043

## Guarantee period

---

## Further information

---

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.