VELUX INTEGRA® power supply unit KUX 110



3 Year Guarantee

Connect your motorised roof window directly to mains power with the VELUX INTEGRA® power supply unit KUX 110 with mains cable and mains plug. Enables electrical operation of one VELUX INTEGRA® window operator (KMG 100/100K), a VELUX INTEGRA® electric awning blind, a VELUX INTEGRA® electric roller shutter or a VELUX INTEGRA® electric interior blind.

- Connect your VELUX electric window operator, blind, awning or shutter product directly to mains power.
- RF technology provides safe and reliable wireless control of any VELUX electric product.
- Add VELUX electric interior blinds, roller shutters or awning blinds for heat protection and light control.

Creation date 29-09-2026 17:20:26 Electrical products K-- Technical info version en-GB - Approved

Technical information

VELUX INTEGRA® power supply unit KUX 110	**Material and colour**	PC, white (NCS S 1000-N)
	Size and weight description	Product including packaging: 238 x 166 x 80 mm. Weight: 1.013 kg
	Installation and use	24 V d.c. SELV class III product. The power supply unit can be installed by non-professionals. The power supply unit for indoor use, maximum ambient temperature 50°C. Installation in rooms with a high level of humidity must comply with relevant regulations. Radio frequency range: 300 m free field. Depending on building construction, the indoor range is approximately 30 m. The power supply unit must not be covered.
	Power consumption	230 V a.c. – 50 Hz / 40 VA.
	Compatibility	KUX 110 is based on radio frequency (RF) technology, 868 MHz range, and is compatible with other products with the io-homecontrol® logo. It can be used with all VELUX electrical window operators as well as electrically operated interior and exterior decoration and sunscreening products.
	Connection	The power supply unit is equipped with a 1.2 m cable and plug for connection to the mains supply. KUX 110 is delivered with an 8 m 0.75 mm^2 2-core cable for connection to the motor. When using a longer cable, please observe the following minimum wiring dimensions: Length up to 20 m = 2 x 0.75 mm^2 50 m = 2 x 1.50 mm^2 All VELUX roof windows are prepared for wiring to fit the 2-core cable.

Creation date 29-09-2026 17:20:26