

VELUX craftsman's roof exit GVK

VELUX®

Glazing 00H



The window can be installed in roof pitches between 20° and 65°.



VELUX roof window GVK is designed for use in uninhabited rooms where easy access to the roof and regular ventilation is needed. Side-hung, it opens to the left or right depending on preferred use. Made from maintenance-free aluminium and polyurethane. Comes complete with integrated flashing and moulded tread. Available with black profiles.

- Three ventilation positions enable you to secure a constant low-level air flow in uninhabited areas.
- Opens outwards to the left or the right for easy access to the roof.
- Patented opening restrictor securely holds the window open at 90-degrees.
- Maintain the traditional exterior expression of the building with the traditional design.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the extruded aluminium sash.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.














Available sizes and daylight area

	460
610	GVK +++ (0.22)

All measurements are in mm. () = Effective daylight area, m² [] = Geometric free area, m²

Glazing features

Glazing 00H		
	Heat insulation The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.	$U_g = 3.0$
	Solar gain In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.	0.79
	Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.	★★☆☆
	Security Thicker laminated inner glass increases resistance to manual attack (burglary).	N/A
	Safety lamination Prevents glass from falling into the room in case of accidental breakage.	
	Toughened glass Adds strength to the outer glass surface to protect from wayward balls and extreme weather such as heavy storms and hail.	
	UV filter Protects your interior furnishings from fading due to the sun's harmful UV rays.	
	Rain noise reduction Rain noise reduction creates a barrier between the window and the weather outside for undisturbed moments during rainy days – or nights.	
	Easy-to-clean Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view.	
	Anti-dew The anti-dew coating significantly reduces the days with dew on the outer glass and thus gives you a clear view.	

Glazing structure

Glazing unit	Composition (from inside to outside)
Double-glazed	3 mm float glass - 10 mm Air - 3 mm float glass

Interior finish

Material Description	Black maintenance free Finished with polyurethane lacquer.
Colour code NCS, inner surface	S 9000-N
Colour code nearest RAL, inner surface	9005

Exterior covers

Material Description	Aluminium, dark grey Dark grey
Colour code NCS, outer surface	S 7500-N
Colour code nearest RAL, outer surface	7043

Guarantee period

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.