



















Quick guide to Vario Continuous Rooflights







Shapes		
		
Vario Norm – Barrel vault Standard	Vario Therm – Barrel vault Energy efficient	Vario Therm S – Mono- or dual pitched Energy efficient




Opening / ventilation / SHEV – Barrel vault				
				
Fixed Mechanical louvre systems	Full flap 165° opening	Side flap 130° opening	Cross beam flap 130° opening	Double flap 95° opening

Opening / ventilation / SHEV – Mono- or dual pitched					
					
Fixed Mechanical louvre systems	Flat saddle 65° opening	Steep saddle 65° opening	Standard shed 65° opening	Customized shed 65° opening	Comfort ventilation 65° opening (top hung)

Glazing U _g -values		
		
U _g = 1,16-2,50 W/(m ² K)	U _g = 1,16-1,80 W/(m ² K)	U _g = 1,1-1,8 W/(m ² K)
Vario Norm 10 different glazing types depending on intention	Vario Therm 9 different glazing types depending on intention	Vario Therm S 3 different glazing types depending on intention

Kerb

Vertical contour Available in the height between: 250 – 700 mm Available in two editions: standard and for insulated/thermal roofs Optional kerb connection profile system OPTIMAL for permanent secure connection of the roof sheeting

Fall-Through Protection Systems					
					
LB-DSL Galvanised steel safety grating	LB-SR Steel tubes with cross beam	LB-DDS Safety steel grid flap protection	PROTECT Shading, hail impact and protection system	PROTECT-120-VWS For more daylight intake Wider slat spacing	SAFEGUARD Traffic route and fall-through safety

Size grids		
		
Vario Norm Width: From 120 up to 1134 cm Length: No limitation	Vario Therm Width: From 120 up to 1134 cm Length: No limitation	Vario Therm S Width: From 100 up to 600 cm Length: No limitation