



# VELUX curved glass ISU 1093

VELUX®



The innovative, maintenance-free curved glass top unit for glass rooflights is a revolution in rooflight design. The premium choice for homeowners that are looking for a glass-to-edge design that boosts the appearance of their homes and delivers optimal drainage - even in 0° roof pitch. The outer glass is toughened making this a highly durable top unit that has increased resistance to wind, snow and hail. The curved glass top unit is compatible with all base units for glass rooflights CFU/CVU.

- Seamless glass-to-edge design blends into the roof and integrates perfectly onto flat-roofed homes.
- The curved-shaped top with natural drainage effect allows the window to be installed in roofs with 0° pitch
- Maintenance-free glass gives peace of mind and features a stylish design
- Discretely placed blackout or awning blind lets you enjoy maximum daylight influx and a stylish interior design at all times.
- The outer glass of the top unit is strength-tested in tough weather conditions.
- Toughened outer glass is attached with high-strength weather-proof sealant.
- Easy and safe transportation of the top unit from ground to roof; no need for manual lifting.



## Application guidance

The curved glass top unit ISU 1093 can be installed with all new generation base units within the roof pitch range of 0°-15° degrees.



Combine the curved glass top unit with a base unit that meets your need for daylight only, or daylight and ventilation. Choose the vented base unit for glass rooflight CVU for fresh air at the touch of a button or the fixed base unit for glass rooflight CFU if your primary need is to bring daylight into the room.

## Available sizes and daylight area

### Compatible Base Units

E	CVU 20Q electric	K	CVU 25Q solar	N	CFU 20Q fixed, A*
I	CVU 20Q solar	L	CVU 25Q solar, A*	O	CFU 25Q fixed
J	CVU 20Q solar, A*	M	CFU 20Q fixed	P	CFU 25Q fixed, A*

	600	800	900	1000	1200	1500	2000
600	ISU 060060 (0.29) I, K, M, O		ISU 090060 (0.45) I, K, M, O				ISU 200060 (1.04) J, L, N, P
800		ISU 080080 (0.54) I, K, M, O				ISU 150080 (1.06) I, K, M, O	
900			ISU 090090 (0.70) I, K, M, O		ISU 120090 (0.95) I, K, M, O		
1000				ISU 100100 (0.88) I, K, M, O		ISU 150100 (1.35) I, K, M, O	ISU 200100 (1.82) J, L, N, P
1200					ISU 120120 (1.3) E, I, K, M, O	ISU 150120 (1.64) J, L, N, P	
1500						ISU 150150 (2.07) J, L, N, P	

All measurements are in mm. ( ) = Effective daylight area, m<sup>2</sup> [ ] = Geometric free area, m<sup>2</sup>

\*A=large sizes with glazing variant -A

## Technical values


Overview of technical values for the product, covering among other, CE marking in accordance with EN 1873 or EAD 200062-00-0401

Window characteristics	CFU 20Q + ISU 1093	CFU 25Q + ISU 1093	CVU 20Q + ISU 1093	CVU 20U + ISU 1093	CVU 25Q + ISU 1093	CVU 25U + ISU 1093	CXU 20U + ISU 1093	CXU 25U + ISU 1093
Air permeability, [class]	4	4	4	4	4	4	4	4
Thermal transmittance Urc,ref300 (CE-marked) (U-value)	0.65	0.55	0.65	0.65	0.55	0.55	0.75	0.65
Arc, ref300 (U-value transmission area)	4.4	4.4	4.4	4.4	4.4	4.4	4.4	4.4
Light transmittance ( $\tau_v$ ) ( $\tau$ )	0.69	0.63	0.69	0.69	0.63	0.63	0.68	0.63
Sound insulation ( $R_w$ ) $R_w$ dB [dB]	39	42	39	39	42	42	39	42
Total solar energy transmittance (g-value) (g)	0.52	0.49	0.52	0.52	0.49	0.49	0.52	0.49
Ultraviolet transmittance ( $\tau_{uv}$ ) ( $\tau_{uv}$ )	0.05	0.05	0.05	0.05	0.05	0.05	0.05	0.05
Burglar resistance window [class]	RC2	RC2	RC2	RC1	RC2	RC1	NPD	NPD
Frame factor	0.1	0.1	0.1	0.1	0.1	0.1	0.1	0.1
Air permeability, [class]	4	4	4	4	4	4	4	4
Reaction to fire [class]	C-s2, d2							
Bonding of cover glass (glass of top unit) [class]	$\Delta X \geq 0.75$							
External fire performance - European [class]								
External fire performance - British [class]	NPD							
Impact resistance [class]	3	3	3	3	3	3	3	3
Impact resistance large soft body [class]	N/A							
Impact resistance small hard body [class]	N/A							
Rain noise (Lia)	44 dB							
Resistance to downward loads	N/A							
Resistance to fire [class]	NPD							
Resistance to snow load	*	*	*	*	*	*	*	*
Resistance to upward load	N/A							
Resistance to wind load [class]	C3							
Water tightness [class]	9A							

NPD: No Performance Determined

\* : See glazing composition

# VELUX electric glass rooflight CVU, Glazing 25, triple-glazed




Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The base unit of the electrically vented glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This vented base unit comes with 3-layer glazing, but is also available with 2-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width		080
Vw	Visible glazing width	738.2
Lw	Inside groove measure width	759
Rw	Roof opening	800
Iw	Inside sash measure width	936
Ew	Exterior frame width	1015

Height		080
Vh	Visible glazing height	738.2
Lh	Inside groove measure height	759
Rh	Roof opening	800
Ih	Inside sash measure height	936
Eh	Exterior frame height	1015

# VELUX electric glass rooflight CVU, Glazing 20, double-glazed




Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The base unit of the electrically vented glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This vented base unit comes with 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width		120
Vw	Visible glazing width	1138.2
Lw	Inside groove measure width	1159
Rw	Roof opening	1200
Iw	Inside sash measure width	1228
Ew	Exterior frame width	1415

Height		120
Vh	Visible glazing height	1138.2
Lh	Inside groove measure height	1159
Rh	Roof opening	1200
Ih	Inside sash measure height	1228
Eh	Exterior frame height	1415

## VELUX fixed glass rooflight CFU, Glazing 20, double-glazed



Transform your home by bringing the magic of daylight into areas where you never thought possible with the new generation of VELUX glass rooflights.


The base unit of the fixed glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This fixed base unit has 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic, thus increasing your indoor comfort.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The low placement of the insulating glass unit in the construction gives optimal energy performance and an elegant, slim design - especially with blinds and awnings installed.
- The loose installation triangle gives you more flexibility during installation and supports installation of the rooflight in different roofing materials and uneven roof surfaces.

Width	060	080	090	100	120	150
Vw   Visible glazing width	538.2	738.2	838.2	938.4	1138.2	1438.2
Lw   Inside groove measure width	559	759	859	959	1159	1459
Rw   Roof opening	600	800	900	1000	1200	1500
Iw   Inside sash measure width	736	936	1036	1136	1228	1636
Ew   Exterior frame width	815	1015	1115	1215	1415	1715

Height	060	080	090	100	120
Vh   Visible glazing height	538.2	738.2	838.2	938.2	1138.2
Lh   Inside groove measure height	559	759	859	959	1159
Rh   Roof opening	600	800	900	1000	1200
Ih   Inside sash measure height	736	936	1036	1136	1228
Eh   Exterior frame height	815	1015	1115	1215	1415

# VELUX fixed glass rooflight CFU, Glazing 25, triple-glazed



Transform your home by bringing the magic of daylight into areas where you never thought possible with the new generation of VELUX glass rooflights.


The base unit of the fixed glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This fixed base unit has 3-layer glazing, but is also available with 2-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic, thus increasing your indoor comfort.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The low placement of the insulating glass unit in the construction gives optimal energy performance and an elegant, slim design - especially with blinds and awnings installed.
- The loose installation triangle gives you more flexibility during installation and supports installation of the rooflight in different roofing materials and uneven roof surfaces.

Width	060	080	090	100	120	150
Vw   Visible glazing width	538.2	738.2	838.2	938.4	1138.2	1438.2
Lw   Inside groove measure width	559	759	859	959	1159	1459
Rw   Roof opening	600	800	900	1000	1200	1500
Iw   Inside sash measure width	736	936	1036	1136	1228	1636
Ew   Exterior frame width	815	1015	1115	1215	1415	1715

Height	060	080	090	100	120
Vh   Visible glazing height	538.2	738.2	838.2	938.2	1138.2
Lh   Inside groove measure height	559	759	859	959	1159
Rh   Roof opening	600	800	900	1000	1200
Ih   Inside sash measure height	736	936	1036	1136	1228
Eh   Exterior frame height	815	1015	1115	1215	1415

# VELUX solar glass rooflight CVU, Glazing 20, double-glazed




Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The glass rooflight base unit has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This solar base unit is fully powered by the sun and can be installed in any flat roof home without any need for wiring. The solar base unit comes with 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width	060	080	090	100	120	150
Vw   Visible glazing width	538.2	738.2	838.2	938.4	1138.2	1438.2
Lw   Inside groove measure width	559	759	859	959	1159	1459
Rw   Roof opening	600	800	900	1000	1200	1500
Iw   Inside sash measure width	736	936	1036	1136	1228	1636
Ew   Exterior frame width	815	1015	1115	1215	1415	1715

Height	060	080	090	100	120
Vh   Visible glazing height	538.2	738.2	838.2	938.2	1138.2
Lh   Inside groove measure height	559	759	859	959	1159
Rh   Roof opening	600	800	900	1000	1200
Ih   Inside sash measure height	736	936	1036	1136	1228
Eh   Exterior frame height	815	1015	1115	1215	1415

# VELUX solar glass rooflight CVU, Glazing 25, triple-glazed




Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The glass rooflight base unit has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This solar base unit is fully powered by the sun and can be installed in any flat roof home without any need for wiring. The solar base unit comes with 3-layer glazing, but is also available with 2-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width	060	080	090	100	120	150
Vw   Visible glazing width	538.2	738.2	838.2	938.4	1138.2	1438.2
Lw   Inside groove measure width	559	759	859	959	1159	1459
Rw   Roof opening	600	800	900	1000	1200	1500
Iw   Inside sash measure width	736	936	1036	1136	1228	1636
Ew   Exterior frame width	815	1015	1115	1215	1415	1715

Height	060	080	090	100	120
Vh   Visible glazing height	538.2	738.2	838.2	938.2	1138.2
Lh   Inside groove measure height	559	759	859	959	1159
Rh   Roof opening	600	800	900	1000	1200
Ih   Inside sash measure height	736	936	1036	1136	1228
Eh   Exterior frame height	815	1015	1115	1215	1415

## VELUX fixed glass rooflight CFU, Glazing 20A, double-glazed



Transform your home by bringing the magic of daylight into areas where you never thought possible with the new generation of VELUX glass rooflights.


The base unit of the fixed glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This fixed base unit has 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic, thus increasing your indoor comfort.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The low placement of the insulating glass unit in the construction gives optimal energy performance and an elegant, slim design - especially with blinds and awnings installed.
- The loose installation triangle gives you more flexibility during installation and supports installation of the rooflight in different roofing materials and uneven roof surfaces.

Width		150	200
Vw	Visible glazing width	1438.2	1938.2
Lw	Inside groove measure width	1459	1959
Rw	Roof opening	1500	2000
Iw	Inside sash measure width	1636	2036
Ew	Exterior frame width	1715	2215

Height		060	100	120	150
Vh	Visible glazing height	538.2	938.2	1138.2	1438.2
Lh	Inside groove measure height	559	959	1159	1459
Rh	Roof opening	600	1000	1200	1500
Ih	Inside sash measure height	736	1136	1228	1636
Eh	Exterior frame height	815	1215	1415	1715

## VELUX fixed glass rooflight CFU, Glazing 25A, triple-glazed



Transform your home by bringing the magic of daylight into areas where you never thought possible with the new generation of VELUX glass rooflights.


The base unit of the fixed glass rooflight has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This fixed base unit has 3-layer glazing, but is also available with 2-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic, thus increasing your indoor comfort.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The low placement of the insulating glass unit in the construction gives optimal energy performance and an elegant, slim design - especially with blinds and awnings installed.
- The loose installation triangle gives you more flexibility during installation and supports installation of the rooflight in different roofing materials and uneven roof surfaces.

Width		150	200
Vw	Visible glazing width	1438.2	1938.2
Lw	Inside groove measure width	1459	1959
Rw	Roof opening	1500	2000
Iw	Inside sash measure width	1636	2036
Ew	Exterior frame width	1715	2215

Height		060	100	120	150
Vh	Visible glazing height	538.2	938.2	1138.2	1438.2
Lh	Inside groove measure height	559	959	1159	1459
Rh	Roof opening	600	1000	1200	1500
Ih	Inside sash measure height	736	1136	1228	1636
Eh	Exterior frame height	815	1215	1415	1715

## VELUX solar glass rooflight CVU, Glazing 20A, double-glazed




Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The glass rooflight base unit has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This solar base unit is fully powered by the sun and can be installed in any flat roof home without any need for wiring. The solar base unit comes with 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width		150	200
Vw	Visible glazing width	1438.2	1938.2
Lw	Inside groove measure width	1459	1959
Rw	Roof opening	1500	2000
Iw	Inside sash measure width	1636	2036
Ew	Exterior frame width	1715	2215

Height		060	100	120	150
Vh	Visible glazing height	538.2	938.2	1138.2	1438.2
Lh	Inside groove measure height	559	959	1159	1459
Rh	Roof opening	600	1000	1200	1500
Ih	Inside sash measure height	736	1136	1228	1636
Eh	Exterior frame height	815	1215	1415	1715

# VELUX solar glass rooflight CVU, Glazing 25A, triple-glazed



Transform your home by bringing the magic of daylight and fresh air into areas where you never thought possible with the new generation of VELUX glass rooflights. The glass rooflight base unit has a unique design with a slim frame and invisible sash providing maximum daylight and a beautiful design from inside the home. This solar base unit is fully powered by the sun and can be installed in any flat roof home without any need for wiring. The solar base unit comes with 2-layer glazing, but is also available with 3-layer glazing, and has excellent energy performance as well as sound reduction capabilities in case of rain, hail or traffic. It delivers fresh air at the touch of a button and has a pre-installed rain sensor that conveniently closes the window automatically in the event of rain, thus providing full peace of mind. It can even be operated via a smart phone, using the VELUX App Control. A both beautiful and convenient solution for your home.

- Unique ThermoTechnology™ material contributes to optimal energy efficiency and indoor comfort
- The wall switch is pre-paired to work with your rooflight right out of the box.
- The motor is hidden from view in the rooflight frame for a sleek appearance and unobstructed view to the sky.

Width		150	200
Vw	Visible glazing width	1438.2	1938.2
Lw	Inside groove measure width	1459	1959
Rw	Roof opening	1500	2000
Iw	Inside sash measure width	1636	2036
Ew	Exterior frame width	1715	2215

Height		060	100	120	150
Vh	Visible glazing height	538.2	938.2	1138.2	1438.2
Lh	Inside groove measure height	559	959	1159	1459
Rh	Roof opening	600	1000	1200	1500
Ih	Inside sash measure height	736	1136	1228	1636
Eh	Exterior frame height	815	1215	1415	1715

## Insulating glass unit structure

	Glazing 20, double-glazed	Glazing 20A, double-glazed	Glazing 25, triple-glazed	Glazing 25A, triple-glazed
<b>Composition (from inside to outside)</b>	7.5 mm laminated float glass - 16 mm Argon - 4 mm toughened glass with enamel	9.5 mm laminated float glass - 15 mm Argon - 8 mm toughened glass with enamel	7.5 mm laminated float glass - 10 mm Argon - 3 mm heat strengthened glass - 10 mm Argon - 4 mm toughened glass with enamel	9.5 mm laminated float glass - 10 mm Argon - 4 mm heat strengthened glass - 10 mm Argon - 8 mm toughened glass with enamel

## Cleaning and maintenance



Cleaning of the top unit is only possible from the outside. When cleaning the top unit of vented glass rooflights, switch off the mains supply, ie do not open the rooflight. To clean inner surface of top unit and outer glass surface of base unit, remove cover caps and screws to remove the top unit and fasten again after cleaning. In regions with heavy snowfall, snow masses on the flat-roof window must be removed on a regular basis.

## Guarantee period

## Blinds and awnings

Complete your VELUX glass rooflight with a blind for complete comfort. Choose between an anti-heat blind to maintain a cool room on hot days or a blackout blind to block outside light for total darkness. The blinds are discreetly placed and do not compromise daylight and design when not in use. You also have the option of adding an insect screen that lets you enjoy fresh air without any insects.

Use VELUX App Control or VELUX ACTIVE with NETATMO for smartphone control of your vented glass rooflight and blinds.

## Further information

---

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.