# VELUX extra sound reduction roof window GGU



Glazing 62SG







The VELUX top-operated, centre-pivot, extra sound reduction roof window GGU is maintenance-free and designed with special glass and extra sound insulation to reduce incoming noise. Top operation allows for easy access to the window, even with furniture placed beneath.

- Maintenance-free, polyurethane coating makes the window ideal when easy maintenance is key.
- Special sound-insulating glazing reduces noise from outside.
- Easily rotate the window 180° for safe cleaning of the outer glass from the inside.
- Easily open and close the roof window even with furniture placed underneath.
- Removable and cleanable ventilation filter protects your home from dust and insects while ventilating.
- Quickly and easily add blinds by simply clicking them into the pre-fitted brackets.
- Upgrade to a remote-controlled mains- or solar-powered motor for extra convenience.







### Application guidance

The window can be installed in roof pitches between 15° and 90° to the horizontal.



Manually top-operated, centre-pivot roof windows make it possible to place furniture directly below the window without obstructing the window's operation. We recommend an installation height that allows for a clear sight line to the outside from both a standing and seated position. Please note that the optimum window height depends on the roof pitch.

### Available sizes and daylight area


	550 mm	660 mm	780 mm	942 mm	1140 mm
mm	GGU CK02				
778 mm	(0.22) [0.26]				
mm	GGU CK04	GGU FK04	GGU MK04		
978 mm	(0.29) [0.34]	(0.38) [0.43]	(0.47) [0.53]		
шu	GGU CK06	GGU FK06	GGU MK06	GGU PK06	GGU SK06
1178 mm	() []	(0.47) [0.54]	(0.59) [0.66]	(0.75) [0.83]	(0.95) [1.03]
98		GGU FK08	GGU MK08	GGU PK08	GGU SK08
1398		(0.58) [0.66]	(0.72) [0.81]	(0.92) [1.01]	(1.16) [1.25]
00			GGU MK10	GGU PK10	
1600			(0.85) [0.94]	(1.07) [1.17]	

All measurements are in mm. ( ) = Effective daylight area,  $m^2$  [ ] = Geometric free area,  $m^2$ 



### Cross section dimensions

Please note that the view of the cross section is from bottom to top.



Width		CK	FK	MK	PK	SK
Sw	Sash aperture width	371	481	601	763	961
Lw	Distance between lining grooves, width	495	605	725	887	1085
Ew	External frame width	550	660	780	942	1140

Height		02	04	06	08	10
Sh	Sash aperture height	584	784	984	1204	1406
Lh	Distance between lining grooves, height	719	919	1119	1339	1541
Eh	External frame height	778	978	1178	1398	1600



## Glazing features

#### Glazing 62SG



		4
*/5	<b>Heat insulation</b> The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.	U <sub>g</sub> = 0.5
-\o\-\cdot\-\cdo	<b>Solar gain</b> In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.	0.47
<u>`</u> ;-\	Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.	***
1×1	Security Thicker laminated inner glass increases resistance to manual attack (burglary).	***
4.0	Safety lamination Prevents glass from falling into the room in case of accidental breakage.	<b>√</b>
	Toughened glass Adds strength to the outer glass surface to protect from wayward balls and extreme weather such as heavy storms and hail.	<b>√</b>
-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\-\	<b>UV filter</b> Protects your interior furnishings from fading due to the sun's harmful UV rays.	<b>√</b>
	Rain noise reduction Rain noise reduction creates a barrier between the window and the weather outside for undisturbed moments during rainy days – or nights.	<b>√</b>
The state of the s	Easy-to-clean Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view.	
00	Anti-dew The anti-dew coating significantly reduces the days with dew on the outer glass and thus gives you a clear view.	<b>√</b>

#### Glazing structure

Glazing unit	Variant composition
Triple-glazed	6.8 mm laminated float glass - 11 mm Krypton - 3 mm heat strengthened glass - 11 mm Krypton - 8 mm toughened glass



### Technical values for the window

Overview of technical values for the product, covering among other, CE marking in accordance with EN 14351-1.

Window characteristics	Performance
Thermal transmittance	0.92 W/(m <sup>2</sup> K)
Light transmittance	0.68
Total solar energy transmittance	0.47
Sound insulation	42(-2;-5)
Air permeability	4 (PK10: 3)
External fire performance - British	AC
External fire performance - European	npd
Impact resistance	3
Load-bearing capacity of safety devices	✓
Reaction to fire	D-s3,d2
Resistance to snow load	See glazing composition
Resistance to wind load	C3 (>SK08: NPD)
Water tightness	E900

NPD: No performance determined



### Visible features



#### Interior insulation, sound reduction, frame top

Innovative ThermoTechnology  $^{\text{IM}}$  insulation is integrated into the top frame of the window to increase energy-efficiency and reduce incoming noise.



#### Noise reduction gasket

Extra gasket to improve sound reduction.



#### Control bar

The ergonomic aluminum control bar allows effortless opening and closing of the window.



#### Blind bracket, manual

Easily install blinds on the window without the need for extra tools. Simply click on the blind in the pre-fitted brackets.



#### Frame hinge, centre-pivot, side

Durable hinge design allows for reliable operation and enables the sash to be rotated for easy cleaning of the outer glass.



#### **Excellent insulation**

High performance insulation materials in the window construction and thermally modified timber core incease the energy efficiency of the window.



#### Barrel bolt

The barrel bolt can be placed into the integrated barrel bolt bushing to secure the window for cleaning of outer glass surface or for safe ventilation.



#### Headlock

When closed, the window is locked firmly into place by the headlock.



### Interior finish

Material Description	White maintenance-free Finished with polyurethane lacquer.		
Colour code NCS, inner surface	S 0500-N		
Colour code nearest RAL, inner surface	9003		

### Exterior covers

Material Description	Aluminium, dark grey Dark grey	Titanium zinc	Untreated copper
Colour code NCS, outer surface	S 7500-N	No colour code	
Colour code nearest RAL, outer surface	7043	No colour code	

### Cleaning and maintenance



To clean the outer glass surface from the inside, rotate sash and secure in cleaning position with barrel bolts.



VELUX repair and maintenance kits are available.

### Guarantee period



The full terms and conditions of the VELUX Product Guarantee are available on our website www.velux.co.uk or www.velux.ie



### Flashings and installation products



#### Flashings

Install the VELUX roof window in virtually any roofing material by using genuine VELUX flashing solutions. Our flashings are designed specifically for the exact size and shape of the roof windows to create perfect, watertight fit. Flashings can also be used to combine multiple roof windows.

#### Installation products

Ensure a proper installation and an air- and watertight connection between the window and roof with VELUX installation products. All installation products are designed to perfectly fit the roof window for a reliable and durable result.

### Blinds, awnings and shutters

Complete the VELUX roof window installation with roller shutters and awning blinds for heat protection and interior blinds for light dimming, blackout and insect protection. Choose from a wide range of manually operated or remote-controlled products that are made to fit the particular window type and size. Please contact your local VELUX sales company for more details about compatibility.

### Further information

We reserve the right to make technical changes.

For more information on our products, please visit https://www.velux.co.uk or https://www.velux.ie.