


- ① ODL flashing (20°-90°)
- ② VELUX window (GGL 20°-90°)
- ③ VELUX underfelt collar (BFX)
- ④ VELUX insulation frame (BDX)
- ⑤ VELUX vapour barrier (BBX)
- ⑥ VELUX vapour barrier tape (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX Lining (LS-)
- ⑨ Installation batten (Non VELUX)
- ⑩ Trimmer where necessary (Non VELUX)
- ⑪ Felt/breather membrane (Non VELUX)
- ⑫ Homij water thightness plate (Non VELUX)
- ⑬ Timber frame 25 mm above batten (Non VELUX)
- ⑭ Homij Side adapter (Non VELUX)
- Gray RAL 7043 Gloss 30
- Black RAL 9005 Gloss 30

Roof covering:



VELUX Products:



VELUX window sizes:

| Size | Width (mm) | Size | Height (mm) |
|------|------------|------|-------------|
| MK-- | 780 | -K08 | 1398 |

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

| | | | |
|-----------------------------------|------------|---------------|---------------|
| VELUX | | | |
| File name: HOMIJ-GGL-VAS-801-0618 | | | |
| Drawing no.:--- | | SCo: --- | |
| Create date: 26.06.2018 | Rev. date: | Format: A3 | Scale: 1:5 |

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.