

- ① VELUX flashing (EDWS 15°-90°)
- ② VELUX window (GGLS 15°-90°)
- ③ VELUX underfelt collar (BFXS are in EDWS)
- ④ VELUX insulation frame (BDXS are in EDWS)
- ⑤ VELUX vapour barrier (BBXS are in EDWS)
- ⑥ VELUX vapour barrier tape (BBXS are in EDWS)
- ⑦ Gasket on BBXS in window rebate
- ⑧ Installation batten (Non VELUX)
- ⑨ Trimmer where necessary (Non VELUX)
- ⑩ Felt/breather membrane (Non VELUX)


Roof covering:

**Tiles**  
Max 120 mm 

VELUX Products:

**GGLS**  
15°-90° 

**EDWS**  
15°-90° 

**BFXS** 

**BDXS** 

**BBXS** 

VELUX window sizes:

Size	Width (mm)	Size	Height (mm)
FFKF	1880	-06	1178
		-08	1398

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

<b>VELUX</b>			
File name: 531166-01 EDWS-GGLS-VAS-126-0619			
Drawing no.:---		SCo:---	
Create date: 19.06.2019	Rev. date:	Format: A3	Scale: 1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.