VELUX solar awning blinds MSI



5 Year Guarantee

VELUX solar awning blinds can be remote-controlled and reduce overheating to maintain a cool, comfortable temperature in your room. They are transparent, so you can always enjoy your views and natural light during the day. They connect with your VELUX roof window and window element GIL/GIU combination to give you total control over your indoor comfort. They are easy to install (no wiring).


- Heat protection keeps your room cool and increases indoor comfort.
- VELUX solar interior blinds, awning blinds and roller shutters give you convenient remote control without any wiring.
- Preserve your outside view, reduce unwanted glare and incoming sunlight
- Maintenance-free design delivers peace of mind for the lifetime of your product.
- Designed to fit for quick and easy installation from the inside
- Compatible with VELUX ACTIVE with NETATMO for a better indoor climate with automatic heat protection. Remote controlled via smartphone or voice.
- Stepless positioning allows you to lower the blind to exactly where needed.
- Built to last, the wind-resistant awning blind has been strength-tested in our testing facilities.

CE

Creation date 27-10-2026 21:06:18 Awning blinds INTEGRA en-GB - Approved

Colours and patterns

VELUX awning blind has a transparent mesh fabric. Add this fabric colour code to your awning blind type when you order your products.



5060

Operation guidance

The solar awning blind is operated by an individual pre-configured wall switch, included in the packages.

Compatibility

Compatibility with VELUX roof windows in sizes C02-U10 and sizes CK02-UK10:

Awning blind MSI can be fitted on GGL, VELUX solar GGL, GGU, VELUX solar GGU, GHL, GPL and GPU combined with fixed additional window element GIL or GIU.

As for sizes, please refer to the price list.

MSI cannot be installed on GPL/GPU roof windows with size codes without letters.

The awning blind can be installed on VELUX electric top-hung roof windows GPU using ZOZ 229S.

If you combine the solar awning blind MSI with VELUX solar roof window GGL or GGU in width FK—(produced from 2012) or width F--/M--/P--/S--/U—(produced between 2000-2012), a dual solar switch ZOZ 246 is required.

The combination of several roof windows side by side requires a frame distance of at least 18 mm. If the windows are combined over/under each other, the frame distance must be at least 250 mm. The solar soft shutters can be fitted in windows with twin flashing EB-.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit https://www.velux.co.uk or https://www.velux.ie.

Creation date 27-10-2026 21:06:18

Technical information

VELUX solar awning blinds MSI	**Battery**	High performance battery, NiMH, 9.6 V DC, 2100 mAh.
	Connection	N/A
	Installation and use	The solar awning blind MSI should be installed from outside because of the fixed window element. The installation is both secure, fast and easy, among other things due to the specially designed VELUX “snap” brackets. It can be done by one person. The awning blind has a high quality NiMH battery, which is charged by a solar cell integrated in the top casing, and is operated with the pre-paired wall switch. The blind supports silent mode when controlled by VELUX ACTIVE with NETATMO or VELUX App control.
	Material and colour	Top casing, side profiles and bottom cover: Lacquered aluminium, grey (NCS S 7500-N) Top casing end pieces, side profile bottom pieces and bottom cover end pieces: Tinted plastic, grey (NCS S 7500-N).
	Power consumption	High performance battery, NiMH, 9.6 V DC, 2100 mAh. The battery is an energy buffer for operation in periods with inadequate charging. A fully charged battery allows up to 100 operations. The shutter comes with a battery which must be switched on before operation. Expected battery lifetime: 10 years.
Pre-paired wall switch	**Installation and use**	A pre-configured one-way radio frequency wall switch (KLI 313) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
	Material and colour	ABS plastic, white (NCS S 1000-N)
	Power consumption overview	2 x alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 1 year.
	Size and weight description	8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg.

Creation date 27-10-2026 21:06:18