

VELUX electric translucent pleated blind FMG

VELUX®



VELUX electric translucent pleated blinds can be remote-controlled and offer soft and decorative daylight control. The cloth helps to diffuse the incoming daylight for a pleasant glare-free environment. The electric pleated blinds connect seamlessly with your VELUX electric flat-roof windows, but can also be used with fixed flat-roof windows. VELUX blinds with white side rails fit perfectly with your white VELUX roof windows.

- Increase your privacy, reduce unwanted glare and control incoming sunlight exactly as you like.
- VELUX electric blinds, awning blinds and shutters give you convenient remote control for extra comfort.
- Slimmest profile design on the market lets more natural light in.
- Standard 100 by OEKO-TEX® certification guarantees the product is made without harmful substances.
- Stepless positioning allows you to lower the blind to exactly where needed.
- Compatible with VELUX ACTIVE with NETATMO - control your products from anywhere you want via smartphone or voice control.
- Elegant blind design with white side rails, which fit perfectly with white VELUX roof windows.
- Integrated side rails provide smooth operation.



Colours and patterns

VELUX interior blinds are available in a wide range of colours and designs. However, a few blind variants are only available in a limited range of colours. Each colour and design option has a unique code. Add the code of your choice to the relevant blind type when ordering your products.



1016



1259

Operation guidance

The VELUX electric translucent pleated blind comes with a pre-paired wall switch for remote control and can be raised and lowered to any desired position.

Compatibility

Compatibility with VELUX electric flat-roof windows:

Translucent pleated blind FMG can be installed in flat-roof windows CFP and CVP (not manually operated). As for sizes, please refer to the price list.

Compatibility with other VELUX sunscreening products, VELUX electric and solar-powered and VELUX ACTIVE products:

The blind can be combined with VELUX solar-powered awning blind MSG.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://www.velux.co.uk> or <https://www.velux.ie>.

Technical information

VELUX electric translucent pleated blind FMG	Connection	When fitting the blind onto flat-roof windows, plug the 2.5 m long motor cable supplied into the blind and connect the cable to the connection box in the VELUX electric flat-roof window or, in the case of VELUX flat-roof windows, to a separate control system.
	Installation and use	When using a longer cable, please observe the following minimum wiring dimensions: Length up to 20 m: 0.75 mm ² Length up to 40 m: 1.50 mm ²
	Material and colour	Installation brackets are delivered with the blind and should be fitted to the window. Once the brackets are fitted, the blind is easily clicked on, leaving both hands free during the remaining part of the installation. The cable supplied is plugged into the blind and connected to the connection box in the window or to a separate control system.
	Power consumption	The translucent pleated blind can be raised and lowered in any position using the wall switch. Manual operation is possible, but should mainly be used for horizontal alignment of the blinds or in extraordinary cases.
Pre-paired wall switch	Installation and use	Control bar with motor unit, top fascia and side rails: White lacquered aluminium. Guides: Plastic, white Bottom brackets: Plastic, grey
	Material and colour	0.25 A, 24 V d.c. from a VELUX electric flat-roof window, or from a VELUX electric control system
	Power consumption overview	A pre-configured one-way radio frequency wall switch (KLI 312) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
	Size and weight description	ABS plastic, white (NCS S 1000-N) 2 x alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 1 year.
Translucent pleated blind cloth	Material and colour	8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg. Cloth: 100 % polyester. Colours: See brochure and price list for VELUX decoration and sun screening products. Cords: 100 % polyester