

VELUX røykvarsler KFA 100



Aktiver røykventilasjonsvindue automatisk med røykvarsleren KFA 100. Den optiske sensoren sørger for tidlig varsling ved røykdannelse. Komfortventilasjon overstyres i nødstilfeller.

- Aktiverer automatisk vindusåpneren for røykventilasjon ved røykutvikling. Tilkobling til et styresystem er påkrevd.
- Legg til flere veggbrytere, brannknapper, røykvarslere og regnsensorer.
- Fullstendig i samsvar med gjeldende og forventede fremtidige CE-standarder og -forskrifter.

Technical information

VELUX røykvarsler KFA 100

Materiale og farge

Cabinet color: RAL 9016, white

Montering og bruk

Up to 10 smoke detectors can be connected to each control system. KFA 100 smoke detectors should always be fitted on the ceiling in accordance with current national legislation. When the base is fitted correctly on the ceiling the smoke detector can be snapped on to it. A dust cover can be added until products are taken into use. With multiple KFA installed, all detectors must be installed in ONE line (series) from the control unit to insure all detectors are monitored. The terminal module in the control unit must be moved to the detectors placed farthest away from the control unit.

Power consumption

12V d.c.

Kompatibilitet

Full compatibility with VELUX smoke ventilation system, KFX and KFC 210/220

Tilkobling

KFA 100 is connected to the control unit by a 2 core cable, min. cross section: 0.5 mm², Max. cable length: 100m.