

VELUX solar 2in1 soft shutter SSSS.



VELUX solar soft shutters deliver effective heat protection keeping your home cool on warm, sunny days. The durable light-tight fabric blocks out light when needed and reduces rain noise. They come complete with pre-paired wall switches for easy operation. The solar 2in1 soft shutters SSSS are specially designed for your VELUX manual and solar 2in1 roof windows GGLS and GPLS.

- Heat protection keeps your room cool and increases indoor comfort.
- The light-tight fabric provides blackout for a better night's sleep.
- VELUX solar interior blinds, awning blinds and roller shutters give you convenient remote control without any wiring.
- Maintenance-free design delivers peace of mind for the lifetime of your product.
- Compatible with VELUX ACTIVE with NETATMO for a better indoor climate with automatic heat protection. Remote controlled via smartphone or voice.
- Stepless positioning allows you to lower the shutter to exactly where needed.



Operation guidance

The solar soft shutters are operated by individually pre-paired wall switches, included in the packages.

Compatibility

Compatibility with VELUX roof windows:

Solar 2in1 soft shutters SSSS can be fitted on VELUX 2in1 roof windows GGLS and GPLS. As for sizes, please refer to the price list.

If combining the solar soft shutters with solar roof windows GGLS FK--, FM-- or FP--, dual solar switch ZOZ 246 must be ordered.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://www.velux.co.uk> or <https://www.velux.ie>.

Technical information

Pre-paired wall switch	Power consumption overview	2 x alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 1 year.
	Size and weight description	8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg.
	Material and colour	ABS plastic, white (NCS S 1000-N)
	Installation and use	A pre-configured one-way radio frequency wall switch (KLI 313) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
VELUX solar 2in1 soft shutter SSSS.	Connection	Each solar soft shutter is a stand-alone product on an io-homecontrol® operation platform. It does not require any wiring or connection to mains supply.
	Battery	High performance battery, NiMH, 9.6 V DC, 2100 mAh.
	Power consumption	High performance battery, NiMH, 9.6 V DC, 2100 mAh. The battery is an energy buffer for operation in periods with inadequate charging. A fully charged battery allows up to 100 operations. The shutter comes with a battery which must be switched on before operation. Expected battery lifetime: 10 years.
	Solar cell	Photovoltaic solar cell unit integrated in the top casing.
Exterior shield	Material and colour	Slats: Lacquered aluminium slats filled with polyurethane foam (does not contain Freon): grey (NCS S 7500-N). Hinges between slats: black rubber.
VELUX solar 2in1 soft shutter SSSS.		The blackout fabric is made of polyester with PVC coating on both sides. The black cloth is tested for UV and heat degradation as well as for shrinkage deformation and curvy appearance.
	Installation and use	The VELUX solar 2in1 soft shutters should be installed from the outside on VELUX 2in1 roof windows GGLS or GPLS. The installation is secure, fast and easy, among other things due to the specially designed VELUX "snap" brackets, and it can be done by one person.