


VELUX®

Commercial

VELUX Modular Skylights

Technical Handbook





DZNE: German Center for Neurodegenerative Diseases, Germany, 2016
Ridgelight at 5° with Beams
Photographer: STORM Production





VELUX Modular Skylights

VELUX Modular Skylights are sash-frame constructed single roof windows with a high-insulating glazing unit. The modules are available as both fixed and venting skylights. All individual skylights are delivered as prefabricated modules with dedicated factory finished flashings to ensure watertightness in every solution.

VELUX Modular Skylights roof windows are CE-marked in accordance with the harmonized standard EN 14351-1 – Windows and doors.

Fire resistant modules are CE-marked in accordance with the EAD 220116-00-0401 of 2018-12 as relevant harmonized technical specification and the essential characteristics are expressed in accordance with the ETA-19/0027 of 2019-03-11.

The self-supporting Ridgelights are CE-marked in accordance with the European Assessment Document EAD 220013-01-0401 of 2017-03 as relevant harmonized technical specification.



The load bearing capacity performance of the self-supporting Ridgelights is expressed in the European Technical Assessment ETA 17/0476 of 2019-01-28.

In addition, the skylight modules have been tested and approved in accordance with EN 12101-2 – Smoke and heat control systems Part 2: Specification for natural smoke and heat exhaust ventilators.



VELUX Modular Skylights has a reference service life of 30 years in accordance with EN 17213.

This technical handbook for VELUX Modular Skylights describes the product characteristics and performance of the skylight module together with sun screening and control system.

For real life case studies and inspiration, please refer to: veluxcommercial.com



VELUX Thermal Break and Double-Glazed Skylight (model code: 424/2200-2/2000)			
Glazing unit area	424 (2000 x 2000)	424 (2000 x 2000)	0.00 - 0.01 depending on size
Thermal break area	424 (2000 x 2000) frame B	424 (2000 x 2000) frame B	0.00 - 0.01 depending on size
Thermal break value	424 (2000 x 2000) frame B	0.00	0.00 - 0.01 depending on size
Glazing unit (G1)	424 (2000 x 2000) frame B	50 (24x12)	7500 (24x12)
Glazing unit (G2)	424 (2000 x 2000) frame B	50 (24x12)	7500 (24x12)
Low and high temperature (T)	424 (2000 x 2000) frame B	1 (12)	1 (12)
Reliability (R1) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R2) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R3) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R4) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R5) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R6) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R7) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R8) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R9) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R10) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R11) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R12) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R13) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R14) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R15) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R16) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R17) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R18) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R19) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R20) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R21) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R22) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R23) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R24) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R25) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R26) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R27) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R28) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R29) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R30) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R31) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R32) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R33) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R34) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R35) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R36) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R37) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R38) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R39) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R40) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R41) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R42) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R43) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R44) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R45) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R46) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R47) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R48) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R49) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R50) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R51) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R52) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R53) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R54) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R55) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R56) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R57) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R58) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R59) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R60) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R61) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R62) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R63) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R64) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R65) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R66) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R67) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R68) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R69) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R70) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R71) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R72) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R73) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R74) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R75) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R76) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R77) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R78) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R79) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R80) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R81) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R82) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R83) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R84) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R85) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R86) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R87) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R88) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R89) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R90) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R91) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R92) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R93) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R94) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R95) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R96) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R97) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R98) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R99) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000
Reliability (R100) (Double glazed)	424 (2000 x 2000) frame B	40 (20 x 20)	1000 x 1000



Modular System

7

Skylight module	8
Functions & sizes / Size grid	8
How to measure the modules	10
Solutions	12
Module – main components	16
Module – electrical components	17
Frame & sash	18
Cladding & flashing	22
Glazing unit	24
Brackets & hinges	28
Module – assembled	30
Sub-construction	32
Vapour barrier connection strip / Products for swimming pool environments	34
Chain actuator	36
Control system	37
Roller blind	38
Beam for Ridgelight at 5°	40
Wind deflector for smoke ventilation modules	42
Data plate	43

Solutions

45

Quick overview of skylight solutions vs. roof constructions	46
Longlight 5-30°	54
Wall-mounted Longlight 5-45°	56
Northlight 25-90°	58
Ridgelight 25-40°	60
Ridgelight at 5° with Beams (Horizontal beam with rectangular profile)	62
Ridgelight at 5° with Beams (Parallel beam with curved profile)	64
Step Longlight 5-25°	66
Step Wall-mounted Longlight 5-25°	68
Step Ridgelight 25°	70
Step Ridgelight 5-25° on Girder	72
Atrium Longlight	74
Atrium Ridgelight & Atrium Ridgelight at 5° with Beams	76

Product Data

79

Skylight module	80
Glazing unit	96
Frame & sash	100
Cladding & flashing	101
Vapour barrier connection strip	102
Chain actuator	103
Control system	103
Roller blind	105
Beam for Ridgelight at 5°	108
Water pressure & drainage	109
Resistance to wind load	110
Reaction to fire	112
Resistance to fire	114
External fire performance	116
Watertightness	118
Air permeability	120

Additional Solutions

123

Shaped solution with adaption of lining	124
Shaped solution with oval lining	124
Asymmetric Ridgelight	125
Ridgelight on Girder	125
Infill panel	126
Skylight modules with photovoltaic glazing units	126
Sun screening – electrochromic glass	127
Sun screening – external awning blinds	127
Ridgelight on Pitch	128
Gable modules	128
Coupled flashings	129
Wall on side	129

Product Codes

131

Modular Skylight – code structure	132
Roller blinds – code structure	133
Product label – code structure	133
Flashings – code structure	134



The image is an isometric line drawing on a dark gray background, illustrating a modular system. It features two rectangular frames. The upper frame is composed of multiple parallel lines, suggesting a multi-layered or reinforced structure. The lower frame is similar but includes a solid, light gray rectangular panel being inserted into it. This panel has a dashed line along its edges, indicating it is a separate component. Small mechanical details, such as clips or fasteners, are visible at the corners where the panel meets the frame, highlighting the system's modularity and ease of assembly. The text 'Modular System' is centered between the two frames.

Modular System

Skylight module

CE-marked VELUX Modular Skylights can be used in any building where the national, local and individual building requirements allow the use of skylight modules. Given the aesthetics and advanced performance of the products, VELUX Modular Skylights are commonly used in heated buildings and primarily in projects that support light

commercial interests, e.g. hospitals, schools, shopping centres, offices, museums etc. However, all buildings that have a suitable structure and are large enough to host an installation, will support VELUX Modular Skylights.

Functions & sizes

VELUX Modular Skylights are available as fixed and venting modules. Due to a hidden chain actuator, the fixed and venting modules appear to be visually identical in closed position. It is not possible to install two venting modules next to each other.

Venting modules are top-hung and can be used for comfort ventilation, and in addition, certain types are approved for smoke ventilation in accordance with EN 12101-2.



HFC

Fixed skylight module.



HFS

Fire resistant module.




HVC-C

Motorized comfort venting skylight module.
Actuator chain stroke 260 mm.


HVC-A


Motorized smoke venting skylight module.
Actuator chain stroke up to 700 mm, which opens in less than 60 seconds.
Only open system actuator available.



Size grid

 Standard size.

 Semi-Standard, functional limitations may apply.

 Non-Standard, available for certain projects.

Fixed modules



mm	675	750	800	900	1000
600	±Δ	±Δ	±Δ	±Δ	±Δ
800	Φ	Φ	Φ	Φ	Φ
1000	Φ	Φ	Φ	Φ	Φ
1200					
1400					
1600					
1800					
2000					
2200					
2400					
2600	*	*	*	*	*
2800	*	*	*	*	*
3000	*	*	*	*	*

Comfort ventilation



mm	675	750	800	900	1000
600					
800	Φ	Φ	Φ	Φ	Φ
1000	Φ	Φ	Φ	Φ	Φ
1200					
1400					
1600					
1800					
2000					
2200					
2400					
2600	* p	* p	* p	* p	* p
2800	* p	* p	* p	* p	* p
3000	* p	* p	* p	* p	* p

Smoke ventilation



mm	675	750	800	900	1000
600					
800	0	0	0	0	0
1000	0	0	0	0	0
1200	0	0	0	0	0
1400	0	0	0	0	0
1600	0	0	0	0	0
1800	0	0	0	0	0
2000	0	0	0	0	0
2200	0	0	0	0	0
2400	0	0	0	0	0
2600	* o p	* o p			
2800	* o p				

* Module height above 2400 mm is delivered with an extra strong glazing unit only.

Δ No roller blinds available.

0 Only open system actuator available.

± Not available for Ridgelight.

p Not possible as start/end modules.

Φ Roller blinds must be pre-mounted or installed by a VELUX technician.

For size specific load capacity, please contact us.

If roller blinds are requested for smoke venting modules or fire resistant modules, please refer to local fire authorities for permission.




NB: Roller blinds for smoke venting modules or fire resistant modules cannot be pre-mounted.

Wind deflector KCD 0080 is not available for sizes above 2400 mm.

How to measure the module

Width and height of the modules are determined by the exterior dimensions of the frame – not the measurements of the cladding, flashing or brackets.





Solutions

VELUX Modular Skylights can be combined in a number of configurations to create perfect solutions for a wide variety of building types, from narrow corridors and internal courts to studios and

large circulation spaces. Each solution is delivered with a specially designed, prefabricated flashing ensuring a perfect system.

Mono pitched solutions

Longlight 5-30°

Page: 54



Wall-mounted Longlight 5-45°


Page: 56



Northlight 25-90°

Page: 58






Dual pitched solutions


Ridgelight 25-40°

Page: 60



Ridgelight at 5° with Beams

Page: 62






Step solutions

Step Longlight 5-25°

Page: 66




Step Wall-mounted Longlight 5-25°

Page: 68




Step Ridgelight 25°


Page: 70



Step Ridgelight 5-25° on Girder

Page: 72





Atrium solutions

Atrium Longlight 5-30°

Page: **74**



Atrium Ridgelight 25-40°

Page: **76**





Atrium Ridgelight at 5° with Beams

Page: **76**












Module – main components





Module – electrical components



Power supply and control unit	Rain sensor	Rain and wind sensor set	Control pad	Wall switch	Switch interface (external wall switch)	Interface (external controls)
				 For ventilation  For roller blinds		
KLC 410	KLA 200	KLA S105	KLR 200/ KLR 300	KLI 311/KLI 312	KLF 050	KLF 150

Frame & sash

The main structural profiles of VELUX Modular Skylights consist of pultruded composite, containing approximately 80% continuous fibreglass threads and 20% two-component polyurethane resin.


The composite guarantees a high heat insulating performance (page 20, graph 1) and thermal stability (page 20, graph 2), as well as, excellent profile stiffness (page 21, graph 3) and strength (page 21, graph 4). Combined, the characteristics of the VELUX composite give the slim profiles self-supporting strength and an ability to

support installations of considerable size. In addition, the material is maintenance-free, non-corrosive and electrically non-conductive.


Combined with low-energy glazing units, VELUX Modular Skylights have one of the lowest overall U-values for frame and glazing assemblies on the skylight market. The inner surface is treated with white paint as standard. However, other colours are available, see page 102.



Frame and sash assembled




Frame & sash



HFC

Frame for fixed skylight module



HVC


Frame and sash for venting skylight module

Frame & sash

1 Thermal conductivity (W/mK)

– A low score means high insulating performance


Profiles used for VELUX Modular Skylights consist of pultruded fibreglass and polyurethane composite, which result in a high insulating performance.




2 Linear expansion coefficient (10⁻⁶ m/mK)

– A low score means high thermal stability

Whereas traditional skylight materials are bound to fluctuations in form due to thermal changes, the composite of VELUX Modular Skylights will maintain its dimensional properties, ensuring tightness of joints and prolonging the expected lifetime of the application.



Source: ¹⁾ Accredited external tests ²⁾ According to EN ISO 10077-2 ³⁾ Value identical to fibreglass ⁴⁾ www.engineeringtoolbox.com ⁵⁾ Internal VELUX test




Frame & sash

3 Flexural modulus (E-Modulus) (GPa)

– A high score means low deflection


The high rigidity of the pultruded composite material results in a very stiff frame and sash, ensuring reliable performance with very little deflection of the profiles and better aesthetics of the skylight.



4 Flexural strength (N/mm²)

– A high score means high strength

The very high strength of the pultruded composite material allows for design and production of longer and slimmer frame and sash profiles than traditional skylight materials allow. This enables design of large skylights with slim profiles resulting in better aesthetic performance.



Source: ¹⁾ Accredited external tests ²⁾ According to EN ISO 10077-2 ³⁾ Value identical to fibreglass ⁴⁾ www.engineeringtoolbox.com ⁵⁾ Internal VELUX test

Cladding

Cladding

Each module has a specific set of claddings. Cladding components are attached on four sides of the skylight, ensuring a watertight connection between sash and frame for both fixed and venting

modules. The cladding is made of extruded aluminium with a scratch resistant, granite grey powder coating for added weather protection and aesthetics. Other colours are available, see page 103.




Flashing


Flashing

VELUX Modular Skylights come with factory-finished flashings. The prefabrication of flashings ensures a high quality solution providing a watertight connection between roof, sub-construction and module, with a safe and fast installation process.




The flashing has a top, side and bottom section made from aluminium with a grey paint finish.

Other colours are available, see page 103.





Flashing

Standard flashing	Cross-section of the bottom flashing
<p>Standard flashing</p> <p>Standard top, bottom and side flashing suitable for a 210 mm sub-construction (measured from inside edge of the steel). See page 32.</p>	
Semi-standard flashing	Cross-section of the bottom flashing
<p>Narrow flashing</p> <p>Narrow top, bottom and side flashing that is suitable for a 150 mm wide sub-construction.</p> <p>Available at additional cost.</p> <p>Can be used for instance, if the extra slim sub-construction is required.</p>	
<p>Wide flashing</p> <p>Wide top, bottom and side flashing that is suitable for a 350 mm wide sub-construction.</p> <p>Available at additional cost.</p> <p>Can be used for instance, if the sub-construction is made of concrete and space for insulation is needed.</p>	

Glazing unit

VELUX Modular Skylights come with a low-energy double-glazing unit. Alternatively, the modules can be supplied with improved solar protection or an Argon or a Krypton filled triple-glazing unit for extra-low U-value. All glazing units include a toughened outer glass layer and a 3+3 or 5+5 mm inner safety glass layer with 2 x 0.38 mm interlayer PVB foil. For technical values on glazing units, please refer to the chapter about Product Data.

The triple-glazed units have a heat strengthened middle glass layer. For triple-glazed variants with a 5+5 mm inner pane, heat strengthened glass is used.

The cavity between the panes of the glazing units is filled with Argon or Krypton gas as a default.

All glazing units have a warm edge spacer and are produced with warm edge technology to minimise the risk of condensation and to give the glazing units the most durable insulation capabilities.




Please note that panes for intentional walkability require a dedicated walk-on product fulfilling load bearing requirements per Eurocode, national annexes to Eurocodes, further national safety guidelines and anti-slippery protection requirements.

VELUX Group does not proactively encourage walking / stepping on panes of slope products intentionally. Per request, the glazing construction and occasionally when available national certificates can be disclosed, however the decision whether customer accepts the glazing and allow walkability in use lies solely with the customer.

Glazing unit


Example of double-glazed unit (LowE)

Variant 10L



Example of triple-glazed unit (LowE)


Variant 16L



Note: Visual quality of glazing units.
Interference effects and/or effects specific to multiple glazing and/or anisotropy may occur in the visible glass surface due to the physics of the material and its production technologies.

Differentiating parameters of the coating variants

Coating options		Coating	Solar gain	Solar protection	Light transmittance	Colour rendering index
Low emissivity	When the highest light transmittance is needed and you would like to let in the heat from the sun during heating season.	LowE	☆☆☆	☆	☆☆☆	☆☆☆
Sun protection	When sun protection is required to keep out the heat from the sun for increased comfort during summer periods.	Sun1	☆☆	☆☆	☆☆	☆☆
Enhanced sun protection	When extra sun protection is required for increased comfort during summer periods and a reduced light transmittance can be accepted.	Sun2	☆	☆☆☆	☆	☆



Glazing unit

Colour renderings of double-glazed units


Additional glazing characteristics and glazing variants are shown on pages 98-100.
All mentioned values are in accordance with EN 410.



Glazing with low emissivity coating (LowE)

Variant 10L



Light transmittance: τ_v -value = 80%
Solar factor: g-value = 61%
Colour rendering index: R_a = 97



Glazing with light sun protection coating (Sun1)

Variant 11L


Light transmittance: τ_v -value = 52%
Solar factor: g-value = 28%
Colour rendering index: R_a = 84



Glazing with enhanced sun protection coating (Sun2)

Variant 12T

Light transmittance: τ_v -value = 18%
Solar factor: g-value = 17%
Colour rendering index: R_a = 92



Spectral values (wave length in nm)

Visible daylight tau

Glazing unit with low emissivity coating and roller blind RMM

Colour renderings of double-glazed units

Additional glazing characteristics and glazing variants with roller blind are shown on pages 108 and 109.


All mentioned values are in accordance with EN 410.



Glazing with low emissivity coating (LowE) and Roller Blind RMM 8806, White

Variant 10L


Light transmittance: τ_v -value = 31%
 Solar factor: g-value = 36%
 Colour rendering index: R_a = -



Glazing with low emissivity coating (LowE) and Roller Blind RMM 8805, Grey

Variant 10L


Light transmittance: τ_v -value = 8%
 Solar factor: g-value = 43%
 Colour rendering index: R_a = -



Glazing with low emissivity coating (LowE) and Roller Blind RMM 8807, Black


Variant 10L

Light transmittance: τ_v -value = 0%
 Solar factor: g-value = 37%
 Colour rendering index: R_a = -



Spectral values (wave length in nm)

Visible daylight tau



Glazing unit with fritted or opal surface

Colour renderings of double-glazed units


Additional glazing characteristics and glazing variants are shown on pages 98-100.
All mentioned values are in accordance with EN 410.



Glazing with low emissivity coating (LowE)

Variant 10L



Light transmittance: τ_v -value = 80%
Solar factor: g-value = 61%
Colour rendering index: R_a = 97



Glazing with low emissivity coating (LowE) and opal surface*

Variant 10L + opal


Light transmittance: τ_v -value = 58%
Solar factor: g-value = 58%
Colour rendering index: R_a = -



Glazing with low emissivity coating (LowE) and fritted surface*

Variant 10L + fritted

Light transmittance: τ_v -value = 80%
Solar factor: g-value = 61%
Colour rendering index: R_a = -



* Glazing with opal or fritted surface are semi-standard variants. The above values (with opal or fritted surface) are based on examples and depend on covering degree and pattern.

Brackets & hinges

Material and surface treatment

Metal components in VELUX Modular Skylights are made of galvanized steel.

The majority of the steel components are electroplated according to European norm EN ISO 2081 table A1 – C: iridescent. Components fulfill corrosion resistance grade 4 in accordance with EN ISO 1670.

Based on these properties, VELUX Modular Skylights can be used where external weather conditions and indoor climate conditions are within the normal spectre of corrosiveness.

Note: VELUX Modular Skylights standard solutions must NOT be used in indoor environments where the risk of condensation on metal components can lead to extreme corrosive attacks. These environments include facilities that use highly corrosive substances, e.g. salt and/or chloride. Evaporation can lead to corrosive attacks on components, weaken the functionality and in the end compromise the structural integrity of the installation. For use of VELUX Modular Skylights in buildings with swimming pools, specific swimming pool products are available, see page 35.

Brackets

VELUX Modular Skylights are supplied with mounting brackets and clamps and are ready to be installed on any preferred sub-construction made of steel, concrete or wood finished with a steel profile at the top. Mounting brackets are fixed during installation with a clamping system holding the skylight in place.


Using a steel profile on top of the sub-construction is an advantage, as the clamps at any time during installation can be released to allow minor positional adjustment of the modules.

If the customer chooses not to use the mounting clamps, but to screw the mounting brackets directly into the wooden batten, please note that the screws are not included in the VELUX delivery, and therefore delivery and correct dimensioning must be ensured by the customer.

Hinges

The pre-fitted hinges of the venting modules are tested under the most severe conditions, by continuously opening and closing the largest and heaviest modules.







Examples of brackets & hinges




Top bracket for Longlight 5-30°



Bottom bracket for Ridgelight at 5° with Beams.
Parallel beam with curved profile.




Bottom bracket for Longlight 5-30° and Ridgelight 25-40°



Bottom bracket for Ridgelight at 5° with Beams.
Horizontal beam with rectangular profile.



Top bracket for Northlight 25-90°



Top bracket for Wall-mounted Longlight 5-45°



Top bracket for Ridgelight at 5° with Beams





Top bracket for Ridgelight 25-40°



Clamp for fixing mounting
bracket on steel profile

Module – assembled






Sub-construction

Easy installation process

VELUX Modular Skylights require an accurate, fixed and dimensioned sub-construction. The strength of the sub-construction must also be calculated for the individual project, based on the building design and application size. It is the responsibility of the customer to have a static calculation of the sub-construction done by a static engineer.

In this way, the sub-construction is not a part of the prefabricated modular skylight system.




Wood sub-construction finished with a steel profile at the top




Wood is the most flexible choice for creating a light and economical sub-construction with maximum energy performance. However, it is not recommended for larger solutions and Ridgelight installations.

Steel sub-construction finished with a steel profile at the top




Steel offers flexibility in combination with great strength. Steel also allows a maximum amount of insulation to be used in the installation.

Concrete sub-construction finished with a steel profile at the top



Concrete provides a strong, but heavy sub-construction and is mostly suited for concrete buildings. Concrete sub-constructions are usually cast on site.



The steel profile

A steel profile is the most important link when mounting the modules to the sub-construction. Please observe that the steel profile should cover the full opening length to allow minor


positional adjustment of the modules during installation. Please also observe that the top and bottom sub-construction and therefore also the steel profile must be horizontal.




Steel profile on wood



Steel profile on steel



Steel profile on concrete



Wood profile on wood is not recommended by VELUX Commercial.

Download material and recommendations on sub-construction



See our large selections of material on Longlight, Wall-mounted Longlight, Northlight, Ridgelight, Ridgelight at 5° with Beams, Step, Longlight, Step Ridgelight, Step Ridgelight on Girder, Atrium Longlight, Atrium Ridgelight and Atrium Ridgelight at 5° with Beams

Read all about sub-constructions in the guides at: veluxcommercial.com


Vapour barrier connection strip


To ensure a high quality installation of VELUX Modular Skylights and to prevent condensation occurring within the sub-construction, it is highly recommended to install BCX vapour barrier connection strip.

The factory-finished BCX creates the perfect connection between the VELUX Modular Skylights and the vapour barrier of the building. BCX is CE-marked in accordance with EN 13984.

The vapour barrier connection strip BCX is made of a diffusion-tight polyethylene foil completed with a pre-fitted rubber gasket along one edge. With a perfect fit into the skylight frame rebate, installation is an easy job that guarantees a vapour-tight solution.

Vapour Barrier Connection Strip
(Factory-finished)





Products for swimming pool environments

When using VELUX Modular Skylights in environments like swimming pools with high levels of humidity, salt or chloride, it is crucial to ensure a vapour tight installation to prevent condensation of highly corrosive substances like salt and/or chloride that can lead to corrosive attacks on metal components.

VELUX specially designed vapour barrier connection strip, vapour barrier adhesive and inner ridge cover must be used in environments with swimming pools. Please observe any national requirements in swimming pool areas.

Vapour barrier connection strip for swimming pools

The factory-finished vapour barrier connection strip BSX developed especially for use in swimming pool environments creates the perfect connection between the VELUX Modular Skylights and the vapour barrier of the building. BSX is CE-marked in accordance with EN 13984.

BSX is made of a multilayer foil including aluminium with a very high water vapour resistance completed with a pre-fitted rubber gasket along one edge. Vapour barrier adhesive ZZZ 255 to be used together with vapour barrier connection strip.

NOTE:



Guarantee provided by VELUX for swimming pool projects is valid only when these dedicated swimming pool products are used correctly. Triple glazing is advised to minimise the risk of condensation. Roller blinds and Ridgelight at 5° with Beams are not compatible for use in swimming pool environments. For use of Northlight solutions, it is important that the roof construction is sufficiently ventilated close to the modules. Fire resistant module HFS is not compatible for use in Ridgelight solutions above swimming pools.

Inner ridge cover for swimming pools

For use of Ridgelight solutions above swimming pools, a specially designed inner ridge cover ZZZ 254 must be used.

ZZZ 254 is made of 2 mm thick extruded white EPDM rubber. Please observe that due to material properties, there is a colour difference between ZZZ 254 and the white skylight frame. Vapour barrier adhesive ZZZ 255 to be used together with inner ridge cover.

Vapour barrier connection strip for swimming pools	Vapour barrier adhesive for swimming pools	Inner ridge cover for swimming pools
		
BSX	ZZZ 255	ZZZ 254




Chain actuator

VELUX venting skylight modules are top-hung and have a hidden chain actuator integrated at the bottom profile.

For comfort ventilation there is one chain actuator variant which can be controlled with either VELUX io-homecontrol® technology and control pad KLR 200 or KLR 300 for user friendly control or your preferred ± 24 V DC open system. The chain actuator for smoke ventilation can only be controlled by a ± 24 V DC open system.

The chain stroke on the open system actuator can be reprogrammed even after installation to suit specific needs.

The chain actuator is accessible from the roof. Therefore, maintenance requires no access from the inside of the building.




Comfort venting VELUX Modular Skylights meet the requirements of the harmonised standard EN 60335-2-103(2015) as to a max opening clearance of 200 mm (by means of physical limitation of the actuator) and as to the max closing speed of 15 mm/sec. Therefore, comfort venting skylights can be installed within reach, i.e. at installation heights below 2.5 m above floor level (inside) and ground level (outside). According to EN 60335-2-103 access levels are defined as e.g. stairs and terraces. Surfaces not normally used for standing on, such as windowsills, and movable equipment such as ladders, are not considered to be access level.

Please note that the venting skylights operate with high closing force, which can cause serious injury in case of entrapment. If VELUX roller blinds are installed in the skylight, please observe recommendations in the safety instructions provided with each VELUX roller blind RMM.

We recommend that you observe national regulations and consider if the planned specific use of the building requires additional safety measures that must be applied by the installer/user to prevent serious injury.

Smoke venting VELUX Modular Skylights and comfort venting VELUX Modular Skylights with a longer chain stroke than standard have a recommended minimum installation height of 2.5 m above floor level (inside) and ground level (outside). If they are installed below this level, safety measures must be applied by the installer/user to prevent serious injury. No instruction or measure can eliminate the inherent hazards resulting from installation heights below 2.5 m.

The VELUX Group will not accept responsibility for damages, injury or death resulting from such an installation. The installer/user is ultimately responsible for own omissions and actions. Measures could for instance be to install a motion sensor that is able to disconnect power from the control unit in case of any movement in the immediate vicinity of the VELUX Modular Skylights.





Control system

VELUX io-homecontrol®

Venting modular skylights and roller blinds RMM can be powered and controlled from the VELUX control unit KLC 410. Each KLC 410 can power and operate one venting skylight module and up to four roller blinds individually, in groups or simultaneously.

Skylights and blinds installed with the VELUX KLC 410 control unit can be operated with the VELUX wall switches KLI 311/312 or control pad KLR 200/300.



Open system

Venting modular skylights and roller blinds controlled with the open system solution are connected to ± 24 V DC. In addition to ± 24 V DC, the open system skylights and roller blinds can be connected to and integrated in common building automation fieldbus systems, i.e. KNX, BACnet, LON and Modbus.

The connection to the skylight actuator is made through the integrated WindowMaster MotorLink™ technology that among other things enables exact position control and feedback.

Roller blind

The internal roller blind RMM is designed for installation with VELUX Modular Skylights, and is available in all standard module sizes above 800 mm in height. The blind protects against heat and glare and helps to control the amount of light in the room.

The blind consists of four wheels, one in each corner of the skylight module and two steel wires, running along the module side frame. The two wires pull a lightweight polyester fabric available in three commonly used colours.


To minimise the light spillage around the edges, a dim out solution with aluminium profiles fitted in module frame is available. The dim out profiles can be pre-mounted from the factory or mounted during installation on-site.

VELUX roller blinds are electrically operated and can be controlled using either VELUX io-homecontrol® or Open System $\pm 24V$ (OS $\pm 24V$ DC).

To support fast and safe installation of VELUX Modular Skylights, it is possible to order roller blinds pre-mounted from the factory, except on smoke venting modules and fire resistant modules.

VELUX Modular Skylights can be pre-fitted with cables for internal roller blinds, making the installation and connection to the module and to the power supply quick and easy. For more information, see page 107-109.


VELUX roller blinds must not be installed in areas with high humidity such as bathrooms.




The blind cloth of VELUX roller blinds is pulled on two tension steel wires on pulley wheels, which are accessible, when the roller blinds are installed on skylights within reach and therefore can cause serious injury, if a person gets in contact with this during the electrical operation of the blind. VELUX roller blinds have a recommended minimum installation height of 2.5 m above floor level (inside) and ground level (outside). In case of installation below that level, safety measures must be applied by the installer/user to prevent serious injury. No instruction or measure can eliminate the inherent hazards resulting from installation heights below 2.5 m.

We recommend you to observe national regulations and consider if the planned specific use of the building requires that additional safety measures must be applied by the installer/user to prevent serious injury.

The VELUX Group will not accept responsibility for damages, injury or death resulting from such installation. The installer/user is ultimately responsible for own omissions and actions. Measures could for instance be to install a motion sensor that is able to disconnect power from the control unit in case of any movement in the immediate vicinity of the VELUX Modular Skylights.




Fire retardant sun screening

			
Colour: Variant code	Grey RMM 8805	White RMM 8806	Black RMM 8807

Order the right size

To order the right sizes see the data plate on the VELUX Modular Skylight.
How to read the data plate, see page 43.



Beam for Ridgelight at 5°

When installing VELUX Modular Skylights in a 5° Ridgelight solution, the modules are supported by a steel beam. There are two beam design options. You can choose either the horizontal beam with rectangular profile or the parallel beam with curved profile.

The beam is included in the VELUX delivery and is ready for fast and easy installation with no further preparation.

VELUX beams are treated with final coating, white RAL 9010, gloss 30 as standard and are available for modules from 800 to 3000 mm in height.

Fire resistance

If the beam is required to meet increased demands for fire resistance, for instance used together with a fire resistant skylight module HFS, it must be treated with fire paint. If such a demand occurs, please be advised:

For up to 30 minutes of fire resistance, clients will need to:

- purchase modules with fire resistant glazing units and intumescent strip (HFS).
- purchase the corresponding beam variant coated with fire resistant paint system providing 30 minutes of resistance to fire to the whole application.


Customers are advised to inform the local VELUX sales company of such demands prior to order, as standard beams are not coated with fire resistant paint system but with standard paint as default, and the applied standard paint system is not compatible for post application of fire protection paint systems. Please note that fire paint will change the visual appearance of the beams slightly.


If there are no specific fire rating demands for the modules, but specific demands for the beams, only point b) is relevant.

Always take into consideration that it is only possible to make beams fire rated for up to 30 minutes. If fire rating demands exceed 30 minutes, 5° Ridgelight configurations are not suited for this installation.

Beam for Ridgelight at 5°

Horizontal beam with rectangular profile






Horizontal beam with rectangular profile



Parallel beam with curved profile

Beam for Ridgelight at 5°

Parallel beam with curved profile



Wind deflector for smoke ventilation modules

The wind deflectors are intended for use with smoke venting modular skylights. The wind deflectors are designed to change the wind profile over the skylights in open position, in order to minimize the risk of air intake and allow outtake of smoke even under unfavorable wind conditions, and at the same time causing the least possible visual effect on the exterior of the skylight. The wind deflectors come in two variants: KCD W00H00 0040 that covers one smoke venting module and KCD 0080 that covers three modules, one smoke venting module in the middle of two fixed modules of the same width.

The deflectors are tested together with VELUX Modular Skylights in accordance with EN 12101-2.


The wind deflector can be purchased and installed at the same time as the smoke ventilator, or they can be installed subsequently, if the skylight configuration allows this. In any case, the aerodynamic free area of the smoke ventilators is declared both with and without wind deflectors and the influence of the deflectors on the performance must be respected.

For further information on the performance of smoke venting modular skylights, the influence of the deflector on the aerodynamic free area and the design possibilities, see pages 87-97.




Wind deflector KCD 0040

Wind deflector KCD W00H00 0040 is a "multifit" single deflector for all module sizes. The deflector is installed on the smoke venting module, one deflector for each module.



Wind deflector KCD 0080

Wind deflector KCD 0080 must always be installed on a group of three skylight modules with identical width, where the middle module is the smoke ventilator and the two modules at the sides are fixed modules. This deflector is manufactured to fit the size of the three modules it is installed on.





Data plate

All VELUX Modular Skylights, electrical components and accessory products have a data plate. The data plate helps to identify the product and must NOT be removed.

If a product is damaged or malfunctioning, the information on the data plate must be given to the VELUX sales company.












Example of data plate and position



The background of the entire page is a solid blue color. Overlaid on this is a complex, white line drawing that resembles a technical architectural sketch. The drawing consists of numerous overlapping, parallel lines that create a sense of depth and perspective, suggesting a series of architectural elements like beams, walls, or a roof structure. The lines are drawn in a way that they intersect and recede into the distance, giving the impression of a three-dimensional space being explored from a low angle.


Solutions

Quick overview of skylight solutions vs. roof constructions















						
Solution*	Longlight		Wall-mounted Longlight		Northlight	
Installation pitch	5-30°		5-45°		25-90°	
HFC = fixed modules, HVC = venting modules	HFC	HVC	HFC	HVC	HFC	HVC
Opening width (Length = ∞) **	0.6 – 3.1 m	0.8 – 2.5 m	0.6 – 3.2 m	0.8 – 2.6 m	0.6 – 3.1 m	0.8 – 2.5 m
 1.2 – 2.5 m > <	✓					
Flat roof with small opening						
 2.0 – 4.5 m > <	✓					
Flat roof with medium opening						
 3.2 – 6.2 m > <						
Flat roof with large opening						
						
Flat roof with extra large opening (Atrium)						
			✓			
Flat roof up against a wall						
					✓	
Northlight						
	✓				✓	
Sloping roof with opening in the side						
						
Sloping roof with opening as ridge						

* Please note that all solutions, regardless of roof construction, require installation on a sub-construction designed according to instructions given by the VELUX Group.











** Measurements are guidelines only. Exact numbers will be supplied by your VELUX sales company.



Idea catalogue on alternative construction possibilities and light distribution


		
Longlight	Wall-mounted Longlight	Northlight
		
Daylight in both an office and a corridor	Newbuild extension with wall-mounted solution	Daylight will be restricted in a 90° solution
		
Asymmetric room with a sloping roof	Buildings with different heights	A lower pitch creates more daylight inside
		
When a sloping roof cannot carry a Ridgelight	Opens up a corridor in a building	Northlight integrated in the roof construction
		
In a shaft between two buildings	Daylight into a basement	

Quick overview of skylight solutions vs. roof constructions






				
Solution*	Ridgelight		Ridgelight at 5° with Beams	
Installation pitch	25-40°		5°	
HFC = fixed modules, HVC = venting modules	HFC	HVC	HFC	HVC
Opening width (Length = ∞) **	1.4 – 4.5 m	1.4 – 4.5 m	1.8 – 6.2 m	1.8 – 5.0 m
 1.2 – 2.5 m	✓			
Flat roof with small opening				
 2.0 – 4.5 m	✓		✓	
Flat roof with medium opening				
 3.2 – 6.2 m	✓		✓	
Flat roof with large opening				
				
Flat roof with extra large opening (Atrium)				
				
Flat roof up against a wall				
				
Northlight				
				
Sloping roof with opening in the side				
	✓			
Sloping roof with opening as ridge				

* Please note that all solutions, regardless of roof construction, require installation on a sub-construction designed according to instructions given by the VELUX Group.













** Measurements are guidelines only. Exact numbers will be supplied by your VELUX sales company.



Idea catalogue on alternative construction possibilities and light distribution


	
Ridgelight	Ridgelight at 5° with Beams
	
On top of a sloping roof	Solution for flat roof with a wide opening
	
Asymmetric Ridgelight with infill panel on south side blocking the excess sun	

Quick overview of skylight solutions vs. roof constructions









								
Solution*	Step Longlight		Step Wall-mounted Longlight		Step Ridgelight		Step Ridgelight on Girder	
Installation pitch	5-25°		5-25°		25°		5-25°	
HFC = fixed modules, HVC = venting modules	HFC	HVC	HFC	HVC	HFC	HVC	HFC	HVC
Opening width (Length = ∞) **	2.6 – 18 m	2.6 – 18 m	2,6 – 18 m	2,6 – 18 m	4.5 – 33 m	4.5 - 33 m	6 – 36 m	6 - 36 m
 1.2 – 2.5 m								
Flat roof with small opening								
 2.0 – 4.5 m								
Flat roof with medium opening								
 3.2 – 6.2 m								
Flat roof with large opening								
	✓				✓		✓	
Flat roof with extra large opening (Step solution)								
			✓					
Flat roof up against a wall								
								
Northlight								
	✓							
Sloping roof with opening in the side								
					✓		✓	
Sloping roof with opening as ridge								

* Please note that all solutions, regardless of roof construction, require installation on a sub-construction designed according to instructions given by the VELUX Group.












** Measurements are guidelines only. Exact numbers will be supplied by your VELUX sales company.



Idea catalogue on alternative construction possibilities and light distribution


			
Step Longlight	Step Wall-mounted Longlight	Step Ridgelight	Step Ridgelight on Girder
			
A roof in two levels with Step Longlight	Two buildings in different height connected by a Step Wall-mounted Longlight		
			
A roof in two levels with Step Ridgelight on Girder	A flat roof with a Step Ridgelight on Girder		

Quick overview of skylight solutions vs. roof constructions


						
Solution*	Atrium Longlight		Atrium Ridgelight		Atrium Ridgelight at 5° with Beams	
Installation pitch	5-30°		25-40°		5°	
HFC = fixed modules, HVC = venting modules	HFC	HVC	HFC	HVC	HFC	HVC
Opening width (Length = ∞) **	0.6 – 3.1 m	0.8 – 2.5 m	1.4 – 4.5 m	1.4 – 4.5 m	1.8 – 6.2 m	1.8 – 5.0 m
 1.2 – 2.5 m						
Flat roof with small opening						
 2.0 – 4.5 m						
Flat roof with medium opening						
 3.2 – 6.2 m						
Flat roof with large opening						
	✓		✓		✓	
Flat roof with extra large opening (Atrium)						
						
Flat roof up against a wall						
						
Northlight						
						
Sloping roof with opening in the side						
						
Sloping roof with opening as ridge						

* Please note that all solutions, regardless of roof construction, require installation on a sub-construction designed according to instructions given by the VELUX Group.


** Measurements are guidelines only. Exact numbers will be supplied by your VELUX sales company.



Idea catalogue on alternative construction possibilities and light distribution




Atrium Longlight




Atrium Ridgelight




Atrium Ridgelight at 5°
with Beams



Atrium Longlight with internal sun screening. Design ideas like internal vertical sun screening are not supplied by the VELUX Group



Atrium Longlight with external sun screening. Design ideas like vertical sun screening are not supplied by the VELUX Group



Atrium Longlight with sun louvers. Design ideas like sun louvers are not supplied by the VELUX Group

Longlight 5-30°

Longlights are bands of VELUX Modular Skylights, supplied with installation brackets and clamps that guarantee a fast and secure installation. The prefabricated flashing allows for configurations with a pitch of 5 to 30°.

Longlights are mounted on a standard steel profile, 100 mm wide (not a VELUX component). The brackets are fixed with a clamping system holding the skylights in place. It is also possible to install the mounting brackets of a Longlight directly onto a wooden batten without using the clamps.



Download
CAD & BIM
objects




Sub-construction
for Longlight at:
veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 1875 mm

Result:
 $\alpha 1$: H = 1800 mm at an installation pitch of **13°**
or
 $\alpha 2$: H = 2000 mm at an installation pitch of **28°**





H: Module height
 α : Installation pitch
A: Opening width
B: Opening length





Sectional drawings




Wall-mounted Longlight 5-45°

Wall-mounted Longlights are bands of VELUX Modular Skylights mounted against a vertical wall. As the skylight modules are supplied with installation brackets and clamps, a fast and secure installation is guaranteed. The flashing allows for configurations with a pitch of 5° to 45°.

Wall-mounted Longlights are mounted on a standard steel profile, 100 mm wide at the wall. At the bottom, you can choose to mount the skylights on either a steel profile using the clamping system or directly onto a wooden batten without using the clamps. The steel profiles and wooden battens are not VELUX components. Please observe a max. 3 m wall height above skylight module.

Download
CAD & BIM
objects




Sub-construction for
Wall-mounted Longlight at:
veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 1700 mm

Result:
α1: H = 1600 mm at an installation pitch of 20°
or
α2: H = 1800 mm at an installation pitch of 31°
or
α3: H = 2000 mm at an installation pitch of 39°
or
α4: H = 2200 mm at an installation pitch of 44°





H: Module height
α: Installation pitch
A: Opening width
B: Opening length





Sectional drawings



Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.



Northlight 25-90°

Similar to Longlights, Northlights are bands of VELUX Modular Skylights. The characteristic upright design is primarily for installations that are directed towards the northern hemisphere for soft and reflected lighting. Northlight installations are applicable for a pitch of 25 to 90°.

At the bottom, Northlights are mounted on a standard steel profile, 100 mm wide (not a VELUX component) and fixed with clamps holding the skylight in place. At the top, the brackets are fixed to the sub-construction with screws meant for wood.

The prefabricated modular flashing ensures easy integration in the roof surface. All flashings are easily installed. The roof surface underneath the flashing must be appropriate for screw fixation.

Please observe a max. 10 m wall height above skylight module, when installed in a sloped roof. Take notice that the top flashing changes in size above and below 54°, see sectional drawing page 59.



Sub-construction for
Northlight at:
veluxcommercial.com


Defining module size to your project

Example:

$\alpha 1$: $H = 1600$ mm at an installation pitch of **50°**



$A_{max} = 1680$ mm

$A_{min} = 1566$ mm




H: Module height
 α : Installation pitch
A: Opening width
B: Opening length



Installation pitch **α**



$A_{max} \leq H + 80$ mm
 $A_{min} \geq H - 34$ mm



Sectional drawings



Longitudinal section


Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.

Ridgelight 25-40°


Ridgelight is a classic solution, consisting of two rows of skylights linked together at the ridge, creating a self-supporting structure. The flashing allows for installations with a pitch of 25 to 40°.

Due to horizontal forces, it is recommended to use a sub-construction of steel or concrete when mounting a Ridgelight. Ridgelights are mounted on a standard steel profile, 100 mm wide (not a VELUX component). The brackets are fixed with a clamping system holding the skylights in place. It is not recommended to fasten the mounting brackets of a Ridgelight directly onto a wooden batten with screws.

Please observe that it is the designers responsibility to calculate the correct number and size of fixing if a wooden batten is used.



Download
CAD & BIM
objects




Sub-construction
for Ridgelight at:
veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 3775 mm

Result:
 α 1: H = 2000 mm at an installation pitch of **26°**
or
 α 2: H = 2200 mm at an installation pitch of **35.5°**




H: Module height
 α : Installation pitch
A: Opening width
B: Opening length





Sectional drawings



Ridgelight at 5° with Beams (Horizontal beam with rectangular profile)

Ridgelights at 5° pitch guarantee the illusion of a small glass roof with discreet transverse horizontal supporting beams. The prefabricated VELUX beam supports the skylights and creates

the 5° pitch. The beams are mounted on a standard steel profile, 100 mm wide (not a VELUX component), on top of the sub-construction.




Sub-construction for Ridgelight at 5° with Beams at: veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 4975 mm

Result:
α: H = 2400 mm at an installation pitch of 5°




- H: Module height
- α: Installation pitch
- A: Opening width
- B: Opening length






Sectional drawings



Cross-section – bottom

Cross-section – bottom



Longitudinal section

Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.

Ridgelight at 5° with Beams (Parallel beam with curved profile)

Ridgelights at 5° pitch guarantee the illusion of a small glass roof with discreet transverse parallel supporting beams. The prefabricated VELUX beam supports the skylights and creates

the 5° pitch. The beams are mounted on a standard steel profile, 100 mm wide (not a VELUX component), on top of the sub-construction.




Sub-construction for Ridgelight at 5° with Beams at: veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 4975 mm

Result:
α: H = 2400 mm at an installation pitch of 5°





- H: Module height
- α: Installation pitch
- A: Opening width
- B: Opening length





Sectional drawings



Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.


Step Longlight 5-25°

Longlights in a Step solution are multiple rows of VELUX Modular Skylights installed close to each other using joint brackets and a clamping system that guarantee a fast and secure installation. The prefabricated flashing allows for configurations with a pitch of 5 to 25°.

The Longlight Step solution is mounted on 100 mm wide standard steel profiles (not a VELUX component).

Please note that the same installation pitch is required on all rows and that the maximum distance from the top of the lowest row of the modules to the top of total skylight is 15 metres.

The supporting beams between the rows are not included in the VELUX delivery. The support structure must be designed by a structural engineer.



Download
CAD & BIM
objects




Sub-construction for
Step Longlight 5-25° at:
veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 7000 mm

Result:
 $\alpha 1$: H = 3 rows x 2200 mm at an installation pitch of **8.5°**
or
 $\alpha 2$: H = 3 rows x 2400 mm at an installation pitch of **23.5°**




H: Module height
 α : Installation pitch
A: Opening width
B: Opening length





Sectional drawings




Step Wall-mounted Longlight 5-25°

A Step solution consisting of multiple rows of VELUX Modular Skylights installed as Step Wall-mounted Longlight, where the modules are installed against a vertical wall in the top. The rows are installed close to each other using joint brackets and a clamping system that guarantee a fast and secure installation. The prefabricated flashings allows for configurations with a pitch of 5 to 25°.


The Wall-mounted Longlight Step solution is mounted on 100 mm wide standard steel profiles (not a VELUX component).

Please note that the same installation pitch is required on all rows and the maximum distance from the top of the vertical wall to the top of the lowest row of modules is 15 metres.

The supporting beams between the rows are not included in the VELUX delivery. The support structure must be designed by a structural engineer.



Download
CAD & BIM
objects



Sub-construction for
Step Wall-mounted Longlight 5-25°
veluxcommercial.com

Design your own grand ideas – Create a magnificent skylight


Ready to know if your ideas can become a reality?

Let us calculate your possibilities and give a price estimate for your chosen solution.



Contact your VELUX sales office for more details.



Sub-construction quality assurance (QA) document and specification document.



Sectional drawings




Step Ridgelight 25°

A Step Ridgelight 25° consist of a Ridgelight with one or more rows of modules below, on one or both sides, mounted close to each other using joint brackets and a clamping system that guarantee a fast and secure installation. The prefabricated flashing allows for configurations with a pitch of 25°


The Ridgelight Step solution is mounted on 100 mm wide standard steel profiles (not a VELUX component).

Please note that the same installation pitch is required on all rows and that the maximum distance from the top of the lowest row of the modules to the top of total skylight is 15 metres.

The supporting beams between the rows are not included in the VELUX delivery. The support structure must be designed by a structural engineer.



Download
CAD & BIM
objects



Sub-construction for
Step Ridgelight at 25° at:
veluxcommercial.com

Design your own grand ideas – Create a magnificent skylight


Ready to know if your ideas can become a reality?

Let us calculate your possibilities and give a price estimate for your chosen solution.



Contact your VELUX sales office for more details.



Sub-construction quality assurance (QA) document and specification document.



Sectional drawings



Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.

Step Ridgelight 5-25° on Girder


A Step Ridgelight 5-25° on Girder, consist of a Ridgelight with one or more rows of modules below, on one or both sides, mounted close to each other using joint brackets and a clamping system that guarantee a fast and secure installation. The prefabricated flashing allows for configurations with a pitch of 5° or 25°.

The Step Ridgelight 5-25° on Girder solutions are mounted on 100 mm wide standard steel profiles (not a VELUX component).

Please note that the same installation pitch is required on all rows on the same side, however different installation pitches is possible on each side of the girder.

The maximum distance from the top of the lowest row of the modules to the top of total skylight is 15 metres.


The supporting beams between the rows are not included in the VELUX delivery. The support structure must be designed by a structural engineer.



Download
CAD & BIM
objects



Sub-construction for
Step Ridgelight 5-25° on Girder at:
veluxcommercial.com



Design your own grand ideas – Create a magnificent skylight


Ready to know if your ideas can become a reality?

Let us calculate your possibilities and give a price estimate for your chosen solution.


Contact your VELUX sales office for more details.



Sub-construction quality assurance (QA) document and specification document.




Sectional drawings



Cross-section - bottom

Cross-section - bottom



Longitudinal section

Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.


Atrium Longlight

An Atrium solution consists of several Longlights attached to each other in the sub-construction. A drainage gutter separates each assembly.

The supporting beams are not included in the VELUX delivery. The support structure is part of the primary structure of the building and will have to be designed by a structural engineer.

The distance between the skylights depends on thickness of insulation, width of drainage gutter and pitch of skylights. The shown example of an Atrium is designed with 100 mm insulation and a 400 mm wide drainage gutter in a 5° pitch, resulting in a distance between skylights of 820 mm.

Download
CAD & BIM
objects




Sub-construction
for Atrium Longlight at:
veluxcommercial.com


Use the table to define module height (H) and/or installation pitch (α).


Example:
A = 2870 mm

Result:
α1: H = 2800 mm at an installation pitch of 10°
or
α2: H = 3000 mm at an installation pitch of 23°




H: Module height
α: Installation pitch
A: Opening width
B: Opening length






Sectional drawings



Cross-section – bottom



Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.

Atrium Ridgelight & Atrium Ridgelight at 5° with Beams

An Atrium Ridgelight solution consists of several Ridgelights attached to each other in the sub-construction. A drainage gutter separates each strip.

The supporting steel beams are not included in the VELUX delivery. The support structure is part of the primary structure of a building and must be designed by a structural engineer.


The distance between the skylights depends on thickness of insulation, width of drainage gutter and pitch of skylights. The shown example of an Atrium is designed with 100 mm insulation and a 400 mm wide drainage gutter in a 5° pitch, resulting in a distance between the skylights of 820 mm.




Use the table to define module height (H) and/or installation pitch (α).



Example:
 $A = 3775 \text{ mm}$

Result:
 α_1 : $H = 1800 \text{ mm}$ at an installation pitch of 5°
 α_2 : $H = 2000 \text{ mm}$ at an installation pitch of 26°
 or
 α_3 : $H = 2200 \text{ mm}$ at an installation pitch of 35.5°





Sectional drawings



Please observe that a lateral slope on the modules is NOT possible, therefore top and bottom sub-construction must be horizontal.



For longitudinal section drawings for Atrium Ridgelight and Atrium Ridgelight 5°, see pages 61, 63 and 65.

Class 1

15

12.5

10

Class 2

6.75

Product Data

5.0

Class 3

2.5

2.2

2.0

Skylight module



Essential characteristic performances for CE-marked skylight modules (EN 14351-1)		
H-C -----		
Essential characteristics	Performance	
Resistance to wind load	Class C5 ¹⁾	
Resistance to snow load	See glazing variant construction	
Reaction to Fire*	Class B, s1-d0 - B, s1-d2 **	
External fire performance***	B _{ROOF} (t1) ; B _{ROOF} (t4)	
Watertightness****	E1200	
Impact resistance	NPD	
Load-bearing capacity of safety devices	NPD ²⁾	
Acoustic performance	35 (-1; -5) - 38 (-1; -4) dB ³⁾	
Thermal transmittance	Double glazing 1.3-1.5 W/m ² K ³⁾	Triple glazing: 0.86-1.1 W/m ² K ³⁾
Solar factor	0.61 - 0.14 ³⁾	
Light transmittance	0.80 - 0.16 ³⁾	
Air permeability*****	Class 4	

¹⁾ For sizes up to 2400 mm height, except HVC 090220, HVC 090240, HVC 100220 and HVC 100240 with glazing variants 10L and 11L, which have Class C4. For skylight height > 2400 mm: NPD.

²⁾ No safety device on VELUX Modular Skylights

³⁾ For specific types and sizes, see the table with glazing variants on page 100

Note:

The performances in the above table and the attached notes to these are valid for the size grid shown on page 9.

For sizes outside the size grid, altering performances may apply. The changes in performances depend on the actual size and are therefore to be identified individually.

* For explanation of test method and results, please refer to section on Reaction to Fire

** Variants with inner pane of 55.2 lamination have a sub-class s1,d0

Variants with inner pane of 33.2 and 44.2 lamination have a sub-class s1,d2

*** For explanation of test method and results, please refer to section on External fire performance

**** For explanation of test method and results, please refer to section on Watertightness

***** For explanation of test method and results, please refer to section on Air Permeability

Performance of fire resistant skylight modules (EN 13501-2 + A1)		
HFS -----		
Essential characteristics	Performance	
Resistance to Fire HFS (fixed)	REI30	

Note:

The fixed fire resistant modules HFS are tested in accordance with EN 1365-2. The classifications are expressed in accordance with EN 13501-2 + A1. The tests are carried out without roller blinds by default. If a customer wishes to install roller blinds on the fire resistant modules subsequently, the VELUX Group recommends that the customer obtains written approval from the local fire authorities. HFS has an intumescent seal strip between the fire resistant glazing and frame and between the modules. The strip expands when exposed to heat in order to contain the fire for a longer time. For more information on the performance characteristics of fire resistant skylight modules, see pages 100 and 117.

- When installing the fixed fire resistant modules HFS, the special HFS installation instructions regarding sealant and protection of the lining / bracket area must be followed. The obtained REI 30 classification of HFS is only valid if the instructions are strictly followed.
- It is the responsibility of the customer that the sub-construction meets the required fire resistance performance of the roof.
- When installing the fixed fire resistant modules HFS in combination with a Step solution, it is the responsibility of the user that the supporting structures between module lines are also designed to meet the fire resistance requirements of the roof construction, therefore not causing weak chain in the performance of the HFS module applications.

* For explanation of test method and results, please refer to section of Reaction to Fire
 ** Variants with inner pane of 55.2 lamination have a sub-class s1,d0
 Variants with inner pane of 33.2 and 44.2 lamination have a sub-class s1,d2

See tables on the next four pages.

Skylight module



Opening under load

Glazing unit construction with a total glass thickness of 12 mm																	
Product ID			HVC 067---			HVC 075---			HVC 080---			HVC 090---			HVC 100---		
	Size [mm]	Width	675			750			800			900			1000		
	Height	Motor program	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]
HVC ---080	800	N0800	353	2.5	2023	353	2.5	1808	353	2.5	1685	353	2.5	1476	353	2.5	1305
		N1000		3.0	2643		3.0	2373		3.0	2218		3.0	1955		3.0	1740
		N1100		3.0	2952		3.0	2655		3.0	2484		3.0	2194		3.0	1958
		N1200		3.0	3262		3.0	2937		3.0	2751		3.0	2434		3.0	2175
		N1300		3.0	3572		3.0	3219		3.0	3017		3.0	2674		3.0	2393
HVC ---100	1000	N0800	410	2.5	1573	410	2.5	1400	439	2.5	1300	439	2.5	1132	439	2.5	994
		N1000		3.0	2073		3.0	1856		3.0	1731		3.0	1519		3.0	1346
		N1100		3.0	2323		3.5	2084		3.5	1946		3.5	1712		3.5	1521
		N1200		3.0	2574		3.5	2311		3.5	2161		3.5	1906		3.5	1697
		N1300		4.0	2824		3.5	2539		3.5	2376		3.5	2099		3.5	1873
HVC ---120	1200	N0800	410	2.5	1268	410	3.0	1123	526	3.0	1040	526	3.0	899	526	3.0	783
		N1000		3.0	1687		3.0	1505		3.5	1401		3.5	1223		3.5	1078
		N1100		3.0	1897		3.5	1696		3.5	1581		3.5	1386		3.5	1226
		N1200		3.0	2107		3.5	1888		4.0	1762		4.0	1548		4.0	1373
		N1300		4.0	2317		4.0	2079		4.0	1942		4.0	1710		4.0	1521
HVC ---140	1400	N0800	410	2.5	1047	410	3.0	923	530	3.0	851	610	3.5	730	610	3.5	631
		N1000		3.0	1409		3.0	1252		3.5	1162		4.0	1010		4.0	885
		N1100		3.0	1589		3.5	1417		3.5	1318		4.0	1150		4.0	1012
		N1200		3.0	1770		3.5	1581		4.0	1473		4.0	1289		4.0	1139
		N1300		4.0	1951		4.0	1746		4.0	1629		4.0	1429		4.0	1266
HVC ---160	1600	N0800	410	2.5	880	410	3.0	771	530	3.0	709	610	3.5	603	700	3.5	516
		N1000		3.0	1198		3.0	1061		3.5	982		4.0	848		4.0	739
		N1100		3.0	1357		3.5	1205		3.5	1119		4.0	971		4.5	851
		N1200		3.0	1515		3.5	1350		4.0	1255		4.0	1094		4.5	962
		N1300		4.0	1674		4.0	1495		4.0	1392		4.0	1217		5.0	1074
HVC ---180	1800	N0800	410	2.5	750	410	3.0	653	530	3.0	598	610	3.5	503	700	3.5	426
		N1000		3.0	1033		3.0	911		3.5	841		4.0	722		4.0	625
		N1100		3.0	1174		3.5	1040		3.5	963		4.0	832		4.5	724
		N1200		3.0	1316		3.5	1169		4.0	1084		4.0	941		4.5	824
		N1300		4.0	1457		4.0	1298		4.0	1206		4.0	1050		5.0	923
HVC ---200	2000	N0800	410	2.5	645	410	3.0	558	530	3.0	508	610	3.5	423	700	3.5	354
		N1000		3.0	900		3.0	790		3.5	727		4.0	621		4.0	533
		N1100		3.0	1028		3.5	907		3.5	837		4.0	719		4.5	623
		N1200		3.0	1156		3.5	1023		4.0	947		4.0	818		4.5	712
		N1300		4.0	1283		4.0	1139		4.0	1057		4.0	917		5.0	802
HVC ---220	2200	N0800	410	2.5	559	410	3.0	480	530	3.0	434	610	3.5	357	700	3.5	294
		N1000		3.0	791		3.0	692		3.5	634		4.0	537		4.0	458
		N1100		3.0	908		3.5	797		3.5	734		4.0	627		4.5	539
		N1200		3.0	1024		3.5	903		4.0	834		4.0	717		4.5	621
		N1300		4.0	1140		4.0	1009		4.0	934		4.0	807		5.0	703
HVC ---240	2400	N800	410	2.5	487	410	3.0	414	530	3.0	373	610	3.5	302	700	3.5	245
		N1000		3.0	700		3.0	609		3.5	556		4.0	467		4.0	395
		N1100		3.0	807		3.5	706		3.5	648		4.0	550		4.5	469
		N1200		3.0	914		3.5	803		4.0	740		4.0	632		4.5	544
		N1300		4.0	1020		4.0	900		4.0	832		4.0	715		5.0	619

The tables illustrate the performance for modules opening under load in accordance with EN 12101-2. The provided performance is NOT equal to structural load bearing capacity of an actual application. The design of a roof light must therefore be dimensioned to fit the specific building project, local architectural style and practice.

Standard size.
 Special sizes, functional limitations may apply.

Technical specifications			
Product range	HVC 067---	HVC 075---	HVC 080---
Product range	HVC 090---	HVC 100---	HVC 110---
Product range	HVC 120---	HVC 130---	HVC 140---
Product range	HVC 150---	HVC 160---	HVC 170---
Product range	HVC 180---	HVC 190---	HVC 200---
Product range	HVC 210---	HVC 220---	HVC 230---
Product range	HVC 240---	HVC 250---	HVC 260---
Product range	HVC 270---	HVC 280---	HVC 290---
Product range	HVC 300---	HVC 310---	HVC 320---
Product range	HVC 330---	HVC 340---	HVC 350---
Product range	HVC 360---	HVC 370---	HVC 380---
Product range	HVC 390---	HVC 400---	HVC 410---
Product range	HVC 420---	HVC 430---	HVC 440---
Product range	HVC 450---	HVC 460---	HVC 470---
Product range	HVC 480---	HVC 490---	HVC 500---
Product range	HVC 510---	HVC 520---	HVC 530---
Product range	HVC 540---	HVC 550---	HVC 560---
Product range	HVC 570---	HVC 580---	HVC 590---
Product range	HVC 600---	HVC 610---	HVC 620---
Product range	HVC 630---	HVC 640---	HVC 650---
Product range	HVC 660---	HVC 670---	HVC 680---
Product range	HVC 690---	HVC 700---	HVC 710---
Product range	HVC 720---	HVC 730---	HVC 740---
Product range	HVC 750---	HVC 760---	HVC 770---
Product range	HVC 780---	HVC 790---	HVC 800---
Product range	HVC 810---	HVC 820---	HVC 830---
Product range	HVC 840---	HVC 850---	HVC 860---
Product range	HVC 870---	HVC 880---	HVC 890---
Product range	HVC 900---	HVC 910---	HVC 920---
Product range	HVC 930---	HVC 940---	HVC 950---
Product range	HVC 960---	HVC 970---	HVC 980---
Product range	HVC 990---	HVC 1000---	HVC 1010---
Product range	HVC 1020---	HVC 1030---	HVC 1040---
Product range	HVC 1050---	HVC 1060---	HVC 1070---
Product range	HVC 1080---	HVC 1090---	HVC 1100---
Product range	HVC 1110---	HVC 1120---	HVC 1130---
Product range	HVC 1140---	HVC 1150---	HVC 1160---
Product range	HVC 1170---	HVC 1180---	HVC 1190---
Product range	HVC 1200---	HVC 1210---	HVC 1220---
Product range	HVC 1230---	HVC 1240---	HVC 1250---
Product range	HVC 1260---	HVC 1270---	HVC 1280---
Product range	HVC 1290---	HVC 1300---	HVC 1310---
Product range	HVC 1320---	HVC 1330---	HVC 1340---
Product range	HVC 1350---	HVC 1360---	HVC 1370---
Product range	HVC 1380---	HVC 1390---	HVC 1400---
Product range	HVC 1410---	HVC 1420---	HVC 1430---
Product range	HVC 1440---	HVC 1450---	HVC 1460---
Product range	HVC 1470---	HVC 1480---	HVC 1490---
Product range	HVC 1500---	HVC 1510---	HVC 1520---
Product range	HVC 1530---	HVC 1540---	HVC 1550---
Product range	HVC 1560---	HVC 1570---	HVC 1580---
Product range	HVC 1590---	HVC 1600---	HVC 1610---
Product range	HVC 1620---	HVC 1630---	HVC 1640---
Product range	HVC 1650---	HVC 1660---	HVC 1670---
Product range	HVC 1680---	HVC 1690---	HVC 1700---
Product range	HVC 1710---	HVC 1720---	HVC 1730---
Product range	HVC 1740---	HVC 1750---	HVC 1760---
Product range	HVC 1770---	HVC 1780---	HVC 1790---
Product range	HVC 1800---	HVC 1810---	HVC 1820---
Product range	HVC 1830---	HVC 1840---	HVC 1850---
Product range	HVC 1860---	HVC 1870---	HVC 1880---
Product range	HVC 1890---	HVC 1900---	HVC 1910---
Product range	HVC 1920---	HVC 1930---	HVC 1940---
Product range	HVC 1950---	HVC 1960---	HVC 1970---
Product range	HVC 1980---	HVC 1990---	HVC 2000---

Skylight module



Opening under load

Glazing unit construction with a total glass thickness of 14 mm																	
Product ID			HVC 067---			HVC 075---			HVC 080---			HVC 090---			HVC 100---		
	Size [mm]	Width	675			750			800			900			1000		
	Height	Motor program	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain s'troke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]
HVC ---080	800	N0800	353	2.5	1984	353	2.5	1768	353	2.5	1644	353	2.5	1434	353	2.5	1263
		N1000		3.0	2603		3.0	2332		3.0	2177		3.0	1913		3.0	1698
		N1100		3.0	2913		3.0	2615		3.0	2444		3.0	2153		3.0	1916
		N1200		3.0	3223		3.0	2897		3.0	2710		3.0	2393		3.0	2133
		N1300		3.0	3533		3.0	3179		3.0	2976		3.0	2632		3.0	2351
HVC ---100	1000	N0800	410	2.5	1533	439	2.5	1359	439	2.5	1260	439	2.5	1090	439	2.5	952
		N1000		3.0	2034		3.0	1815		3.0	1690		3.0	1477		3.0	1303
		N1100		3.0	2284		3.5	2043		3.5	1905		3.5	1671		3.5	1479
		N1200		3.0	2534		3.5	2271		3.5	2120		3.5	1864		3.5	1655
		N1300		4.0	2785		3.5	2499		3.5	2336		3.5	2058		3.5	1831
HVC ---120	1200	N0800	410	2.5	1228	460	3.0	1082	526	3.0	999	526	3.0	857	526	3.0	741
		N1000		3.0	1648		3.0	1465		3.5	1360		3.5	1182		3.5	1036
		N1100		3.0	1858		3.5	1656		3.5	1540		3.5	1344		3.5	1184
		N1200		3.0	2068		3.5	1847		4.0	1721		4.0	1506		4.0	1331
		N1300		4.0	2278		4.0	2039		4.0	1902		4.0	1669		4.0	1479
HVC ---140	1400	N0800	410	2.5	1008	460	3.0	882	530	3.0	811	610	3.5	689	610	3.5	589
		N1000		3.0	1369		3.0	1212		3.5	1122		4.0	968		4.0	843
		N1100		3.0	1550		3.5	1377		3.5	1277		4.0	1108		4.0	970
		N1200		3.0	1731		3.5	1541		4.0	1432		4.0	1248		4.0	1097
		N1300		4.0	1912		4.0	1706		4.0	1588		4.0	1388		4.0	1224
HVC ---160	1600	N0800	410	2.5	841	460	3.0	731	530	3.0	668	610	3.5	561	700	3.5	474
		N1000		3.0	1159		3.0	1020		3.5	941		4.0	807		4.0	697
		N1100		3.0	1317		3.5	1165		3.5	1078		4.0	930		4.5	809
		N1200		3.0	1476		3.5	1310		4.0	1214		4.0	1052		4.5	920
		N1300		4.0	1635		4.0	1454		4.0	1351		4.0	1175		5.0	1032
HVC ---180	1800	N0800	410	2.5	711	460	3.0	613	530	3.0	557	610	3.5	462	700	3.5	384
		N1000		3.0	994		3.0	871		3.5	800		4.0	681		4.0	583
		N1100		3.0	1135		3.5	1000		3.5	922		4.0	790		4.5	682
		N1200		3.0	1277		3.5	1128		4.0	1044		4.0	899		4.5	782
		N1300		4.0	1418		4.0	1257		4.0	1165		4.0	1009		5.0	881
HVC ---200	2000	N0800	410	2.5	606	460	3.0	518	530	3.0	467	610	3.5	382	700	3.5	312
		N1000		3.0	861		3.0	750		3.5	687		4.0	579		4.0	491
		N1100		3.0	989		3.5	866		3.5	796		4.0	678		4.5	581
		N1200		3.0	1116		3.5	983		4.0	906		4.0	776		4.5	670
		N1300		4.0	1244		4.0	1099		4.0	1016		4.0	875		5.0	760
HVC ---220	2200	N0800	410	2.5	520	460	3.0	439	530	3.0	394	610	3.5	316	700	3.5	252
		N1000		3.0	752		3.0	651		3.5	594		4.0	495		4.0	415
		N1100		3.0	868		3.5	757		3.5	693		4.0	585		4.5	497
		N1200		3.0	984		3.5	863		4.0	793		4.0	675		4.5	579
		N1300		4.0	1101		4.0	969		4.0	893		4.0	765		5.0	660
HVC ---240	2400	N800	410	2.5	447	460	3.0	374	530	3.0	332	610	3.5	261	700	3.5	202
		N1000		3.0	661		3.0	569		3.5	516		4.0	426		4.0	352
		N1100		3.0	768		3.5	666		3.5	607		4.0	508		4.5	427
		N1200		3.0	874		3.5	763		4.0	699		4.0	591		4.5	502
		N1300		4.0	981		4.0	860		4.0	791		4.0	673		5.0	577

The tables illustrate the performance for modules opening under load in accordance with EN 12101-2. The provided performance is NOT equal to structural load bearing capacity of an actual application. The design of a roof light must therefore be dimensioned to fit the specific building project, local architectural style and practice.

Standard size. Special sizes, functional limitations may apply.

Skylight module



Opening under load

Glazing unit construction with a total glass thickness of 18 mm																	
Product ID			HVC 067---			HVC 075---			HVC 080---			HVC 090---			HVC 100---		
	Size [mm]	Width	675			750			800			900			1000		
	Height	Motor program	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]
HVC ---080	800	N0800	353	2.5	1911	353	2.5	1693	353	2.5	1569	353	2.5	1357	353	2.5	1184
		N1000		3.0	2530		3.0	2258		3.0	2102		3.0	1836		3.0	1620
		N1100		3.0	2840		3.0	2540		3.0	2368		3.0	2076		3.0	1837
		N1200		3.0	3150		3.0	2822		3.0	2634		3.0	2316		3.0	2055
		N1300		3.0	3460		3.0	3105		3.0	2901		3.0	2555		3.0	2273
HVC ---100	1000	N0800	410	2.5	1459	439	2.5	1284	439	2.5	1183	439	2.5	1012	439	2.5	872
		N1000		3.0	1960		3.0	1740		3.0	1613		3.0	1399		3.0	1224
		N1100		3.0	2210		3.5	1968		3.5	1829		3.5	1593		3.5	1400
		N1200		3.0	2460		3.5	2196		3.5	2044		3.5	1786		3.5	1576
		N1300		4.0	2710		3.5	2424		3.5	2259		3.5	1980		3.5	1751
HVC ---120	1200	N0800	410	2.5	1153	460	3.0	1006	526	3.0	921	526	3.0	778	526	3.0	661
		N1000		3.0	1573		3.0	1388		3.5	1282		3.5	1103		3.5	956
		N1100		3.0	1783		3.5	1580		3.5	1463		3.5	1265		3.5	1103
		N1200		3.0	1993		3.5	1771		4.0	1644		4.0	1427		4.0	1251
		N1300		4.0	2203		4.0	1962		4.0	1824		4.0	1590		4.0	1398
HVC ---140	1400	N0800	410	2.5	932	460	3.0	805	530	3.0	733	610	3.5	609	610	3.5	508
		N1000		3.0	1294		3.0	1135		3.5	1044		4.0	889		4.0	762
		N1100		3.0	1475		3.5	1299		3.5	1199		4.0	1028		4.0	889
		N1200		3.0	1655		3.5	1464		4.0	1354		4.0	1168		4.0	1016
		N1300		4.0	1836		4.0	1629		4.0	1510		4.0	1308		4.0	1143
HVC ---160	1600	N0800	410	2.5	765	460	3.0	654	530	3.0	590	610	3.5	481	700	3.5	393
		N1000		3.0	1083		3.0	943		3.5	863		4.0	727		4.0	616
		N1100		3.0	1241		3.5	1088		3.5	999		4.0	850		4.5	727
		N1200		3.0	1400		3.5	1232		4.0	1136		4.0	972		4.5	839
		N1300		4.0	1559		4.0	1377		4.0	1272		4.0	1095		5.0	950
HVC ---180	1800	N0800	410	2.5	634	460	3.0	535	530	3.0	478	610	3.5	381	700	3.5	302
		N1000		3.0	917		3.0	793		3.5	721		4.0	600		4.0	501
		N1100		3.0	1059		3.5	922		3.5	843		4.0	710		4.5	600
		N1200		3.0	1200		3.5	1051		4.0	965		4.0	819		4.5	700
		N1300		4.0	1342		4.0	1179		4.0	1086		4.0	928		5.0	799
HVC ---200	2000	N0800	410	2.5	529	460	3.0	440	530	3.0	388	610	3.5	301	700	3.5	230
		N1000		3.0	784		3.0	672		3.5	608		4.0	498		4.0	409
		N1100		3.0	912		3.5	788		3.5	717		4.0	597		4.5	499
		N1200		3.0	1040		3.5	905		4.0	827		4.0	696		4.5	588
		N1300		4.0	1167		4.0	1021		4.0	937		4.0	794		5.0	678
HVC ---220	2200	N0800	410	2.5	443	460	3.0	361	530	3.0	314	610	3.5	235	700	3.5	170
		N1000		3.0	675		3.0	573		3.5	514		4.0	415		4.0	333
		N1100		3.0	792		3.5	679		3.5	614		4.0	504		4.5	415
		N1200		3.0	908		3.5	785		4.0	714		4.0	594		4.5	496
		N1300		4.0	1024		4.0	891		4.0	814		4.0	684		5.0	578
HVC ---240	2400	N800	410	2.5	371	460	3.0	296	530	3.0	253	610	3.5	180	700	3.5	120
		N1000		3.0	584		3.0	490		3.5	436		4.0	345		4.0	270
		N1100		3.0	691		3.5	587		3.5	528		4.0	427		4.5	345
		N1200		3.0	797		3.5	684		4.0	620		4.0	510		4.5	420
		N1300		4.0	904		4.0	782		4.0	711		4.0	592		5.0	495
HVC ---260	2600	N0800	410	2.5	309	460	3.0	240	The tables illustrate the performance for modules opening under load in accordance with EN 12101-2. The provided performance is NOT equal to structural load bearing capacity of an actual application. The design of a roof light must therefore be dimensioned to fit the specific building project, local architectural style and practice.								
		N1000		3.0	507		3.0	420									
		N1100		3.0	605		3.5	510									
		N1200		3.0	704		3.5	599									
		N1300		4.0	802		4.0	689									
HVC ---280	2800	N0800	410	2.5	257	410	3.0	210	The tables illustrate the performance for modules opening under load in accordance with EN 12101-2. The provided performance is NOT equal to structural load bearing capacity of an actual application. The design of a roof light must therefore be dimensioned to fit the specific building project, local architectural style and practice.								
		N1000		3.0	440		3.0	350									
		N1100		3.0	532		3.0	432									
		N1200		3.0	623		3.0	513									
		N1300		4.0	715		3.0	595									

Standard size.

Special sizes, functional limitations may apply.

Only applicable for double glazing variants with -T.

Technical specifications			
Product range	HVC 067---	HVC 075---	HVC 080---
Product range	HVC 090---	HVC 100---	HVC 110---
Product range	HVC 120---	HVC 130---	HVC 140---
Product range	HVC 150---	HVC 160---	HVC 170---
Product range	HVC 180---	HVC 190---	HVC 200---
Product range	HVC 210---	HVC 220---	HVC 230---
Product range	HVC 240---	HVC 250---	HVC 260---
Product range	HVC 270---	HVC 280---	HVC 290---
Product range	HVC 300---	HVC 310---	HVC 320---
Product range	HVC 330---	HVC 340---	HVC 350---
Product range	HVC 360---	HVC 370---	HVC 380---
Product range	HVC 390---	HVC 400---	HVC 410---
Product range	HVC 420---	HVC 430---	HVC 440---
Product range	HVC 450---	HVC 460---	HVC 470---
Product range	HVC 480---	HVC 490---	HVC 500---
Product range	HVC 510---	HVC 520---	HVC 530---
Product range	HVC 540---	HVC 550---	HVC 560---
Product range	HVC 570---	HVC 580---	HVC 590---
Product range	HVC 600---	HVC 610---	HVC 620---
Product range	HVC 630---	HVC 640---	HVC 650---
Product range	HVC 660---	HVC 670---	HVC 680---
Product range	HVC 690---	HVC 700---	HVC 710---
Product range	HVC 720---	HVC 730---	HVC 740---
Product range	HVC 750---	HVC 760---	HVC 770---
Product range	HVC 780---	HVC 790---	HVC 800---
Product range	HVC 810---	HVC 820---	HVC 830---
Product range	HVC 840---	HVC 850---	HVC 860---
Product range	HVC 870---	HVC 880---	HVC 890---
Product range	HVC 900---	HVC 910---	HVC 920---
Product range	HVC 930---	HVC 940---	HVC 950---
Product range	HVC 960---	HVC 970---	HVC 980---
Product range	HVC 990---	HVC 1000---	HVC 1010---
Product range	HVC 1020---	HVC 1030---	HVC 1040---
Product range	HVC 1050---	HVC 1060---	HVC 1070---
Product range	HVC 1080---	HVC 1090---	HVC 1100---
Product range	HVC 1110---	HVC 1120---	HVC 1130---
Product range	HVC 1140---	HVC 1150---	HVC 1160---
Product range	HVC 1170---	HVC 1180---	HVC 1190---
Product range	HVC 1200---	HVC 1210---	HVC 1220---
Product range	HVC 1230---	HVC 1240---	HVC 1250---
Product range	HVC 1260---	HVC 1270---	HVC 1280---
Product range	HVC 1290---	HVC 1300---	HVC 1310---
Product range	HVC 1320---	HVC 1330---	HVC 1340---
Product range	HVC 1350---	HVC 1360---	HVC 1370---
Product range	HVC 1380---	HVC 1390---	HVC 1400---
Product range	HVC 1410---	HVC 1420---	HVC 1430---
Product range	HVC 1440---	HVC 1450---	HVC 1460---
Product range	HVC 1470---	HVC 1480---	HVC 1490---
Product range	HVC 1500---	HVC 1510---	HVC 1520---
Product range	HVC 1530---	HVC 1540---	HVC 1550---
Product range	HVC 1560---	HVC 1570---	HVC 1580---
Product range	HVC 1590---	HVC 1600---	HVC 1610---
Product range	HVC 1620---	HVC 1630---	HVC 1640---
Product range	HVC 1650---	HVC 1660---	HVC 1670---
Product range	HVC 1680---	HVC 1690---	HVC 1700---
Product range	HVC 1710---	HVC 1720---	HVC 1730---
Product range	HVC 1740---	HVC 1750---	HVC 1760---
Product range	HVC 1770---	HVC 1780---	HVC 1790---
Product range	HVC 1800---	HVC 1810---	HVC 1820---
Product range	HVC 1830---	HVC 1840---	HVC 1850---
Product range	HVC 1860---	HVC 1870---	HVC 1880---
Product range	HVC 1890---	HVC 1900---	HVC 1910---
Product range	HVC 1920---	HVC 1930---	HVC 1940---
Product range	HVC 1950---	HVC 1960---	HVC 1970---
Product range	HVC 1980---	HVC 1990---	HVC 2000---

Skylight module



Opening under load

Glazing unit construction with a total glass thickness of 22 mm																	
Product ID			HVC 067---			HVC 075---			HVC 080---			HVC 090---			HVC 100---		
	Size [mm]	Width	675			750			800			900			1000		
	Height	Motor program	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]	Chain stroke [mm]	Electric current requirement [AMP]	Snow Load [Pa]
HVC ---080	800	N0800	353	2.5	1850	353	2.5	1630	353	2.5	1504	353	2.5	1289	353	2.5	1114
		N1000		3.0	2470		3.0	2194		3.0	2037		3.0	1769		3.0	1549
		N1100		3.0	2780		3.0	2477		3.0	2303		3.0	2008		3.0	1767
		N1200		3.0	3089		3.0	2759		3.0	2569		3.0	2248		3.0	1985
		N1300		3.0	3399		3.0	3041		3.0	2836		3.0	2487		3.0	2203
HVC ---100	1000	N0800	410	2.5	1394	439	2.5	1216	439	2.5	1114	439	2.5	941	439	2.5	799
		N1000		3.0	1895		3.0	1672		3.0	1544		3.0	1328		3.0	1150
		N1100		3.0	2145		3.5	1900		3.5	1760		3.5	1521		3.5	1326
		N1200		3.0	2395		3.5	2128		3.5	1975		3.5	1715		3.5	1502
		N1300		4.0	2646		3.5	2356		3.5	2190		3.5	1908		3.5	1678
HVC ---120	1200	N0800	410	2.5	1086	460	3.0	936	526	3.0	850	526	3.0	704	526	3.0	585
		N1000		3.0	1505		3.0	1318		3.5	1211		3.5	1029		3.5	880
		N1100		3.0	1715		3.5	1510		3.5	1392		3.5	1191		3.5	1028
		N1200		3.0	1925		3.5	1701		4.0	1572		4.0	1354		4.0	1175
		N1300		4.0	2135		4.0	1892		4.0	1753		4.0	1516		4.0	1323
HVC ---140	1400	N0800	410	2.5	862	460	3.0	733	530	3.0	659	610	3.5	533	610	3.5	431
		N1000		3.0	1224		3.0	1063		3.5	970		4.0	813		4.0	685
		N1100		3.0	1405		3.5	1227		3.5	1126		4.0	953		4.0	812
		N1200		3.0	1586		3.5	1392		4.0	1281		4.0	1093		4.0	939
		N1300		4.0	1766		4.0	1557		4.0	1437		4.0	1233		4.0	1066
HVC ---160	1600	N0800	410	2.5	694	460	3.0	580	530	3.0	515	610	3.5	404	700	3.5	314
		N1000		3.0	1011		3.0	869		3.5	788		4.0	650		4.0	537
		N1100		3.0	1170		3.5	1014		3.5	925		4.0	773		4.5	649
		N1200		3.0	1329		3.5	1159		4.0	1061		4.0	895		4.5	760
		N1300		4.0	1487		4.0	1303		4.0	1198		4.0	1018		5.0	872
HVC ---180	1800	N0800	410	2.5	562	460	3.0	460	530	3.0	402	610	3.5	303	700	3.5	223
		N1000		3.0	845		3.0	718		3.5	645		4.0	522		4.0	422
		N1100		3.0	986		3.5	847		3.5	767		4.0	632		4.5	521
		N1200		3.0	1128		3.5	976		4.0	889		4.0	741		4.5	620
		N1300		4.0	1269		4.0	1105		4.0	1011		4.0	850		5.0	720
HVC ---200	2000	N0800	410	2.5	456	460	3.0	364	530	3.0	311	610	3.5	222	700	3.5	149
		N1000		3.0	711		3.0	596		3.5	531		4.0	420		4.0	329
		N1100		3.0	838		3.5	713		3.5	641		4.0	518		4.5	418
		N1200		3.0	966		3.5	829		4.0	750		4.0	617		4.5	508
		N1300		4.0	1094		4.0	945		4.0	860		4.0	716		5.0	598
HVC ---220	2200	N0800	410	2.5	368	460	3.0	285	530	3.0	237	610	3.5	155	700	3.5	89
		N1000		3.0	601		3.0	497		3.5	437		4.0	335		4.0	252
		N1100		3.0	717		3.5	602		3.5	537		4.0	425		4.5	334
		N1200		3.0	833		3.5	708		4.0	637		4.0	515		4.5	416
		N1300		4.0	950		4.0	814		4.0	737		4.0	605		5.0	497
HVC ---240	2400	N800	410	2.5	295	460	3.0	219	530	3.0	174	610	3.5	100	700	3.5	38
		N1000		3.0	509		3.0	413		3.5	358		4.0	265		4.0	188
		N1100		3.0	616		3.5	510		3.5	450		4.0	347		4.5	263
		N1200		3.0	722		3.5	607		4.0	542		4.0	430		4.5	338
		N1300		4.0	829		4.0	705		4.0	633		4.0	512		5.0	413
HVC ---260	2600	N0800	410	2.5	234	460	3.0	162	The tables illustrate the performance for modules opening under load in accordance with EN 12101-2. The provided performance is NOT equal to structural load bearing capacity of an actual application. The design of a roof light must therefore be dimensioned to fit the specific building project, local architectural style and practice.								
		N1000		3.0	431		3.0	342									
		N1100		3.0	529		3.5	432									
		N1200		3.0	628		3.5	522									
		N1300		4.0	727		4.0	612									
HVC ---280	2800	N0800	410	2.5	180	<div>Standard size.</div> <div>Special sizes, functional limitations may apply.</div>											
		N1000		3.0	364												
		N1100		3.0	455												
		N1200		3.0	547												
		N1300		4.0	639												

VETUX Commercial

Skylight module



Smoke ventilation systems



A smoke ventilation system always has a building specific design, incorporating smoke ventilators, controls, air inlets and mechanical ventilation.

Designing a smoke ventilation system is therefore a rather complex matter, which must be addressed by skilled and authorized fire engineers in order to obtain an adequate level of performance and safety.

The design covers all relevant parameters such as the location of the building, height and shape of the roof, position of ventilators on the

roof, relative position to each other, facades and doors providing air intake, mechanical ventilation, evacuation plan and escape routes, and the natural and artificial wind obstacles in the surroundings of the building.

The VELUX Group provides the essential performance characteristics of each individual CE-marked VELUX Modular Skylight in accordance with EN 12101-2, but cannot validate the functionality and safety of the complete system.



Source of images: DE 611XB549 Rapport, page 2, figure 1, and page 11

VELUX smoke venting modular skylights can be used without wind deflector in roof mounted applications, when local regulations and design conditions are allowing to do so.

VELUX wind deflector KCD is not applicable above 60° installation pitch, on so-called wall-mounted smoke ventilators. Smoke ventilators installed in this range are to be considered wind sensitive by default in accordance with EN 12101-2. When a smoke ventilator is used in wall-mounted applications i.e. above 60° installation inclination the aerodynamic area must be by default expressed without influence of side wind, therefore the use of a smoke deflector is meaningless in such applications. Wind deflector KCD is furthermore not compatible with narrow bottom flashing, Northlight flashings, Ridgelight on Pitch flashings and Step solution flashings.

Skylight module



Wind deflector KCD W00H00 0040

Material	Aluminium
Material thickness	3 mm
Surface treatment	Powder coated (60 - 120µ)
Colour	NCS S7500-N, gloss 30



Wind deflector KCD 0080

Material	Aluminium
Material thickness	3 mm
Surface treatment	Anodized
Colour	Nature anodized Optional - coloured powder coating

In accordance with EN 12101-2:


A_v [m²] Geometric area, corresponds to frame aperture area.

Smoke ventilators installed above 60° up to 90°. Wall-mounted smoke ventilators are, as per definition, wind sensitive regardless of the design.

A 3D cutaway diagram of a skylight assembly. It shows a rectangular glass panel set within a black frame. Below the frame, a thick red insulation layer is visible, followed by a white structural layer. The assembly is shown from an isometric perspective, highlighting the internal components and the sealant around the glass.

In accordance with EN 13141-1

Used to define natural ventilation performance of comfort venting modular skylights and dual purpose smoke venting modular skylights in comfort ventilation use.



In accordance with EN 12101-2

Skylight module



Table for European values

Ventilation characteristics for HVC (European values)																		
Size of Skylights	Smoke ventilation characteristics HVC-----AB														Comfort ventilation (EN13141-1)			
	Actuator chain stroke [mm]	Opening angle	Geometric area: A _v [m ²]	Discharge coefficient (C _v) (EN 12101-2)						Aerodynamic free area (A _a) [m ²] (EN 12101-2)						HVC-----CB and HVC-----AB in comfort function		
				Without deflector		With deflector type KCD 0080		With deflector type KCD 0040		Without deflector			With deflector type KCD 0080	With deflector type KCD 0040	Actuator chain stroke [mm]	Opening angle	Geometric free area: A _v [m ²]	
				without side wind	with side wind	without side wind	with side wind	without side wind	with side wind	5° ≤ installation inclination ≤ 60°		installation inclination > 60°	5° ≤ installation inclination ≤ 60°	5° ≤ installation inclination ≤ 60°				
				C _{v0}	C _{vw}	C _{v0}	C _{vw}	C _{v0}	C _{vw}	A _{a Roof} ¹⁾ without side wind ²⁾	A _{a Roof} with side wind	A _{a Wall} ³⁾	A _{a Roof} ⁴⁾	A _{a Roof} ⁴⁾				
675 x 800	353	25.0°	0.48	0.42	0.00	0.49	0.59	0.40	0.26	0.20	0.00	0.20	0.24	0.13	260	18.5°	0.16	
675 x 1000	410	23.0°	0.61	0.44	0.00	0.46	0.60	0.40	0.24	0.27	0.00	0.27	0.28	0.15	260	14.5°	0.17	
675 x 1200	410	19.5°	0.74	0.40	0.00	0.43	0.57	0.38	0.22	0.30	0.00	0.30	0.32	0.16	260	12.5°	0.19	
675 x 1400	410	16.5°	0.87	0.36	0.00	0.40	0.54	0.35	0.20	0.31	0.00	0.31	0.35	0.17	260	10.5°	0.20	
675 x 1600	410	14.5°	1.00	0.33	0.00	0.38	0.52	0.33	0.19	0.33	0.00	0.33	0.38	0.19	260	9.0°	0.22	
675 x 1800	410	13.0°	1.12	0.34	0.00	0.36	0.49	0.34	0.19	0.38	0.00	0.38	0.40	0.21	260	8.0°	0.23	
675 x 2000	410	11.5°	1.25	0.32	0.00	0.33	0.45	0.33	0.16	0.40	0.00	0.40	0.41	0.20	260	7.5°	0.25	
675 x 2200	410	10.5°	1.38	0.31	0.00	0.32	0.43	0.32	0.17	0.43	0.00	0.43	0.44	0.23	260	6.5°	0.26	
675 x 2400	410	9.5°	1.51	0.29	0.00	0.30	0.41	0.30	0.16	0.44	0.00	0.44	0.45	0.24	260	6.0°	0.28	
675 x 2600	410	9.0°	1.64	0.31	0.00	-	-	0.32	0.17	0.50	0.00	0.50	-	0.28	260	5.5°	0.29	
675 x 2800	410	8.0°	1.76	0.28	0.00	-	-	0.31	0.18	0.49	0.00	0.49	-	0.32	260	5.5°	0.31	
750 x 800	353	25.0°	0.54	0.41	0.00	0.47	0.56	0.38	0.26	0.22	0.00	0.22	0.25	0.14	260	18.5°	0.17	
750 x 1000	439	25.0°	0.68	0.46	0.00	0.49	0.61	0.40	0.24	0.31	0.00	0.31	0.33	0.16	260	14.5°	0.19	
750 x 1200	460	21.5°	0.83	0.44	0.00	0.44	0.57	0.41	0.23	0.36	0.00	0.36	0.36	0.19	260	12.5°	0.20	
750 x 1400	460	18.5°	0.97	0.39	0.00	0.41	0.54	0.38	0.22	0.38	0.00	0.38	0.40	0.21	260	10.5°	0.22	
750 x 1600	460	16.0°	1.11	0.37	0.00	0.39	0.51	0.36	0.21	0.41	0.00	0.41	0.43	0.23	260	9.0°	0.23	
750 x 1800	460	14.5°	1.25	0.36	0.00	0.37	0.50	0.35	0.19	0.45	0.00	0.45	0.46	0.24	260	8.0°	0.25	
750 x 2000	460	13.0°	1.40	0.37	0.00	0.36	0.48	0.35	0.19	0.52	0.00	0.52	0.50	0.27	260	7.5°	0.26	
750 x 2200	460	12.0°	1.54	0.37	0.00	0.34	0.46	0.36	0.19	0.57	0.00	0.57	0.52	0.29	260	6.5°	0.27	
750 x 2400	460	11.0°	1.68	0.35	0.00	0.33	0.44	0.35	0.15	0.59	0.00	0.59	0.56	0.25	260	6.0°	0.29	
750 x 2600	460	10.0°	1.83	0.33	0.00	-	-	0.33	0.16	0.60	0.00	0.60	-	0.29	260	5.5°	0.30	

¹⁾ External building surfaces with inclination of 60° or less relative to the horizontal; shed roofs and continuous roof-lights, independent of inclination angle, are considered to be part of the roofs.

²⁾ The aerodynamic area has been declared in accordance with EN 12101-2, which means the products have been tested with and without side wind. The aerodynamic area expressed without deflector is wind sensitive which therefore, in connection with the design of the smoke ventilation system, means that steps must be taken to incorporate the products as part of a total solution that can be approved by the local fire authorities. This solution could consist of, for instance, a wind direction sensor, a wind deflector or another device that ensures a sufficient aerodynamic area at all times.

It is the responsibility of the building owner – together with the local fire authorities, if necessary – to ensure the system is specified, installed and operated in accordance with current national legislation and requirements.

³⁾ External building surfaces with an inclination of more than 60° relative to the horizontal.

⁴⁾ Aerodynamic tests as outlined in EN 12101-2:2003 were conducted both with wind (C_{vw}) and without influence of wind (C_{v0}). In any case, the lower of C_{v0} and C_{vw} is used.

Product Data

Product name	VELUX Commercial Skylight	Product code	VELUX Commercial Skylight
Product description	Commercial skylight with actuator chain stroke [mm]	Product description	Commercial skylight with actuator chain stroke [mm]
Product dimensions	800 x 800, 800 x 1000, 800 x 1200, 800 x 1400, 800 x 1600, 800 x 1800, 800 x 2000, 800 x 2200, 800 x 2400	Product dimensions	800 x 800, 800 x 1000, 800 x 1200, 800 x 1400, 800 x 1600, 800 x 1800, 800 x 2000, 800 x 2200, 800 x 2400
Product weight	15 kg	Product weight	15 kg
Product material	Aluminum	Product material	Aluminum
Product finish	White	Product finish	White
Product warranty	5 years	Product warranty	5 years
Product certification	EN 12101-2	Product certification	EN 12101-2
Product installation	See installation manual	Product installation	See installation manual
Product maintenance	See maintenance manual	Product maintenance	See maintenance manual
Product accessories	See accessories manual	Product accessories	See accessories manual

Skylight module



Table for European values

Ventilation characteristics for HVC (European values)																		
Size of Skylights	Smoke ventilation characteristics HVC----- ----AB														Comfort ventilation (EN13141-1)			
	Actuator chain stroke [mm]	Opening angle	Geometric area: A _v [m²]	Discharge coefficient (C _v) (EN 12101-2)						Aerodynamic free area (A _a) [m²] (EN 12101-2)						HVC----- ----CB and HVC----- ----AB in comfort function		
				Without deflector		With deflector type KCD 0080		With deflector type KCD 0040		Without deflector		With deflector type KCD 0080	With deflector type KCD 0040	Actuator chain stroke [mm]	Opening angle	Geometric free area: A _c [m²]		
				without side wind	with side wind	without side wind	with side wind	without side wind	with side wind	5° ≤ installation inclination ≤ 60°		installation inclination > 60°	5° ≤ installation inclination ≤ 60°				5° ≤ installation inclination ≤ 60°	
				C _{v0}	C _{vw}	C _{v0}	C _{vw}	C _{v0}	C _{vw}	A _a Roof ¹⁾ without side wind ²⁾	A _a Roof with side wind	A _a Wall ³⁾	A _a Roof ⁴⁾				A _a Roof ⁴⁾	
	800 x 800	353	25.0°	0.58	0.40	0.00	0.46	0.54	0.37	0.25	0.23	0.00	0.23	0.27	0.14	260	18.5°	0.18
800 x 1000	439	25.0°	0.73	0.45	0.00	0.48	0.59	0.41	0.24	0.33	0.00	0.33	0.35	0.18	260	14.5°	0.19	
800 x 1200	526	25.0°	0.88	0.48	0.00	0.49	0.63	0.44	0.22	0.42	0.00	0.42	0.43	0.19	260	12.5°	0.21	
800 x 1400	530	21.5°	1.04	0.45	0.00	0.45	0.59	0.41	0.22	0.47	0.00	0.47	0.47	0.23	260	10.5°	0.22	
800 x 1600	530	19.0°	1.19	0.42	0.00	0.43	0.57	0.39	0.22	0.50	0.00	0.50	0.51	0.26	260	9.0°	0.24	
800 x 1800	530	16.5°	1.34	0.39	0.00	0.40	0.54	0.38	0.21	0.52	0.00	0.52	0.54	0.28	260	8.0°	0.25	
800 x 2000	530	15.0°	1.50	0.40	0.00	0.39	0.52	0.39	0.19	0.60	0.00	0.60	0.58	0.28	260	7.5°	0.27	
800 x 2200	530	13.5°	1.65	0.38	0.00	0.37	0.50	0.37	0.18	0.63	0.00	0.63	0.61	0.30	260	6.5°	0.28	
800 x 2400	530	12.5°	1.80	0.37	0.00	0.35	0.47	0.36	0.14	0.67	0.00	0.67	0.63	0.25	260	6.0°	0.30	
900 x 800	353	25.0°	0.65	0.39	0.00	0.43	0.50	0.35	0.25	0.25	0.00	0.25	0.28	0.16	260	18.5°	0.20	
900 x 1000	439	25.0°	0.83	0.44	0.00	0.45	0.57	0.39	0.23	0.36	0.00	0.36	0.37	0.19	260	14.5°	0.21	
900 x 1200	526	25.0°	1.00	0.46	0.00	0.47	0.60	0.42	0.20	0.46	0.00	0.46	0.47	0.20	260	12.5°	0.23	
900 x 1400	610	24.5°	1.17	0.47	0.00	0.47	0.62	0.42	0.18	0.55	0.00	0.55	0.55	0.21	260	10.5°	0.24	
900 x 1600	610	21.5°	1.35	0.45	0.00	0.44	0.58	0.41	0.21	0.61	0.00	0.61	0.59	0.28	260	9.0°	0.25	
900 x 1800	610	19.0°	1.52	0.43	0.00	0.42	0.55	0.41	0.20	0.65	0.00	0.65	0.64	0.30	260	8.0°	0.27	
900 x 2000	610	17.0°	1.69	0.41	0.00	0.40	0.53	0.40	0.18	0.69	0.00	0.69	0.68	0.30	260	7.5°	0.28	
900 x 2200	610	16.0°	1.86	0.40	0.00	0.40	0.52	0.40	0.16	0.75	0.00	0.75	0.75	0.30	260	6.5°	0.30	
900 x 2400	610	14.5°	2.04	0.38	0.00	0.38	0.49	0.38	0.14	0.77	0.00	0.77	0.77	0.29	260	6.0°	0.31	
1000 x 800	353	25.0°	0.73	0.37	0.00	0.40	0.47	0.33	0.25	0.27	0.00	0.27	0.29	0.18	260	18.0°	0.21	
1000 x 1000	439	25.0°	0.92	0.41	0.00	0.43	0.54	0.37	0.21	0.38	0.00	0.38	0.40	0.19	260	14.5°	0.23	
1000 x 1200	526	25.0°	1.11	0.44	0.00	0.45	0.58	0.40	0.18	0.49	0.00	0.49	0.50	0.20	260	12.5°	0.24	
1000 x 1400	610	25.0°	1.31	0.46	0.00	0.46	0.61	0.42	0.16	0.60	0.00	0.60	0.60	0.21	260	10.5°	0.26	
1000 x 1600	700	24.0°	1.50	0.47	0.00	0.46	0.60	0.44	0.17	0.71	0.00	0.71	0.69	0.26	260	9.0°	0.27	
1000 x 1800	700	22.0°	1.69	0.47	0.00	0.44	0.58	0.42	0.17	0.80	0.00	0.80	0.75	0.29	260	8.0°	0.29	
1000 x 2000	700	20.0°	1.89	0.44	0.00	0.43	0.55	0.42	0.16	0.83	0.00	0.83	0.81	0.30	260	7.5°	0.30	
1000 x 2200	700	18.0°	2.08	0.42	0.00	0.42	0.52	0.41	0.15	0.87	0.00	0.87	0.87	0.31	260	6.5°	0.31	
1000 x 2400	700	16.5°	2.27	0.39	0.00	0.40	0.51	0.39	0.13	0.89	0.00	0.89	0.91	0.30	260	6.0°	0.33	

¹⁾ External building surfaces with inclination of 60° or less relative to the horizontal; shed roofs and continuous roof-lights, independent of inclination angle, are considered to be part of the roofs.

²⁾ The aerodynamic area has been declared in accordance with EN 12101-2, which means the products have been tested with and without side wind. The aerodynamic area expressed without deflector is wind sensitive which therefore, in connection with the design of the smoke ventilation system, means that steps must be taken to incorporate the products as part of a total solution that can be approved by the local fire authorities. This solution could consist of, for instance, a wind direction sensor, a wind deflector or another device that ensures a sufficient aerodynamic area at all times.

It is the responsibility of the building owner – together with the local fire authorities, if necessary – to ensure the system is specified, installed and operated in accordance with current national legislation and requirements.

³⁾ External building surfaces with an inclination of more than 60° relative to the horizontal.

⁴⁾ Aerodynamic tests as outlined in EN 12101-2:2003 were conducted both with wind (C_{vw}) and without influence of wind (C_{v0}). In any case, the lower of C_{v0} and C_{vw} is used.

Skylight module



Other relevant aerodynamic areas

The aerodynamic areas below are outside of the scope of EN 12101-2.

They are however used nationally and referred to in national regulations and/or practical guides.

1) A_g [m^2] Geometric free area, corresponds to the minimum unobstructed opening area of the smoke ventilators.

The typical use of this parameter is to define the ventilation area of smoke ventilators when they are used as so called cold smoke exhaust ventilators, assuming that the outtake pressure is generated by mechanical extract fans or generated by a chimney stack effect. A typical use of this area is when smoke ventilators are used over staircases. National and local regulations may differ and wherever they exist, they must be followed.

Definition of the geometric free area:

Figure 1.a:
Germany: In accordance with DIN 18232

The area is calculated in relation to the use of the total unobstructed opening area of the ventilator. In case of modular skylight top-hung ventilators it equals to the front opening (A) and the side triangles (B + C).

Not identical to A_e [m^2], which is calculated in comfort opening position.

Figure 1.b:
Austria: In accordance with the Guideline TRVB S 111 + addendum 3.3.2018 to point 5.4

The area is calculated in relation to the use of the total unobstructed opening area of the ventilator with some limitations depending on the size and installation inclination and the relation of the opening angle to the installation inclination.

In case of modular skylight top-hung ventilators the value is equal to

- The front opening (A) when the $A_v \leq 1m^2$
- The front opening (A) when the $A_v > 1m^2$ and the sash remains below horizontal position
- The front opening (A) plus one of the two side triangles (B) when $A_v > 1m^2$ and the sash raises minimum up to horizontal level or above

Figure 1.c:
Belgium: In accordance with NBN S21-208-3

The area is calculated in relation to the use of the total unobstructed opening area of the ventilator. In case of modular skylight top-hung

ventilators it equals to the front opening (A).

Figure 2:
Great Britain: Free area of smoke ventilators

- Great Britain: In accordance with Approved Document B, Volume 2, Appendix C, Section 5.b, Diagram C7, figure a

The area is usable as an alternative to the first place cited Aerodynamic Free (A_a) in accordance with BS EN 12101-2 under Section 5.a. whenever it is specified in the requirements.



Smoke ventilat

In accordance with DBI 027



Smoke ventilat



Smoke ventilator

Smoke ventilat

Skylight module



Table for country specific values

Additional ventilation charateristics HVC									
Basic geometry data				Additional national smoke ventilation characteristics HVC----- ----AB					
Size of Skylights	Actuator chain stroke [mm]	Opening angle	Geometric area: A _v [m²] (EN12101-2)	Germany	Denmark	Belgium	Austria		Great Britain
				DIN 18232	DBI 027	NBN S21-208-3:2018	Guideline TRVB S 111 + addendum 3.3.2018 to point 5.4.		
				Geometric free area: A _g [m²]	Cold smoke exhaust area: A _g [m²]	Geometric free area (A) in accordance with NBN S21-208-3:2018	The installation inclination of the module is smaller than the opening angle of the sash relative to horizontal, i.e the sash raises above horizontal in fully opened position.	The installation inclination of the module is equal or larger than the opening angle of the sash relative to horizontal, i.e the sash remains below or raises maximum up to horizontal in fully opened position	The Free Area Smoke Ventilator in accordance with Approved Document B, Volume 2, Appendix D, Section 5.b, Diagram D7, figure a.
Geometric area: A _g [m²]							Geometric free area: A _g [m²] *		
675 x 800	353	25.0°	0.48	0.28	0.28	0.16	0.16	0.16	0.14
675 x 1000	410	23.0°	0.61	0.39	0.39	0.20	0.20	0.20	0.18
675 x 1200	410	19.5°	0.74	0.44	0.44	0.20	0.20	0.20	0.17
675 x 1400	410	16.5°	0.87	0.48	0.48	0.20	0.20	0.20	0.17
675 x 1600	410	14.5°	1.00	0.52	0.52	0.20	0.20	0.20	0.17
675 x 1800	410	13.0°	1.12	0.56	0.56	0.20	0.38	0.20	0.17
675 x 2000	410	11.5°	1.25	0.60	0.60	0.20	0.40	0.20	0.16
675 x 2200	410	10.5°	1.38	0.64	0.64	0.20	0.42	0.20	0.16
675 x 2400	410	9.5°	1.51	0.68	0.68	0.20	0.44	0.20	0.16
675 x 2600	410	9.0°	1.64	0.72	0.72	0.20	0.46	0.20	0.16
675 x 2800	410	8.0°	1.76	0.76	0.76	0.20	0.48	0.20	0.16
750 x 800	353	25.0°	0.54	0.30	0.30	0.18	0.18	0.18	0.16
750 x 1000	439	25.0°	0.68	0.46	0.46	0.24	0.24	0.24	0.22
750 x 1200	460	21.5°	0.83	0.55	0.55	0.26	0.26	0.26	0.23
750 x 1400	460	18.5°	0.97	0.60	0.60	0.26	0.26	0.26	0.23
750 x 1600	460	16.0°	1.11	0.65	0.65	0.26	0.45	0.26	0.22
750 x 1800	460	14.5°	1.25	0.70	0.70	0.26	0.48	0.26	0.22
750 x 2000	460	13.0°	1.40	0.75	0.75	0.26	0.50	0.26	0.22
750 x 2200	460	12.0°	1.54	0.80	0.80	0.26	0.53	0.26	0.22
750 x 2400	460	11.0°	1.68	0.85	0.85	0.26	0.55	0.26	0.22
750 x 2600	460	10.0°	1.83	0.90	0.90	0.26	0.58	0.26	0.22
800 x 800	353	25.0°	0.58	0.31	0.31	0.20	0.20	0.20	0.17
800 x 1000	439	25.0°	0.73	0.48	0.48	0.26	0.26	0.26	0.24
800 x 1200	526	25.0°	0.88	0.69	0.69	0.33	0.33	0.33	0.31
800 x 1400	530	21.5°	1.04	0.76	0.76	0.33	0.54	0.33	0.30
800 x 1600	530	19.0°	1.19	0.82	0.82	0.33	0.58	0.33	0.30
800 x 1800	530	16.5°	1.34	0.89	0.89	0.33	0.61	0.33	0.29
800 x 2000	530	15.0°	1.50	0.95	0.95	0.33	0.64	0.33	0.29
800 x 2200	530	13.5°	1.65	1.01	1.01	0.33	0.67	0.33	0.29
800 x 2400	530	12.5°	1.80	1.08	1.08	0.33	0.70	0.33	0.29

* Note that this particular calculation of the The Free Area Smoke Ventilator in accordance with Approved Document B, Volume 2, Appendix D, Section 5.b, Diagram D7, figure a. is only a secondary alternative to the in the first place cited Aerodynamic Free (Aa) in accordance with BS EN 12101-2 under Section 5.a. Furthermore, the calculation in accordance to 5.d diagram D7, figure a. cannot take into consideration individual lining depths used in specific interior design cases, which may give further limitations to the values presented above.

Product name	VELUX 1000 x 800	VELUX 1000 x 1000	VELUX 1000 x 1200	VELUX 1000 x 1400	VELUX 1000 x 1600	VELUX 1000 x 1800	VELUX 1000 x 2000	VELUX 1000 x 2200	VELUX 1000 x 2400
Product code	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product description	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product weight	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product dimensions	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product material	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product finish	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product warranty	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product installation	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400
Product maintenance	1000 x 800	1000 x 1000	1000 x 1200	1000 x 1400	1000 x 1600	1000 x 1800	1000 x 2000	1000 x 2200	1000 x 2400

Skylight module







Table for country specific values





Additional ventilation characteristics HVC									
Basic geometry data				Additional national smoke ventilation characteristics HVC-----AB					
Size of Skylights	Actuator chain stroke [mm]	Opening angle	Geometric area: A _v [m²] (EN 12101-2)	Germany	Denmark	Belgium	Austria		Great Britain
				DIN 18232	DBI 027	NBN S21-208-3:2018	Guideline TRVB S 111 + addendum 3.3.2018 to point 5.4.		
				Geometric free area: A _g [m²]	Cold smoke exhaust area: A _s [m²]	Geometric free area (A) in accordance with NBN S21-208-3:2018	The installation inclination of the module is smaller than the opening angle of the sash relative to horizontal, i.e the sash raises above horizontal in fully opened position.	The installation inclination of the module is equal or larger than the opening angle of the sash relative to horizontal, i.e the sash remains below or raises maximum up to horizontal in fully opened position	The Free Area Smoke Ventilator in accordance with Approved Document B, Volume 2, Appendix D, Section 5.b, Diagram D7, figure a.
							Geometric area: A _g [m²]		
900 x 800	353	25.0°	0.65	0.34	0.34	0.22	0.22	0.22	0.20
900 x 1000	439	25.0°	0.83	0.52	0.52	0.30	0.30	0.30	0.27
900 x 1200	526	25.0°	1.00	0.73	0.73	0.37	0.37	0.37	0.35
900 x 1400	610	24.5°	1.17	0.98	0.98	0.44	0.71	0.44	0.42
900 x 1600	610	21.5°	1.35	1.05	1.05	0.44	0.75	0.44	0.41
900 x 1800	610	19.0°	1.52	1.13	1.13	0.44	0.79	0.44	0.41
900 x 2000	610	17.0°	1.69	1.21	1.21	0.44	0.83	0.44	0.40
900 x 2200	610	16.0°	1.86	1.29	1.29	0.44	0.87	0.44	0.40
900 x 2400	610	14.5°	2.04	1.37	1.37	0.44	0.91	0.44	0.40
1000 x 800	353	25.0°	0.73	0.36	0.36	0.25	0.25	0.25	0.22
1000 x 1000	439	25.0°	0.92	0.55	0.55	0.33	0.33	0.33	0.30
1000 x 1200	526	25.0°	1.11	0.77	0.77	0.41	0.59	0.41	0.39
1000 x 1400	610	25.0°	1.31	1.02	1.02	0.49	0.76	0.49	0.47
1000 x 1600	700	24.0°	1.50	1.32	1.32	0.58	0.95	0.58	0.56
1000 x 1800	700	22.0°	1.69	1.42	1.42	0.58	1.00	0.58	0.55
1000 x 2000	700	20.0°	1.89	1.51	1.51	0.58	1.05	0.58	0.55
1000 x 2200	700	18.0°	2.08	1.61	1.61	0.58	1.10	0.58	0.54
1000 x 2400	700	16.5°	2.27	1.71	1.71	0.58	1.14	0.58	0.54



* Note that this particular calculation of the The Free Area Smoke Ventilator in accordance with Approved Document B, Volume 2, Appendix D, Section 5.b, Diagram D7, figure a. is only a secondary alternative to the in the first place cited Aerodynamic Free (Aa) in accordance with BS EN 12101-2 under Section 5.a. Furthermore, the calculation in accordance to 5.d diagram D7, figure a. cannot take into consideration individual lining depths used in specific interior design cases, which may give further limitations to the values presented above.


Glazing unit




Coating options	Colour code	Explanation
LowE		Low-emissivity coating
Sun1		Light sun protection coating
Sun2		Enhanced sun protection coating









Glazing description	Colour code	Explanation	Characteristic bending strength
F		Float	45.0 N/mm ²
H		Toughened	120.0 N/mm ²
HS		Heat Strengthened	70.0 N/mm ²
Int		Fire protection gel	-




Gas description	Colour code
Argon	
Krypton	

Foil	Colour code	Explanation
Polyvinyl butyral (PVB)		Lamination foil between the sheets of the laminated glass




Example of glazing unit construction

Description, from outside - inside		
Glazing variant	IGU 16L	
Construction	6H LowE - 14 Argon - 6HS - 14 Argon - 6.76F LowE (33.2)	
Description		Visual colour description
6H	6 mm pane with toughened glass	
LowE	Low-emissivity coating	
14 Argon	14 mm Argon filled cavity	
6HS	6 mm pane with heat strengthened glass	
14 Argon	14 mm Argon filled cavity	
6.76F (33.2)	Laminated glass, 3 mm float - 2 x 0.38 PVB foil - 3 mm float	
LowE	Low-emissivity coating	
Description, from outside - inside		Visual colour description, from outside - inside
Construction colour code	6H LowE - 14 Argon - 6HS - 14 Argon - 6.76F LowE (33.2)	

Fire resistant glazing units used in fire resistant modules HFS				
TG/ DG	Coating		Construction	Visual colour description
		IGU	Insulating Glass Unit (IGU)	Insulating Glass Unit (IGU)
		code	(outside - inside)	(outside - inside)
DG	LowE	10U	6H LowE - 9 Krypton - 5H - Int.6 - 8.76F (44.2)	
DG	Sun1	11U	6H Sun1 - 9 Krypton - 5H - Int.6 - 8.76F (44.2)	
DG	Sun2	12U	6H Sun2 - 9 Krypton - 5H - Int.6 - 8.76F (44.2)	

Glazing unit



Glazing units																
Double glazing = DG / Triple glazing = TG	Coating	IGU	Thermal transmittance U_g	Psi value ψ	Thermal transmittance of the entire window in accordance with EN 14351-1		Light transmittance τ_v	Solar factor g	UV transmittance τ_{uv}	Colour rendering index R_a	Direct airborne sound reduction IGU $R_w (C, C_{tr})$	Acoustic performance window ^{1), 2)} $R_w (C, C_{tr})$	Rain noise L_{ia}	Total solar energy direct absorption a	Resistance to pendulum body impact Class	Resistance to burglary Class
					area > 2.3 m ²	area ≤ 2.3 m ²										
					U_w	U_w										
					W/m ² K	W/m ² K										
		code	W/m ² K	W/mK	W/m ² K	W/m ² K	%	%	%		dB	dB	dB	%	Outside/Inside	Inside
DG	LowE	10L	1.1	0.059	1.4	1.4	80	61	0.0	97	35 (-3;-7)	35 (-1;-5)	52	23	1C1/1B1	P2A
DG	LowE	10T	1.0	0.066	1.3	1.4	73	51	0.0	94	41 (-1;-4)	38 (-1;-4)	49	29	1C1/1B1	P2A
TG	LowE	16L	0.6	0.060	0.89	0.98	72	52	0.0	96	37 (-2;-6)	36 (-1;-4)	49	29	1C2/NPD/1B1	P2A
TG	LowE	16K	0.5	0.080	0.86/0.87 ³⁾	0.96/0.99 ³⁾	70	49	0.0	96	42 (-2;-6)	38 (-1;-4)	48	30	1C2/NPD/1B1	P2A
TG	LowE	16T	0.7	0.080	1.0	1.1	70	49	0.0	96	42 (-2;-6)	38 (-1;-4)	48	30	1C2/NPD/1B1	P2A
DG	Sun1	11L	1.1	0.059	1.4	1.4	52	28	0.0	84	35 (-3;-7)	35 (-1;-5)	52	46	1C2/1B1	P2A
DG	Sun1	11T	1.0	0.066	1.3	1.4	51	28	0.0	83	40 (-1;-5)	38 (-1;-4)	49	48	1C2/1B1	P2A
TG	Sun1	17L	0.6	0.060	0.89	0.98	46	25	0.0	88	37 (-2;-6)	36 (-1;-4)	49	46	1C2/NPD/1B1	P2A
TG	Sun1	17K	0.5	0.080	0.86/0.87 ³⁾	0.96/0.99 ³⁾	45	24	0.0	88	42 (-2;-6)	38 (-1;-4)	48	48	1C2/NPD/1B1	P2A
TG	Sun1	17T	0.7	0.080	1.0	1.1	45	24	0.0	88	42 (-2;-6)	38 (-1;-4)	48	48	1C2/NPD/1B1	P2A
DG	Sun2	12T	1.1	0.066	1.4	1.5	18	17	0.0	92	41 (-1;-4)	38 (-1;-4)	49	59	1C1/1B1	P2A
TG	Sun2	18T	0.7	0.080	1.0	1.1	16	14	0.0	93	42 (-2;-6)	38 (-1;-4)	48	61	1C1/NPD/1B1	P2A

Fire resistant glazing units used in fire resistant modules HFS											
	Coating	IGU	U_g	ψ	U_w Area > 2.3m ²	U_w Area ≤ 2.3m ²	τ_v	g	τ_{uv}	R_a	a
		code	W/m ² K	W/mK	W/m ² K	W/m ² K	%	%	%		%
DG	LowE	10U	1.0	0.083	1.3	1.4	76	60	-	96	29
DG	Sun1	11U	1.0	0.083	1.3	1.4	65	40	-	92	37
DG	Sun2	12U	1.0	0.083	1.3	1.4	57	33	-	90	40

Notes:

¹⁾ For product sizes A ≤ 2.7 m². For product sizes of 2.7 m² < A < 3.6 m², the sound insulation values must be deducted by 1 dB

²⁾ The R_w -value indicates the number of decibels by which a window will reduce apparent noise.

R_w+C is an adjustment factor to account for high frequency noise sources e.g. living activities (talking, music, radio, TV), railway traffic at medium to high speed, road traffic exceeding 80 km/h or a jet aircraft.

R_w+C_{tr} is an adjustment factor to account for low frequency noise sources e.g. urban road traffic or railway traffic at low speeds.



³⁾ HFC/HVC

General notes:

- It is up to the customer to verify the chosen fire resistant glazing unit against the project specific conditions following the national requirement.
- Production height for calculation of climatic load is from 0 to 300 metre above sea level.
- Modules higher than 2400 mm will be delivered with a T-pane.
- Other insulating glass units are available, contact your VELUX sales office for more details.


Under normal conditions the free vision through the glass in a HFS module will not be adversely affected.

The term normal conditions implies that the gel layer may not be allowed to reach temperatures below -10°C or above +45°C.



Frame and Sash

Material	Pultruded composite (approx. 80% fibreglass and 20% polyurethane)
Material thickness	3-4 mm
Surface coating	Waterbased white coating
Colour	RAL 9010, gloss 30




Thermal transmittance of the frame profiles (U_f)

$U_f^{1)} [W/m^2K]$	
Double-glazed	Triple-glazed
1.40	1.25

¹⁾ Calculated in accordance to EN ISO 10077-2:2012 and refers to the joint profiles when modules are combined.

Cladding & flashing



Cladding

Material	Aluminium
Material thickness	1.5 mm
Surface	Scratch resistant powder lacquer (60-120 my)
Colour	Noir 2100 Sable (Granite 60)

Flashing

Flashing material	Aluminium	
Material thickness	1 mm	
Surface	Front: PVdf lacquer	Back: polyamid polyester lacquer
Colour	Front: NCS standard colour: S 7500-N (RAL 7043)	
Insulation material	EPS	
Material thickness	10 mm	
Wind and snow stop	Polyurethane foam	

Frame & sash – interior colours



Standard colours



Frame and Sash **White**

Material: Pultruded composite (approx. 80% fibreglass and 20% polyurethane)
Surface: Waterbased white coating
Colour: RAL 9010, gloss 30

Semi-standard colours (Available at additional cost)




Frame and Sash **Light grey**

Material: Pultruded composite (approx. 80% fibreglass and 20% polyurethane)
Surface: Waterbased light grey coating
Colour: RAL 7037, gloss 30



Frame and Sash **Dark grey**

Material: Pultruded composite (approx. 80% fibreglass and 20% polyurethane)
Surface: Waterbased dark grey coating
Colour: RAL 7021, gloss 30



Frame and Sash **Black**

Material: Pultruded composite (approx. 80% fibreglass and 20% polyurethane)
Surface: Waterbased black coating
Colour: RAL 9005, gloss 30

Special colours



Special colours

All other colours can be ordered at additional price, though with exception of mother-of-pearl, effect and metallic colours, neon colours, and colours with other substances than pigment.
Contact our sales team for more details.

A diagram illustrating the assembly of a rectangular frame. The frame consists of four dark-colored corner brackets and a central rectangular panel. The brackets are shown being attached to the corners of the panel, with one bracket already partially attached to the bottom-left corner.

Material: Aluminium (1.5 mm)
Surface: Scratch resistant powder lacquer
Colour: Noir 2100 Sable (Granite 60)




Material: Aluminium (1 mm)
Surface: PVdf lacquer
Colour: NCS standard colour: S 7500-N (RAL 7043), gloss 30

Material: Aluminium (1.5 mm)
Surface: Scratch resistant powder lacquer
Colour: AA10F Sable (Granite 01)




Material: Aluminium (1 mm)
Surface: PVdf lacquer
Colour: RAL 9010, gloss 30




Material: Aluminium (1.5 mm)
Surface: Scratch resistant powder lacquer
Colour: Gris 400 Sable (Granite 20)




Material: Aluminium (1 mm)
Surface: PVdf lacquer
Colour: RAL 7037, gloss 30




Not a semi-standard colour
Same as our standard colour cladding



Material: Aluminium (1.5 mm)
Surface: Scratch resistant powder lacquer
Colour: Noire 900 Sable (Granite 80)



Material: Aluminium (1 mm)
Surface: PVdf lacquer
Colour: RAL 7021, gloss 30




Material: Aluminium (1 mm)
Surface: PVdf lacquer
Colour: RAL 9005, gloss 30



All other colours can be ordered at additional price, though with exception of mother-of-pearl, effect and metallic colours, neon colours, and colours with other substances than pigment.
Contact our sales team for more details.

Vapour barrier connection strip



	BCX	BSX
Membrane	Polyethylene (PE-LD) 150 µm	Multilayer foil containing polyethylene and aluminium, 0.15 mm thick
Gasket	Welded EPDM rubber seal gasket	Welded EPDM rubber seal gasket
Height	200 mm	200 mm
Length	10,000 mm (10 m)	10,000 mm (10 m)
Classification	BCX is CE-marked in accordance with EN 13984	BSX is CE-marked in accordance with EN 13984
Resistance	Water vapour resistance Sd = 80 m	Water vapour resistance Sd = >1500 m
Reaction to fire	Class E	Class E

Chain actuator



Venting modular skylights and roller blinds can be powered and controlled from either a VELUX io-homecontrol® or an Open system control system.

With VELUX io-homecontrol® the actuator is powered and controlled with control unit KLC 410 and operated with a VELUX control pad. With Open system the actuator can be powered and controlled with either a ±24 V DC or a MotorLink™ control system.

VELUX io-homecontrol® / Open system	
Material	Anodised aluminium housing with zinc chromate passivated steel chain
Weight	Max 5.5 kg
Control system	VELUX io-homecontrol®, MotorLink™ or ±24 V DC*
Supply cable	1.2 m grey silicone cable, 3 cord, 0.75 mm² (white brown green**)
Chain stroke	HVC ----CB (comfort) 260 mm HVC ----AB (smoke and comfort) up to 700 mm (depending on module size)
Opening speed	HVC ----CB (comfort) 7 mm/s HVC ----AB (smoke and comfort) up to 13 mm/s
Sound level	32 dB (min speed)***
Holding force (tractive)	5000 N (burglary strength) min
Pressure force	1000 Newton* (smoke ventilation: 1300 Newton)
Tractive force	300-1000 Newton
IP rating	IPX4
Operation conditions	-15°C - +76°C, max. 90% relative humidity (not condensing)
Nominal voltage	24 V DC (max 10% ripple) ****
Voltage	19-32 V DC
Max voltage	32 V DC
Switch-on-duration	ED max 20% (2 minutes per 10 minutes)
Current consumption	HVC ----CB (comfort) max. 2A HVC ----AB (smoke and comfort) 2.5 - 5.5A depending on module size, glazing variant and required snow load
Service	It is recommended to carry out a function test of the actuator at least once a year and to make sure that the skylight opens correctly.
CE marking	The product is tested with the original WindowMaster control units and complies with the EMC directive's requirements for use in residential, commercial and light commercial buildings.
Reservation	The VELUX Group reserves the right to make technical changes.


$$\text{Max cable length} = \frac{(\text{admissible voltage drop (UL)} \times \text{conductivity of copper (56)} \times \text{cable cross-section (a)})}{(\text{total max. actuator current (I) in amps} \times 2)}$$

****The provided characteristics for Opening under load and related current consumptions on pages 82-85 are tested and valid for 24 V DC nominal voltage.

The actuator is lifetime tested for comfort ventilation with a chain stroke up to 530 mm.

800	260	20
1000	260	20
1200	260	20
1400	260	20
1600	260	20
1800	260	20
2000	260	20
2200	260	20
2400	260	20
2600	260	20
2800	260	20

Material and colour	ABS, white (NCS S 1000-N), black (RAL 9005) and metallic grey
Size and weight	Product including packaging: 235 x 153 x 48 mm (W x H x D), 250 g Control pad: 95 x 95 x 23 mm (W x H x D), 180 g
Use	For indoor use, maximum ambient temperature 50°C Radio frequency range: 200 m range open field. Depending on the building construction, the indoor range is approximately 20 m Maximum number of products is 200*
Battery requirement	3 x Alkaline AA (1.5 V) batteries Expected battery lifetime: Approximately 1 year
Compatibility	Based on radio frequency (RF) technology, transmitted in 868 MHz range. Compatible with products with the io-homecontrol® logo.
CE marking	CE-marked to indicate that it is in accordance with the following EU directives: CPR, LVD, MD, RoHS, WEEE, R&TTE, Packaging waste directive and EMC for household, trade and light industry. Combinations of VELUX electrical products meet the requirements of above-mentioned directives.
Note	This product has been designed for use with genuine VELUX products. The connection to other products may cause damage or malfunction. The VELUX Group reserves the right to make technical changes.

VELUX Commercial 103

Control system



Control pad KLR 300	
Material and colour	ABS, white (NCS S 1000-N)
Size and weight	Product including packaging: 92 x 74 x 99 mm , 331 g Control pad: 81 x 81 x 17 mm (W x H x D) , 112 g
Use	For indoor use, maximum ambient temperature 50°C. Radio frequency range: 100 m range open field. Depending on the building construction, the indoor range is approximately 10 m. Maximum number of products is 200*
Battery requirements	2 x alkaline AAA (1.5 V) batteries Expected battery lifetime: Approximately 1 year
Compatibility	Based on radio frequency (RF) technology, transmitted in 868 MHz range. Compatible with products with the io-homecontrol® logo.
CE marking	CE-marked to indicate that it is in accordance with the following EU directives: CPR, LVD, MD, RoHS, WEEE, R&TTE, Packaging waste directive and EMC for household, trade and light industry. Combinations of VELUX electrical products meet the requirements of above-mentioned directives.
Note	This product has been designed for use with genuine VELUX products. Connection to other products may cause damage or malfunction. The VELUX Group reserves the right to make technical changes.

* Maximum 99 of the same product type can be connected at once.

Control system



Power supply and control unit KLC 410	
Material and colour	Black fire resistant polycarbonate
Size and weight	Product including packaging: 92 x 99 x 74 mm (W x H x D), 331 g Control pad: 81 x 81 x 17 mm (W x H x D), 112g
Installation	24 V DC SELV class III construction output. The control unit is for use in small/medium installations with VELUX Modular Skylights. The control unit can be installed under the flashing of VELUX Modular Skylights or inside the building, at a maximum cable distance of 20 m from the chain actuator. The control unit functions at temperatures between -15°C and +50°C. ta=40°C. The control unit is equipped with a 2.2 m 2-core cable (2 x 1.5 mm² H05VV-F) and plug for connection to the mains supply. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
IP rating	IPX4
Power supply characteristics	Primary side: 230/240 V AC - 50 Hz / 250W Secondary side: 24 V DC - 10 A class III construction output.
Connection	The control unit is only to be used with VELUX Modular Skylights and VELUX roller blinds RMM. The control unit can supply power to one venting skylight module and/or up to four roller blinds RMM. The connection wires are pre-fitted with wire-to-wire connectors. The connection wires to the chain actuator and the roller blinds RMM can be extended up to 20 m with a 2 x 1.5 mm² cable.
Compatibility	KLC 410 is based on radio frequency (RF) technology and signals are transmitted in the 868 MHz range. It can be used with VELUX Modular Skylights chain actuator and roller blinds RMM. VELUX electrical products connected to KLC 410 can be operated by io-homecontrol® compatible activation controls.
CE marking	CE-marked to indicate that it is in accordance with the following EU directives: CPR, LVD, MD, RoHS, WEEE, R&TTE, Packaging waste directive and EMC for household, trade and light industry. Combinations of VELUX electrical products meet the requirements of above-mentioned directives.
Note	The VELUX Group reserves the right to make technical changes.

* For Open system ± 24 V DC connection, the maximum distance from roller blind to power supply is in accordance to the following calculation:

$$\text{Max. cable length} = \frac{\text{admissible voltage drop (UL)} \times \text{conductivity of copper (56)} \times \text{cable cross-section (a)}}{\text{total max. actuator current (I) in amps} \times 2}$$

** Green cable has no function
*** Only valid for pre-wired modules

Roller blind



Roller blind cloth properties

Colour	White (8806)	Grey (8805)	Black (8807)
--------	--------------	-------------	--------------

Radiation properties without glazing unit (%)

Total solar energy transmittance (g-value)	37%	31%	15%
Light transmittance in visible light spectrum (tau, v)	36%	10%	1%
Light transmittance in full light spectrum (tau, e)	35%	22%	3%
Light reflectance in full light spectrum (rho, e)	59%	45%	53%
Light absorption in full light spectrum (alpha, e)	6%	33%	44%
Openness factor	1	1	1

Reaction to Fire

Norm	Class
EN 13501-1 + A1	B, s1-d0
DIN 4202-1	B1
NF P 92 503 -507	M1

Roller blind effects on double-glazing unit (%)

Glazing variant		10L			11L		
		g-value	τ _v -value	Fc-value	g-value	τ _v -value	Fc-value
Without RMM		61%	80%	100%	28%	52%	100%
With RMM	White (8806)	36%	31%	59%	17%	21%	61%
	Grey (8805)	43%	8%	70%	22%	5%	79%
	Black (8807)	37%	0%	61%	18%	0%	64%

Roller blind effects on double-glazing unit (%)

Glazing variant		10T			11T			12T		
		g-value	τ _v -value	Fc-value	g-value	τ _v -value	Fc-value	g-value	τ _v -value	Fc-value
Without RMM		51%	73%	100%	28%	51%	100%	17%	18%	100%
With RMM	White (8806)	30%	29%	59%	18%	19%	57%	13%	8%	76%
	Grey (8805)	37%	7%	73%	21%	5%	75%	14%	2%	82%
	Black (8807)	32%	0%	63%	17%	0%	61%	13%	0%	76%


Roller blind effects on triple-glazing unit (%)										
Glazing variant		16T / 16K			17T / 17K			18T		
		g-value	τ _v -value	Fc-value	g-value	τ _v -value	Fc-value	g-value	τ _v -value	Fc-value
Without RMM		49%	70%	100%	24%	45%	100%	14%	16%	100%
With RMM	White (8806)	30%	28%	61%	15%	18%	63%	11%	7%	79%
	Grey (8805)	37%	7%	76%	19%	5%	79%	13%	2%	93%
	Black (8807)	32%	0%	65%	16%	0%	67%	12%	0%	86%

Beam for Ridgelight at 5°




Beam for Ridgelight at 5°		
	Horizontal beam with rectangular profile	Parallel beam with curved profile
Material	Steel	Steel
Material thickness	3 mm	4 mm
Construction	Hollow beam	Hollow beam
Surface	Powder coating, white RAL 9010, gloss 30	Powder coating, white RAL 9010, gloss 30
Foam gasket on beam	Grey 15 mm	Black 6 mm

Horizontal beam with rectangular profile



Parallel beam with curved profile




Product Name	VELUX Commercial Skylight	Product Code	VELUX Commercial Skylight
Product Description	VELUX Commercial Skylight	Product Description	VELUX Commercial Skylight
Product Dimensions	VELUX Commercial Skylight	Product Dimensions	VELUX Commercial Skylight
Product Weight	VELUX Commercial Skylight	Product Weight	VELUX Commercial Skylight
Product Material	VELUX Commercial Skylight	Product Material	VELUX Commercial Skylight
Product Finish	VELUX Commercial Skylight	Product Finish	VELUX Commercial Skylight
Product Installation	VELUX Commercial Skylight	Product Installation	VELUX Commercial Skylight
Product Warranty	VELUX Commercial Skylight	Product Warranty	VELUX Commercial Skylight
Product Availability	VELUX Commercial Skylight	Product Availability	VELUX Commercial Skylight
Product Price	VELUX Commercial Skylight	Product Price	VELUX Commercial Skylight
Product Lead Time	VELUX Commercial Skylight	Product Lead Time	VELUX Commercial Skylight
Product Support	VELUX Commercial Skylight	Product Support	VELUX Commercial Skylight
Product Contact	VELUX Commercial Skylight	Product Contact	VELUX Commercial Skylight

Water pressure & drainage




Additional information on water pressure and drainage on a Step Wall-mounted Longlight

Please note that the same installation pitch is required on all rows and the maximum distance from the top of the vertical wall to the top of the lowest row of modules is 15 metres.



Additional information on water pressure and drainage on a Northlight

Please ensure max. 10 m distance above the skylight module, when installed in a sloping roof.




Additional information on water pressure and drainage on a Wall-mounted Longlight

Please ensure a max. 3 m wall height above skylight module.




Resistance to wind load

Test method: EN 12211



VELUX Modular Skylights: Class C5 *

P₁: 2000 Pa
P₂: 1000 Pa
P₃: 3000 Pa



* Valid for sizes up to 1000 mm width and up to 2400 mm height, except HVC 090220, HVC 090240, HVC 100220 and HVC 100240 with glazing variants 10L and 11L, which have Class C4. Above these sizes the applicable performance is NPD.

Classification of wind load			
Class	P1	P2 ¹⁾	P3
0	–	not tested	–
1	400	200	600
2	800	400	1200
3	1200	600	1800
4	1600	800	2400
5	2000	1000	3000
Exxxx ²⁾	xxxx	–	–

²⁾ Specimen tested with wind load above class 5, classified Exxxx – where xxxx is the actual test pressure P1 (e.g. 2350 etc.)

²⁾ Specimen tested with wind load above class 5, classified Exxxx – where xxxx is the actual test pressure P1 (e.g. 2350 etc.)

Note: In resistance to wind load classification, the number refers to the wind load class, see table 1 and the letter to the relative frontal deflection, see table 2

- Frontal deflection measured at P1: 2000 Pa is less than $L/300$.
- 50 cycle pressure test P2: 1000 Pa
- After that repeated air permeability test passed

Safety test done at P3: 3000 Pa passed with no released part

VELUX Commercial 111

Reaction to fire


Test method: EN ISO 11925-2, EN 13823



Reaction to fire classes for building products (excl. floorings)							
Main class	Smoke class	Burning droplets class	Requirements according to			FIGRA	
			Non comb	SBI	Small flame	W/s	
A1	-	-	x	-	-	-	Non combustible
A2	s1 - s3	d0 - d2	x	x	-	≤ 120	
B	s1 - s3	d0 - d2	-	x	x	≤ 120	
C	s1 - s3	d0 - d2	-	x	x	≤ 250	
D	s1 - s3	d0 - d2	-	x	x	≤ 750	
E	-	- or d2	-	-	x	-	
F	-	-	-	-	-	-	No performance determined

¹⁾ The test is a corner basket test, which shows how much the product contributes to the development of fire.


Internal fire spread and smoke contribution.




Product Name	VELUX Modular Skylights	Product Code	VELUX-MSK-01
Product Description	Modular skylights with polycarbonate glazing	Product Code	VELUX-MSK-02
Product Description	Modular skylights with glass glazing	Product Code	VELUX-MSK-03
Product Description	Modular skylights with glass glazing and integrated LED lighting	Product Code	VELUX-MSK-04
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation	Product Code	VELUX-MSK-05
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation and rain sensor	Product Code	VELUX-MSK-06
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation and rain sensor and remote control	Product Code	VELUX-MSK-07
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation and rain sensor and remote control and battery pack	Product Code	VELUX-MSK-08
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation and rain sensor and remote control and battery pack and solar panel	Product Code	VELUX-MSK-09
Product Description	Modular skylights with glass glazing and integrated LED lighting and ventilation and rain sensor and remote control and battery pack and solar panel and motion sensor	Product Code	VELUX-MSK-10

Reaction to fire

Classification: EN 13501-1 + A1



Smoke sub-class



CLASSIFICATION
A1, A2, B: Non-combustable and not very combustible product. Over 20 minutes to flashover.
C: Moderate combustible products. Between 10 and 20 minutes to flashover.
D: Moderate combustible products. Between 2 and 10 minutes to flashover.
E: Moderate combustible products.
F: Highly combustible products (or products whose reaction to fire has not been assessed).

SUB-CLASS
s1: Low smoke production.
s2: Medium smoke production.
s3: High smoke production.

FLAMING DROPLETS SUB-CLASSIFICATION
d0: No flaming droplets.
d1: Flaming droplets that persist for less than 10 s.
d2: Flaming droplets.

VELUX Modular Skylights: Class B, s1-d0 or d2

B: Very low combustibility
(A: Incumbustable eg steel and concrete)

s1: Lowest smoke volume
d0: No droplets in T-pane variants
d2: Droplets in standard pane variant

Resistance to fire

Test method: EN 1365-2




Fixed modules: EN 1365-2 Fire resistance tests for loadbearing elements - Part 2: Floors and roofs*

* In accordance with EN 1365-2, 1, which is the relevant standard for fixed modular skylights, roofs can be roof constructions incorporating glazed elements.


Under fire conditions, certain elements and windows can be required to remain satisfactory fire barriers depending on national and local requirements.

The tests assess how satisfactory fire barriers the modules are in the defined test conditions.

More simply, the tests assess the length of time the modules can effectively keep the fire inside the burning compartment.



Temperature in the furnace



Modules on the furnace



Presentation of classification

The classification shall be presented according to the following template

R- Load bearing capacity (not applicable on venting modules, only on fixed)
Withstanding fire exposure without loss of mechanical stability

No cracks or openings in excess of given dimension
No ignition of a cotton pad on the unexposed side
No flames sustained on the unexposed side

Maximum temperature rise on unexposed side not exceeding 180°
Mean temperature rise on unexposed side not exceeding 140°C

Classification periods

Declaration of performance

VELUX Modular Skylights:



VELUX Commercial 115


External fire performance




Test method: TS 1187 - External fire exposure to roofs*

* In accordance with EN 14351-1, TS1187 test methods T1 and T4 must be used to determine the external fire performance of roof windows.


The tests assess the fire spread across the external surface of the roof*, the fire spread within the roof*, the fire penetration and the production of falling droplets or debris falling from the underside of the roof*.



Test 1 – with burning brands



Test 4 - two stages incorporating burning brands, wind and supplementary radiant heat



Product name	VELUX Modular Skylights	Product code	10000000000000000000
Product description	VELUX Modular Skylights	Product description	VELUX Modular Skylights
Product type	VELUX Modular Skylights	Product type	VELUX Modular Skylights
Product material	VELUX Modular Skylights	Product material	VELUX Modular Skylights
Product color	VELUX Modular Skylights	Product color	VELUX Modular Skylights
Product size	VELUX Modular Skylights	Product size	VELUX Modular Skylights
Product weight	VELUX Modular Skylights	Product weight	VELUX Modular Skylights
Product dimensions	VELUX Modular Skylights	Product dimensions	VELUX Modular Skylights
Product features	VELUX Modular Skylights	Product features	VELUX Modular Skylights
Product benefits	VELUX Modular Skylights	Product benefits	VELUX Modular Skylights
Product applications	VELUX Modular Skylights	Product applications	VELUX Modular Skylights
Product certifications	VELUX Modular Skylights	Product certifications	VELUX Modular Skylights
Product compliance	VELUX Modular Skylights	Product compliance	VELUX Modular Skylights
Product safety	VELUX Modular Skylights	Product safety	VELUX Modular Skylights
Product warranty	VELUX Modular Skylights	Product warranty	VELUX Modular Skylights
Product support	VELUX Modular Skylights	Product support	VELUX Modular Skylights
Product contact	VELUX Modular Skylights	Product contact	VELUX Modular Skylights
Product website	VELUX Modular Skylights	Product website	VELUX Modular Skylights
Product email	VELUX Modular Skylights	Product email	VELUX Modular Skylights
Product phone	VELUX Modular Skylights	Product phone	VELUX Modular Skylights
Product fax	VELUX Modular Skylights	Product fax	VELUX Modular Skylights
Product address	VELUX Modular Skylights	Product address	VELUX Modular Skylights
Product city	VELUX Modular Skylights	Product city	VELUX Modular Skylights
Product state	VELUX Modular Skylights	Product state	VELUX Modular Skylights
Product zip	VELUX Modular Skylights	Product zip	VELUX Modular Skylights
Product country	VELUX Modular Skylights	Product country	VELUX Modular Skylights



External fire performance


Classification: EN 13501-5 + A1

Test 1

Class	Classification criteria
B_{ROOF} (t1)	<p>All of the following conditions must be satisfied for all tests:</p> <ul style="list-style-type: none"> external and internal fire spread upwards < 0.700 m external and internal fire spread downwards < 0.600 m maximum burned length external and internal < 0.800 m no burning material (droplets or debris) falling from exposed side no burning/glowing particles penetrate the roof construction no single through opening > 25 mm² sum of all spread opening < 4500 mm² lateral fire spread does not reach the edges of the measuring zone no internal glowing combustion maximum radius of fire spread on flat roofs, external and internal < 0.200 m
F_{ROOF} (t1)	No performance determined.


Test 4


Class	Classification criteria
B_{ROOF} (t4)	<ul style="list-style-type: none"> No penetration of roof system within 1 h. In preliminary test, after withdrawal of the test flame, specimens burn for < 5 min. In preliminary test, flame spread < 0.38 m across region of burning.
C_{ROOF} (t4)	<ul style="list-style-type: none"> No penetration of roof system within 30 min. In preliminary test, after withdrawal of the test flame, specimens burn for < 5 min. In preliminary test, flame spread < 0.38 m across region of burning.
D_{ROOF} (t4)	<ul style="list-style-type: none"> Roof system is penetrated within 30 min but is not penetrated in the preliminary test. In preliminary test, after withdrawal of the test flame, specimens burn for < 5 min. In preliminary test, flame spread < 0.38 m across region of burning.
E_{ROOF} (t4)	<ul style="list-style-type: none"> Roof system is penetrated within 30 min but is not penetrated in the preliminary test. Flame spread is not controlled.
F_{ROOF} (t1)	No performance determined.

 **VELUX Modular Skylights**
B_{ROOF} (t1)
B_{ROOF} (t4)

Watertightness

Test method: EN 1027



Watertightness		
Classification	Pressure (Pa)	Wind (Km/h)
1 A	0	0
2 A	50	32
3 A	100	45
4 A	150	55*
5 A	200	63
6 A	250	71
7 A	300	78
8 A	450	95
9 A	600	110
E750	750	123**
E900	900	134
E1050	1050	145
 E1200	1200	155


** Equal to tropical storm



No water penetration up to 1200 Pa.
1200 Pa equals 155 Km/h.

Air permeability


Test method: EN 1026



⊗ Opening and closing

Test pressure

150 Pa - Class 1
300 Pa - Class 2
600 Pa - Class 3, 4






VELUX Modular Skylights: Class 4

The background of the entire page is a solid dark gray. Overlaid on this is a complex, abstract geometric pattern. It consists of numerous thin, white, parallel lines that intersect to form a grid-like structure of rectangular and trapezoidal shapes. These shapes are tilted at various angles, creating a sense of depth and perspective. Interspersed among these white lines are several thick, solid blue lines. These blue lines are curved, following the general orientation of the white grid but with a more fluid, organic feel. They appear to be part of the overall structure, possibly representing a different material or a specific path within the grid. The overall effect is a modern, architectural, and somewhat futuristic design.

Additional Solutions

The following shown solutions for other types of skylight projects is project specific

Shaped solution with adaption of lining



Atrium Longlight
 Internal lining
 Roof




Atrium Longlight
 Internal lining
 Roof

Feature	Advantage	Benefit
By adapting the internal lining, it is possible to build a shaped skylight with standard skylight modules. *	By using standard skylight modules on non-square roof designs, the architects will not have to compromise the wishes for the interior design. The solution can be combined with venting modules and internal roller blinds.	Using standard products with standard installation principles gives high security in the design and building process. Installing venting modules and roller blinds gives a better indoor climate.

* If the modules are fitted with RMM, access from outside is mandatory.


Shaped solution with oval lining




Ridgelight
 Internal lining
 Roof

Feature	Advantage	Benefit
By adapting the internal lining, it is possible to build a shaped skylight with standard skylight modules. *	By using standard skylight modules on non-square roof designs, the architects will not have to compromise the wishes for the interior design.	Using standard products with standard installation principles gives high security in the design and building process. The solution can be combined with internal roller blinds.

* If the modules are fitted with RMM, access from outside is mandatory.



Asymmetric Ridgelight




Feature	Advantage	Benefit
By constructing an asymmetric Ridgelight, it is possible to combine modules of different lengths in an installation.	The solution allows for installation between two roofs of different heights or of modules in different slopes. By combining panes with different characteristics on each side of the Ridgelight, it is possible to maximize daylight and minimize heat gain.	The asymmetric Ridgelight offers more flexibility in installations between buildings or sections of buildings.

Ridgelight on Girder



Feature	Advantage	Benefit
A Ridgelight solution that consists of two rows of VELUX Modular Skylights installed on one supporting horizontal girder at the ridge. The solution is delivered with a factory finished flashing designed for installation in pitches between 5-40°, either on a flat roof construction or at the top of a sloped roof. Girder and inner girder cover is not part of VELUX delivery.	<ul style="list-style-type: none"> The girder supports the installation and thus allows for increased installation pitch possibilities of the modules. Possibilities of vented modules on both sides. Possibilities of different glazing types on each side. 	<ul style="list-style-type: none"> Additional design options. Low pitch allows maximum daylight in the room. The large opening gives an illusion of a small glass roof.


Infill panel




Feature	Advantage	Benefit
Ventilation shaft: Use an infill panel when penetrating the skylight with e.g. ventilation. Wall: Use infill panels when covering a wall in the building.	Continuous modular skylight installations instead of disrupted installations.	Cheaper product solution and better design.

Note:
Products with a fixed, opaque insulating infill panel are out of the scope of the harmonised product standard EN 14351-1 used for CE marking of windows. No harmonised product standard is available/applicable for these products; they are not and cannot be CE-marked. The VELUX Group can deliver the above-mentioned products and provide product specifications on the relevant general performance characteristics for thermal transmittance, air permeability, watertightness, resistance to wind load and reaction to fire on request. The VELUX Group is not responsible for the specific application of the product with fixed, opaque insulating infill panel. It is the responsibility of the customer to verify the fitness of the product for specific use with the relevant authorities.

Skylight modules with photovoltaic glazing units



Feature	Advantage	Benefit
VELUX Modular Skylights can be delivered with photovoltaic glazing units in both a fully covered or partly covered variant (illustration shows partly covered variant).	The solution offers a built-in solution where photovoltaic panels are combined with skylight installations.	The solution will optimize the utilization of space on the roof. Furthermore, the photovoltaic panels create a shadow effect in the building that reduces heat gain and glare.




Sun screening – electrochrome glass



Glazing with electrochrome glass in clear state. Visible light transmission 57%



Glazing with electrochrome glass in intermediate state. Visible light transmission 15%



Glazing with electrochrome glass in fully tinted state. Visible light transmission 1%

VELUX Modular Skylights are available with electrochromic panes. The electrochromic pane is an insulated glazing unit with electrochromic, tintable coating. The coating can be darkened on demand by applying a low voltage of electricity. The dynamic changing in tint provides exceptional control of daylight, glare and energy use

without blinds or shades. An easy-to-use control system allows anyone to operate the electrochromic panes with wall switches, a mobile app or with a building management system. A combination of the three is also possible.

Sun screening – external awning blinds


Maintain a pleasant thermal indoor environment

The Topfix® VMS external awning blind by Renson protects the interior from excessive solar heating. The product is optimized for VELUX Modular Skylights and is applicable to both fixed and vent-

ing modules. Topfix® VMS operates on mounting feet that fits perfectly onto the external surface of the modular profiles. The blinds features a VELUX compatible operation system and can endure wind loads up to 120 km/h.



Ridgelight on Pitch




Feature	Advantage	Benefit
The Ridgelight on Pitch solution is a non-standard flashing for installing a Ridgelight or an asymmetric Ridgelight at the top of a sloped roof in level with the roof.	<ul style="list-style-type: none">• It ensures a watertight and airtight connection between the skylight solutions and the roof.• Possibilities of venting modules on both sides.• Possibility of different glazing types on each side.	<ul style="list-style-type: none">• Design flexibility when specifying Ridgelight solutions on a sloped roof.• A classic looking solution that add natural light and openness to the area below.• Ensures unique light conditions and possibility to "manage the sun" and ensures thermal comfort.

Gable modules



Feature	Advantage	Benefit
Gable modules for Ridgelight and Wall-mounted Longlight solutions, available at either one of the gables or both gable ends.	It ensures a watertight and air tight solution at the end of the skylight. Possibility of different glazing types or infill panels, depending on the visual expression to be achieved with the installation.	Design flexibility when specifying Ridgelight and Wall-mounted Longlights solutions. Installation with gable modules will result in a simpler sub-construction.



Coupled flashings





Feature	Advantage	Benefit
A flashing connection creating a small distance between two modules. Available for Longlight, Ridgelight and Wall-mounted Longlights installations.	The solution makes room for a e.g. rafter in the construction, while still enabling the possibility for full-length steel profile on the sub-construction. The flashing ensures a watertight and airtight connection between two sections of modules.	By using a coupled flashing, the solution can be continued using one subconstruction.

Wall on side



Feature	Advantage	Benefit
A special flashing solution for Longlight and Ridgelight solutions with a wall on the side of the installation. The solution can be with a wall on either side or both sides of the installation.	The solution allows for installation close to a wall on the side, ensuring a watertight and airtight connection between the module and the wall.	The special flashing offers more flexibility when designing a Longlight or a Ridgelight solution.






Product Codes

Modular Skylights – code structure



Example

HVC	067	160	0	0	10	T	C	B
Type	Module width	Module height	Interior colour	Exterior colour	Glazing type	Glazing variant	Electric variant	Generation
H = VMS	067 = 675 mm	120 = 1200 mm	0 = std.	0 = std.	10 = DGU/LowE	L = 3+3 mm inner glass	A = Open-system/Smoke	
	075 = 750 mm	140 = 1400 mm			11 = DGU/Sun1			
F = Fixed	080 = 800 mm	160 = 1600 mm	RAL colour 9010, gloss 30	Noir 2100 Sable	12 = DGU/Sun2	T = 5+5 mm inner glass	C = Open-system/Comfort	
V = Venting	090 = 900 mm	180 = 1800 mm			16 = TGU/LowE	K = Krypton gas instead of the standard Argon gas, 5 + 5 mm inner glass.		
	100 = 1000 mm	200 = 2000 mm			17 = TGU/Sun1			
C = Commercial market		220 = 2200 mm	8 = Special	8 = Special	18 = TGU/Sun2	U = Fire resistant		
		240 = 2400 mm						
		260 = 2600 mm						
		280 = 2800 mm						
S = Fire-resistant variant. With fire resistant glazing unit and intumescent strip		300 = 3000 mm						



Roller blinds – code structure



Example

RMM	067	160	8805
Type	Module width	Module height	Fabric variant
R = Roller blind	067 = 675 mm	120 = 1200 mm	8805 = Grey, fire retardant
	075 = 750 mm	140 = 1400 mm	8806 = White, fire retardant
M = Electrical	080 = 800 mm	160 = 1600 mm	8807 = Black, fire retardant
	090 = 900 mm	180 = 1800 mm	
M = For VELUX Modular Skylights	100 = 1000 mm	200 = 2000 mm	
		220 = 2200 mm	
		240 = 2400 mm	
		260 = 2600 mm	
		280 = 2800 mm	
		300 = 3000 mm	

Product label – code structure



Product illustration

Module type

Module size

Colour variant

Pane type

Pane variant

Electrical variant

Generation

Order number

HVC 090180 0010TCB

Vented Module

Width (W) x Height (H)
90 cm x 180 cm
Volume 0.27 m³
Weight 108 kg

(97)006008818863

(240)HVC 090180 0010


HUSCOMPAGNIET - 29136802/Kim
Ring ved lev
ALDRSHVILEVEJ 153
DK-2450 KBH S

Made in Denmark by the VELUX Group

Product dimensions and weight


EAN code

Delivery address




Flashings – code structure

Longlight 5-30°




Ridgelight 25-40°




Wall-mounted Longlight 5-45°




Ridgelight at 5° with Beams






Northlight 25-90°




Step Longlight 5-25°



Code structure	
 Flashing configuration	 Step solution extension flashing



Flashing configuration – code structure



Example

ERC	080	160	0	0	0	25	D	B			
Type	Module width	Module height	Interior	Exterior flashing	Exterior cladding	Installation pitch				VMS Cover	Generation
E = Flashing	067 = 675 mm	120 = 1200 mm	0 = std.	0 = std.	0 = std.	05 = 5°, 10 = 10° etc.				D = Extra cover	
	075 = 750 mm	140 = 1400 mm	Only relevant on ERC: Beams and Inner ridge covering	NCS standard colour: S 7500-N (RAL 7043)	Noir 2100 Sable	Standard pitches:				Extra Cover When HVC ≥ HFC	
L = Longlight	080 = 800 mm	160 = 1600 mm				ELC	ERC	EWG	ENC		
R = Ridgelight	090 = 900 mm	180 = 1800 mm				05	05	05			
N = Northlight	100 = 1000 mm	200 = 2000 mm				10		10			
W = Wall-mounted Longlight		220 = 2200 mm				15		15			
		240 = 2400 mm	20		20						
		260 = 2600 mm	25	25	25						
C = Commercial Market		280 = 2800 mm		30	30						
		300 = 3000 mm		35	35						
				40	40						
							25				
						55					
			8 = special								

VELUX Group
VELUX Commercial
Ådalsvej 99
2970 Hørsholm
Denmark

Web: veluxcommercial.com
Blog: commercial.velux.com/blog

Your preferred partner for
daylight and ventilation solutions

VELUX®

Commercial

Version 7.0