VELUX solar 3in1 roller shutter SSLS.



5 Year Guarantee

Perfect for any climate, the exterior-mounted remote-controlled VELUX solar roller shutters protect your home from inclement weather. The robust aluminium design reduces solar heating, gives you blackout when needed, reduces rain noise, and increases security for your home. The solar 3in1 roller shutters SSLS are specially designed roller shutter for your VELUX manual or solar 3in1 roof windows GGLS and GPLS.

- Heat protection keeps your room cool and increases indoor comfort.
- The best blackout on the market gives you complete darkness for a better night's sleep or an afternoon nap.
- Ventilation with shutter down
- Stepless positioning allows you to lower the shutter to exactly where needed.
- Sleep undisturbed during hail or rain thanks to the noise reduction effect.
- Thermal insulation keeps your room at a comfortable temperature during winter
- VELUX solar interior blinds, awning blinds and roller shutters give you convenient remote control without any wiring.

CE

Creation date 29-09-2026 22:54:52 VRS Roller shutters INTEGRA en-GB - Approved

Operation guidance

The 3in1 roller shutters SSLS come with a ready-to-use wall switch for remote-control and can be raised and lowered to any desired position.

Compatibility

Solar 3in1 roller shutters SSLS can be fitted on VELUX 3in1 roof window GGLS and GPLS. As for sizes, please refer to the price list.

Solar roller shutters can be combined with copper windows using the ZOZ FFKF-- 251.

If combining the roller shutter with solar 3in1 roof windows GGLS, 2 pcs. dual solar switch ZOZ 246 must be ordered.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit https://www.velux.co.uk or https://www.velux.ie.

Creation date 29-09-2026 22:54:52

Technical information

Pre-paired wall switch	**Power consumption overview**	2 x alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 1 year.
	Size and weight description	8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg.
	Material and colour	ABS plastic, white (NCS S 1000-N)
	Installation and use	A pre-configured one-way radio frequency wall switch (KLI 313) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
VELUX solar 3in1 roller shutter SSLS.	**Power consumption**	High performance battery, NiMH, 9.6 V DC, 2100 mAh.
	Solar cell	Photovoltaic solar cell unit integrated in the roller shutter top cover.
	Connection	Powered by the solar panel
Exterior shield	**Material and colour**	Slats: Lacquered aluminium slats filled with polyurethane foam (does not contain Freon): grey (NCS S 7500-N). Hinges between slats: black rubber.
VELUX solar 3in1 roller shutter SSLS.	**Installation and use**	Solar 3in1 roller shutters SSLS can be installed from both the outside and the inside on VELUX 3in1 roof windows GGLS or GPLS. The installation is secure, fast and easy, among other things due to the specially designed VELUX “snap” brackets, and it can be done by one person.
	Battery	The battery is an energy buffer for operation in periods with inadequate charging. A fully charged battery allows up to 100 operations. The roller shutters come with a battery which must be switched on before operation. Expected battery lifetime: 10 years.
	Material and colour	Top casing, side covers, side profiles, slats and bottom cover: Lacquered aluminium, grey (NSC S 7500-N). Top casing end pieces, opening restrictors and side profile bottom pieces: Tinted plastic, grey (NSC S 7500-N). Top casing strip: Tinted plastic, black. Textile in slats, polyester with a TPU coating.

Creation date 29-09-2026 22:54:52