Quick guide to Dome Rooflights									
Shapes									
····		The second				$\overline{\mathbf{O}}$		·	
Square		Rectangular		Circular		Н	Circular emispheric	Pyramid square / rectangular	
Upstands									
							E		
Vertical Metal, PVC, GRP		Splayed Metal, PVC, GRP		Circular GRP	Profiled Revolt GRP		Northlight _{GRP}	Refurbishment adapter frame	
Glazing									
1-skin dome	2-skin d	dome 3-skin c	ome	4-skin dome	5-skin dom		Hybrid From 1 to 4 skins + insulated glass pan + 8mm safety glass + 16mm PC Multiwall	el or 1 to 2 PC	
Glazing material and colour									
								R	
Acrylic (PMMA) opal / clear Sun protection (Heatstop)		Polycarbonate (PC) opal / clear Sun protection		Acrylic (PMMA) black		Acrylic (PMMA) coloured		Glass opal / clear	
Special glazings									
·									
Impact resistant		High fire classifications Sun		protection Acoustic ins or Sound re-			Dark top for smoke and h exhaust ventilat		
Ventilation									
		1 th		A.		E		- China - Chin	
Ventilation integrated in upstand		Spindle actuator manually operated		Spindle, chain or rack actuator 230 V electrically operated				Smoke and heat exhaust ventilation according to EN 12101-2	
Safety systems									
		1							
Built-in fall-through protection system		Top-mounted fall-through protection system		Top-mounted force-absorbing grid		Fall-through protection safety glass		Burglary-resistant	
Accessories									
				E.					
Sun screening		Insect protection		Access hatch		Ladders and stairs Scissor stairs and safety ladder for roof access		Automation	
Size options									
	Standard size and made-to-measure Dome Rooflights are available								