


VELUX electric wall switch KLI 310

VELUX®



Conveniently operate your VELUX electric or solar products with the wall switch for universal usage KLI 310. The switch comes in a neutral design and operates any type of VELUX electric motors, interior blinds, awnings and shutters. It offers convenient operation with open/stop/close functionality and allows for grouping several of the same type of products in one switch.

- Control any of your solar or mains-powered VELUX products with the universal wall switch.
- Quickly and conveniently operate up to 200 electric or solar VELUX products of the same type simultaneously.
- Place the wireless wall switch anywhere in your room using the convenient wall mount.

Technical information

| | | |
|---|------------------------------------|--|
| VELUX electric wall switch KLI 310 | Material and colour | ABS (plastic), white (NCS S 1000-N) |
| | Size and weight description | Product including packaging: 235 x 153 x 48 mm (W x H x D). Weight: 0.224 kg. Wall switch: 82 x 82 x 17 mm (W x H x D). Weight: 0.125 kg. |
| | Installation and use | The wall switch is for indoor use only, minimum ambient temperature 5°C and maximum ambient temperature 45°C. It can be used in a dry or humid environment (such as a living room or a bathroom). Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m. |
| | Power consumption | 2x alkaline AAA (1.5 V) batteries. Expected battery lifetime: Up to 1 year. |
| | Compatibility | Wall switch KLI 310 is based on radio frequency (RF) technology and signals are transmitted in the 868 MHz range. The wall switch is compatible with products with the io-homecontrol® logo and can be used with VELUX electric and solar window operators as well as interior and exterior sunscreening products. |
| | Connection | VELUX io-home control connection of 868 MHz. |