VELUX electric wall switch KLI 310



3 Year Guarantee

Conveniently operate your VELUX electric or solar products with the wall switch for universal usage KLI 310. The switch comes in a neutral design and operates any type of VELUX electric motors, interior blinds, awnings and shutters. It offers convenient operation with open/stop/close functionality and allows for grouping several of the same type of products in one switch.

- Control any of your solar or mains-powered VELUX products with the universal wall switch.
- Quickly and conveniently operate up to 200 electric or solar VELUX products of the same type simultaneously.
- Place the wireless wall switch anywhere in your room using the convenient wall mount.

Creation date 10-11-2026 18:04:45 Electrical products K-- Technical info version en-GB - Approved

Technical information

VELUX electric wall switch KLI 310	**Material and colour**	ABS (plastic), white (NCS S 1000-N)
	Size and weight description	Product including packaging: 235 x 153 x 48 mm (W x H x D). Weight: 0.224 kg. Wall switch: 82 x 82 x 17 mm (W x H x D). Weight: 0.125 kg.
	Installation and use	The wall switch is for indoor use only, minimum ambient temperature 5°C and maximum ambient temperature 45°C. It can be used in a dry or humid environment (such as a living room or a bathroom). Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
	Power consumption	2x alkaline AAA (1.5 V) batteries. Expected battery lifetime: Up to 1 year.
	Compatibility	Wall switch KLI 310 is based on radio frequency (RF) technology and signals are transmitted in the 868 MHz range. The wall switch is compatible with products with the io-homecontrol® logo and can be used with VELUX electric and solar window operators as well as interior and exterior sunscreening products.
	Connection	VELUX io-home control connection of 868 MHz.

Creation date 10-11-2026 18:04:45