

VELUX electric translucent roller blind RML

VELUX®



The VELUX electric translucent roller blinds can be remote-controlled and delivers stepless light adjustment and privacy in rooms where blackout is not needed. The electric roller blinds connects seamlessly with your VELUX electric roof windows to give you flexible control over the natural light in your room. Comes in a lot of different and decorative colours and patterns.

- Increase your privacy, reduce unwanted glare and control incoming sunlight exactly as you like.
- VELUX electric blinds, awning blinds and shutters give you convenient remote control for extra comfort.
- Slimmest profile design on the market lets more natural light in.
- Install in minutes - simply click on the blind in the pre-fitted brackets and they are connected for remote control.
- Standard 100 by OEKO-TEX® certification guarantees the product is made without harmful substances.
- Compatible with VELUX ACTIVE with NETATMO - control your products from anywhere you want via smartphone or voice control.
- Stepless positioning allows you to lower the blind to exactly where needed.
- Integrated side rails provide smooth operation.



Colours and patterns

VELUX interior blinds are available in a wide range of colours and designs. However, a few blind variants are only available in a limited range of colours. Each colour and design option has a unique code. Add the code of your choice to the relevant blind type when ordering your products.



1086

Operation guidance

The VELUX electric roller blind comes with a pre-paired wall switch for remote-control and can be raised and lowered to any desired position.

Compatibility

Compatibility with VELUX electric roof windows:

Roller blind RML can be installed in GGL, VELUX electric GGL, GGU, VELUX electric GGU, GPL, GPU, GLL, GLU, GGLS and GPLS.

As to sizes, please refer to the price list as continuous changes of the product programme are made. The blind can also be made to measure.

Compatibility with other VELUX sunscreening products, VELUX electric and solar products and VELUX ACTIVE products:

The blind cannot be combined with other interior suncreening products. It can be combined with exterior suncreening products and electric window operators. It can also be fitted with insect roller screen ZIL.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://www.velux.co.uk> or <https://www.velux.ie>.

Technical information

VELUX electric translucent roller blind RML	Connection	When fitting the blind onto VELUX electric roof windows, no wiring is required as it is clicked directly onto the electrical installation brackets in the window. When fitting the blind onto manually operated VELUX roof windows or a VELUX roof window with retrofitted window operator, a separate cable set is required: ZOZ 241 for roof windows with K in size code, e.g. CK-- ZOZ 242 for roof windows size PK25 ZOZ 243 for roof windows with one letter in size code, e.g. C-- ZOZ 244 for V21 roof windows size P25
	Installation and use	The roller blind is easily clicked onto the top brackets pre-fitted in the window, leaving both hands free during the remaining part of the installation. When clicked onto VELUX electric roof windows, no wiring is required as the windows have preinstalled electrical installation brackets. When installing RML in a manually operated VELUX roof window or a VELUX roof window with retrofitted window operator, a separate cable set is required: ZOZ 241 for roof windows with K in size code, e.g. CK-- ZOZ 242 for roof windows size PK25 ZOZ 243 for roof windows with one letter in size code, e.g. C-- ZOZ 244 for V21 roof windows size P25
		The roller blind can be raised and lowered in any position using the remote control. Manual operation is possible, but should mainly be used for horizontal alignment of the blinds or in extraordinary cases. The blind supports silent mode when controlled by VELUX ACTIVE with NETATMO or VELUX App control.
	Material and colour	Control bar with motor unit, top fascia and side rails: Anodised aluminium. Guides and bottom brackets: Plastic, grey.
Pre-paired wall switch	Power consumption	0.6 A, 24 V d.c. from a VELUX electric roof window, or from a VELUX electric control system.
	Installation and use	A pre-configured one-way radio frequency wall switch (KLI 312) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.
	Material and colour	ABS plastic, white (NCS S 1000-N)
	Power consumption overview	2 x alkaline AAA (1.5V) batteries Expected battery lifetime: Up to 1 year.
Translucent roller blind cloth	Size and weight description	8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg.
	Material and colour	Cloth: 100 % polyester. Colours: See brochure and price list for VELUX decoration and suncreening products. Cords: 100 % polyester