

VELUX electric translucent pleated blind FML

VELUX®



VELUX electric translucent pleated blinds provide elegant lighting effects that bathe your room in pleasant, soft light. They connect seamlessly with your existing VELUX electric roof windows to give you convenient remote control over the privacy and natural light in your room. The electric pleated blinds are available in a wide range of colours and styles. VELUX blinds with white side rails fit perfectly with your white VELUX roof windows.

- Increase your privacy, reduce unwanted glare and control incoming sunlight exactly as you like.
- VELUX electric blinds, awning blinds and shutters give you convenient remote control for extra comfort.
- Slimmest profile design on the market lets more natural light in.
- Compatible with VELUX ACTIVE with NETATMO - control your products from anywhere you want via smartphone or voice control.
- Install in minutes - simply click on the blind in the pre-fitted brackets and they are connected for remote control.
- Elegant blind design with white side rails, which fit perfectly with white VELUX roof windows.
- Standard 100 by OEKO-TEX® certification guarantees the product is made without harmful substances.
- Stepless positioning allows you to lower the blind to exactly where needed.



Colours and patterns

VELUX interior blinds are available in a wide range of colours and designs. However, a few blind variants are only available in a limited range of colours. Each colour and design option has a unique code. Add the code of your choice to the relevant blind type when ordering your products.



1016



1256

Operation guidance

The VELUX electric single-pleated blind comes with a pre-paired wall switch for remote-control and can be raised and lowered to any desired position.

Compatibility

Compatibility with VELUX electric roof windows:

Pleated blind FML can be installed in GGL, VELUX electric GGL, GGU, VELUX electric GGU, GPL, GPU, GZL, GLL, GLU, GGGS and GPLS.

As to sizes, please refer to the price list as continuous changes of the product programme are made. The blind can also be made to measure.

Compatibility with other VELUX sun screening products, VELUX electric and solar-powered products and VELUX ACTIVE products:

The blind cannot be combined with other interior sun screening products. It can be combined with exterior sun screening products and electric window operators. It can also be fitted with insect roller screen ZIL.

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://www.velux.co.uk> or <https://www.velux.ie>.

Technical information

VELUX electric translucent pleated blind FML

Connection

When fitting the blind onto VELUX electric roof windows, no wiring is required as it is clicked directly onto the electrical installation brackets in the window. When fitting the blind onto manually operated VELUX roof windows or a VELUX roof window with retrofitted window operator, a separate cable set is required:
 ZOZ 241 for roof windows with K in size code, e.g. CK--
 ZOZ 242 for roof windows size PK25
 ZOZ 243 for roof windows with one letter in size code, e.g. C--
 ZOZ 244 for V21 roof windows size P25

Installation and use

The pleated blind is easily clicked onto the top brackets pre-fitted in the window, leaving both hands free during the remaining part of the installation. When clicked onto VELUX electric roof windows, no wiring is required as the windows have preinstalled electrical installation brackets. When installing FML in a manually operated VELUX roof window or a VELUX roof window with retrofitted window operator, a separate cable set is required:
 ZOZ 241 for roof windows with K in size code, e.g. CK--
 ZOZ 242 for roof windows size PK25
 ZOZ 243 for roof windows with one letter in size code, e.g. C--
 ZOZ 244 for V21 roof windows size P25

The pleated blind can be raised and lowered in any position using the remote control. Manual operation is possible, but should mainly be used for horizontal alignment of the blinds or in extraordinary cases.
 The blind supports silent mode when controlled by VELUX ACTIVE with NETATMO or VELUX App control.

Material and colour

Control bar with motor unit, top fascia and side rails: White lacquered aluminium.
 Guides and bottom brackets: Plastic, grey.

Power consumption

0.6 A, 24 V d.c. from a VELUX electric roof window, or from a VELUX electric control system.

Pre-paired wall switch

Installation and use

A pre-configured one-way radio frequency wall switch (KLI 312) is included. Radio frequency range: 300 m range open field. Depending on the building construction, the indoor range is approximately 30 m.

Material and colour

ABS plastic, white (NCS S 1000-N)

Power consumption overview

2 x alkaline AAA (1.5V) batteries
 Expected battery lifetime: Up to 1 year.

Size and weight description

8.2 cm x 8.2 cm x 1.7 cm, 0.125 kg.

Translucent pleated blind cloth

Material and colour

Cloth: 100 % polyester.
 Colours: See brochure and price list for VELUX decoration and sun screening products.
 Cords: 100 % polyester