

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	VELUX Group
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-VEL-20250109-CBI1-EN
Issue date	20.03.2025
Valid to	23.05.2027

VELUX Pro+ flashing set for flat roofing material (incl. BDX and BFX)

VELUX Group

www.ibu-epd.com | <https://epd-online.com>



General Information**VELUX Group****Programme holder**

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-VEL-20250109-CBI1-EN

This declaration is based on the product category rules:

Windows and doors , 01.08.2021
(PCR checked and approved by the SVR)

Issue date

20.03.2025

Valid to

23.05.2027



Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)



Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

**VELUX Pro+ flashing set for flat roofing material
(incl. BDX and BFX)****Owner of the declaration**

VELUX Group
Ådalsvej 99
2970 Hørsholm
Denmark

Declared product / declared unit

1m² VELUX Pro+ flashing set for flat roofing material EDN MK06 2000

The declared unit is based on the configuration of a standard size window measuring 0.78m x 1.178m.

Scope:

Productline VELUX Pro+ flashing set for flat roofing material EDN MK06 2000; manufactured by VELUX in France, Hungary, Poland, Denmark and China for sale in Europe.


Declaration according to *ISO 14025* and *EN 15804* describing specific environmental performances of the construction product.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR		
Independent verification of the declaration and data according to ISO 14025:2011		
<input type="checkbox"/>	internally	<input checked="" type="checkbox"/> externally



Prof. Dr. Birgit Grahl,
(Independent verifier)

Product

Product description/Product definition

The VELUX Pro+ flashing sets for flat roofing material are products for sale in the European market. This group of flashings cover a large range of different flashing types for profiled roofing material.

The different flashing types fit for installation with either a single window configuration or configurations of multiple windows installed adjacent to each other.

The VELUX Pro+ flashing set comes with an easy-to-fit underfelt collar (BFX) that includes an integrated drainage gutter and an insulation frame (BDX) that insulates the gap between the roof window and the roof construction.

The calculations are based on the flashing set for flat roofing material named EDN 2000. It declares the combination of the flashing EDN (EPD-VEL-20220114-CBB3-EN) and the collar BFX (EPD-VEL-20220111-CBB3-EN) and BDX (EPD-VEL-20220112-CBB3-EN) according to a representative window size.

For the use and application of the product the respective national provisions at the place of use apply, in Germany for example the building codes of the federal states and the corresponding national specifications.

Application

VELUX flashings for flat roofing material are used in renovation and new build. Either installed as a single window or in a combination of multiple windows.

Technical Data

The performance values are specific for the EDN flashing, underfelt collar BFX and insulation frame BDX.

The declared values in the table relate to the reference product.

Constructional data

Name	Value	Unit
Reaction to fire EN 13501-1	E	class

LCA: Calculation rules

Declared Unit

The declared unit is one m² related to a reference window, that the flashing set EDN MK06 2000 is installed in connection with.

The declared unit (1m²) is based on the representative product measuring 0.78m x 1.178m = 0.92m².

Declared unit

Name	Value	Unit
Declared unit	1	m ²
Grammage	9.65	kg/m ²
Weight per area	8.88	kg/repr. prod. (0.92m ²)
Weight per area	9.65	kg/DU (1m ²)
Layer thickness	0	m

System boundary

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision (no CE-marking).

Base materials/Ancillary materials

Name	Value	Unit
Aluminium	36	%
Galvanized steel	42	%
Stainless steel	0.1	%
Polyethylene LD	8	%
Polypropylene	6	%
Polybutadiene	7	%
Hot-melt adhesive	0.4	%

REACH

This product/article/at least one partial article contains substances listed in the candidate list (date: 17.01.2022) exceeding 0.1 percentage by mass: no.

Recycled content

Name	Value	Unit
Aluminum	30	%
Steel	10	%
Others	0	%

The values stated in the table relate to the recycled material streams in VELUX production.

Reference service life

A calculation of the reference service life according to ISO 15686 is not possible.

The Bundesinstitut für Bau, Stadt und Raumforschung/Federal office for building and regional planning (BBSR) table declares for the complete roof window a service life dependent on the applied window frame material between 25 and ≥ 50 years. This includes collars and flashings as declared with this EPD.

Type of EPD: Cradle to gate - with options. The following life cycle stages were considered:

Production stage A1-A3:

Consideration of the production of raw materials and their processing; transport of major material to the manufacturing site; assembly of semi-finished products to the final product; packaging material (including waste paper input for paper and cardboard).

End-of-Life stage C1, C2, C3:

C1: a manual demolition is assumed, resulting in indicator value "0".

C2: For the transport to EoL by truck a distance of 50 km is assumed.

C3: A scenario for the incineration of plastics in a waste incineration plant (WIP) is assumed.

The EoL-Scenario does not assume waste to be disposed of on

a landfill site. Module C4 is declared as "0".

Benefits for the next product system D:
Resulting electrical and thermal energy from the WIP, avoiding the generation of electricity and heat via fossil fuels, is considered.
The amount of metals after the reduction due to the net-flow calculations is sent to a recycling process. The effort for recycling, as well as the benefit for the regained metals are declared in module D.

Contribution of waste flows is considered in the modules where they occur.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. The *software GaBi* is used accompanied by the *GaBi background data base* (version 2021.2, 2021).

LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

The following declared values refer to the declared unit of 1m².

Information on describing the biogenic Carbon Content at factory gate

The declared biogenic content comprises the packaging material consisting of cardboard and paper. As module A5 is not declared, the information on packaging supports further EoL calculations.

Name	Value	Unit
Biogenic carbon content in product	-	kg C
Biogenic carbon content in accompanying packaging	0.62	kg C

The value refers to the following packaging material (per 1m²):
Cardboard packaging: 1.422kg, Paper insert: 0.020kg

The carbon stored in the packaging was taken into account as "CO₂-neutral". Thus the storage effect of the carbon bound in the packaging is not included in the calculation but is considered as emitted immediately.

Note: 1 kg of biogenic carbon is equivalent to 44/12 kg of CO₂.

Reference service life

Name	Value	Unit
Life Span (according to BBSR) depending on window frame material	25 - 50	a

End of life (C1-C4)

Name	Value	Unit
Collected separately waste type	9.65	kg
Recycling	7.49	kg
Energy recovery	2.16	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

Name	Value	Unit
Aluminium (net-flow calculation)	2.31	kg/1m ² product
Steel (net-flow calculation)	5.07	kg/1m ² product
Stainless steel (net-flow calculation)	8.18E-03	kg/1m ² product

LCA: Results

The LCIA assessment is performed applying the characterisation factor "EN 15804+A2, EF 3.0".

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² EDN MK06 2000

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Global Warming Potential total (GWP-total)	kg CO ₂ eq	4.78E+01	0	2.94E-02	8.26E+00	0	-2.79E+01
Global Warming Potential fossil fuels (GWP-fossil)	kg CO ₂ eq	4.78E+01	0	2.92E-02	8.26E+00	0	-2.78E+01
Global Warming Potential biogenic (GWP-biogenic)	kg CO ₂ eq	-3.03E-03	0	-3.47E-05	4.71E-04	0	-6.6E-02
Global Warming Potential luluc (GWP-luluc)	kg CO ₂ eq	2.69E-02	0	2.38E-04	2.6E-04	0	-9E-03
Depletion potential of the stratospheric ozone layer (ODP)	kg CFC11 eq	2.47E-11	0	5.75E-18	2.15E-15	0	-7.85E-14
Acidification potential of land and water (AP)	mol H ⁺ eq	1.68E-01	0	5.75E-05	1E-03	0	-1.04E-01
Eutrophication potential aquatic freshwater (EP-freshwater)	kg P eq	1.35E-04	0	8.65E-08	3.3E-07	0	-1.33E-05
Eutrophication potential aquatic marine (EP-marine)	kg N eq	3.1E-02	0	2.38E-05	2.63E-04	0	-1.48E-02
Eutrophication potential terrestrial (EP-terrestrial)	mol N eq	3.29E-01	0	2.7E-04	4.57E-03	0	-1.59E-01
Formation potential of tropospheric ozone photochemical oxidants (POCP)	kg NMVOC eq	1.07E-01	0	5.13E-05	7.63E-04	0	-4.87E-02
Abiotic depletion potential for non fossil resources (ADPE)	kg Sb eq	7.91E-05	0	2.58E-09	3.12E-08	0	-1.95E-05
Abiotic depletion potential for fossil resources (ADPF)	MJ	7.33E+02	0	3.88E-01	2.77E+00	0	-3.52E+02
Water use (WDP)	m ³ world eq deprived	1.32E+01	0	2.7E-04	8.3E-01	0	-2.18E+01

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² EDN MK06 2000

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Renewable primary energy as energy carrier (PERE)	MJ	1.6E+02	0	2.23E-02	5.98E-01	0	-1.12E+02
Renewable primary energy resources as material utilization (PERM)	MJ	2.36E+01	0	0	0	0	0
Total use of renewable primary energy resources (PERT)	MJ	1.84E+02	0	2.23E-02	5.98E-01	0	-1.12E+02
Non renewable primary energy as energy carrier (PENRE)	MJ	6.41E+02	0	3.89E-01	9.5E+01	0	-3.52E+02
Non renewable primary energy as material utilization (PENRM)	MJ	9.22E+01	0	0	-9.22E+01	0	0
Total use of non renewable primary energy resources (PENRT)	MJ	7.34E+02	0	3.89E-01	2.77E+00	0	-3.52E+02
Use of secondary material (SM)	kg	2.96E+00	0	0	0	0	6.26E+00
Use of renewable secondary fuels (RSF)	MJ	0	0	0	0	0	0
Use of non renewable secondary fuels (NRSF)	MJ	0	0	0	0	0	0
Use of net fresh water (FW)	m ³	5.81E-01	0	2.56E-05	1.97E-02	0	-7.12E-01

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m² EDN MK06 2000

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Hazardous waste disposed (HWD)	kg	6.72E-07	0	2.05E-11	4.96E-10	0	-4.88E-06
Non hazardous waste disposed (NHWD)	kg	6.6E+00	0	6.11E-05	6.44E-01	0	-4.32E+00
Radioactive waste disposed (RWD)	kg	3.69E-02	0	7.06E-07	1.12E-04	0	-1.8E-02
Components for re-use (CRU)	kg	0	0	0	0	0	0
Materials for recycling (MFR)	kg	0	0	0	6.5E+00	0	0
Materials for energy recovery (MER)	kg	0	0	0	0	0	0
Exported electrical energy (EEE)	MJ	0	0	0	1.79E+01	0	0
Exported thermal energy (EET)	MJ	0	0	0	3.21E+01	0	0

RESULTS OF THE LCA - additional impact categories according to EN 15804+A2-optional: 1 m² EDN MK06 2000

Parameter	Unit	A1-A3	C1	C2	C3	C4	D
Incidence of disease due to PM emissions (PM)	Disease incidence	1.75E-06	0	3.49E-10	1.29E-08	0	-1.18E-06
Human exposure efficiency relative to U235 (IR)	kBq U235 eq	7.83E+00	0	1.03E-04	1.49E-02	0	-3.41E+00
Comparative toxic unit for ecosystems (ETP-fw)	CTUe	3.27E+02	0	2.88E-01	1.93E+00	0	-9.75E+01
Comparative toxic unit for humans (carcinogenic) (HTP-c)	CTUh	4.97E-08	0	5.82E-12	1.1E-10	0	-1.52E-08

Comparative toxic unit for humans (noncarcinogenic) (HTP-nc)	CTUh	6.04E-07	0	3.16E-10	1.11E-08	0	-3.19E-07
Soil quality index (SQP)	SQP	2.25E+02	0	1.33E-01	6.81E-01	0	-1.63E+01

Disclaimer 1 – for the indicator 'Potential Human exposure efficiency relative to U235'.

This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.

Disclaimer 2 – for the indicators 'abiotic depletion potential for non-fossil resources', 'abiotic depletion potential for fossil resources', 'water (user) deprivation potential, deprivation-weighted water consumption', 'potential comparative toxic unit for ecosystems', 'potential comparative toxic unit for humans – cancerogenic', 'Potential comparative toxic unit for humans - not cancerogenic', 'potential soil quality index'.

The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experience with the indicator.

Disclaimer 3 – for 'potential soil quality index'.

Due to a data lack in the foreground data of VELUX, the result has a very high uncertainty and refers only to the background data, which contain respective information.

References

BBSR

BBSR, 24.02.2017, Nutzungsdauer von Bauteilen nach BNB

DIN EN 13501

DIN EN 13501-1:2019-05: Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

DIN EN ISO 10077

DIN EN ISO 10077-1:2020-10: Thermal performance of windows, doors and shutters - Calculation of thermal transmittance

EN 15804

EN 15804:2012+A2:2019, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

GaBi

GaBi Software and GaBi Database by Sphera Solution GmbH, version: 2021.2, 2021

IBU 2021

Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V., Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021, www.ibu-epd.com

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

ISO 15686

ISO 15686:2011-05: Buildings and constructed assets - Service life planning - Part 1: General principles and framework

PCR part A

Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report according to EN 15804+A2:2019, version 1.4, Berlin: Institut Bauen und Umwelt e.V., 2024

PCR part B

Requirements on the EPDS for Windows and doors, version 10 - 05.07.2023, Berlin: Institut Bauen und Umwelt e.V.

REACH

Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Regulation (EU) No. 305/2011 (CPR)

Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 laying down harmonized conditions for the marketing of construction products and repealing Council Directive 89/106/EEC



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com

Angela Schindler
Umweltberatung



Author of the Life Cycle Assessment

Angela Schindler Umweltberatung
Tüfing Str. 12
88682 Salem
Germany

07553 919 9456
angela@schindler-umwelt.de
www.schindler-umwelt.de



Daxner & Merl GmbH
Lindengasse 39/8
1070 Wien
Austria

+43 676 849477826
office@daxner-merl.com
www.daxner-merl.com

Owner of the Declaration

VELUX Group
Ådalsvej 99
2970 Hørsholm
Denmark

+4545164726
jakob.roerbeck@velux.com
www.velux.com