

VELUX electric battery backup KLB 100

VELUX®



Operate your VELUX electric products, even in a power outage with the VELUX electric battery backup KLB. The battery back-up is suitable for VELUX electric centre-pivot roof windows GGL/GGU, window operator KMG 100/100K, and power supply unit KUX 110. The battery backup is compatible with io-homecontrol® and is recommended for areas where power failures are common.

- Ensures uninterrupted power to mains-powered VELUX electric products.

Technical information

VELUX electric battery backup KLB 100	Material and colour	Shockproof plastic, white (NCS S 1000-N)
	Size and weight description	Product in packaging: 327 x 166 x 80 mm, 1.5 kg Battery backup: 180 x 85 x 67 mm (W x H x D), 0.3 kg
	Installation and use	The battery backup is for indoor use, maximum ambient temperature 50°C. It must not be covered.
	Power consumption	24 V d.c. from VELUX electric roof and flat-roof windows, VELUX electric upgrade kits or VELUX electric control system KUX 110. Automatic re-charging of battery through electric roof and flat-roof windows, VELUX electric upgrade kits or VELUX electric control system KUX 110.
	Compatibility	KLB 100 is based on radio frequency (RF) technology, 868 MHz range, and is compatible with other products with the io-homecontrol® logo. KLB 100 is not compatible with VELUX battery and solar powered products.
	Connection	8 m connection cable included. The battery backup is to be connected to the connection box of VELUX electric windows or VELUX electric control system KUX 110.