

VELUX roof window VLT 0000Z

Glazing 00H

VELUX®



The window can be installed in roof pitches between 15° and 60°.



VELUX roof window VLT 0000Z is designed for use in uninhabited rooms where light and ventilation is needed. The roof window is top-hung and has three ventilation positions. Made from maintenance-free black polyurethane and aluminium. Comes complete with integrated flashing.

- Three ventilation positions enable you to secure a constant low-level air flow in uninhabited areas.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the extruded aluminium sash.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.









Available sizes and daylight area

| | |
|-----|---------------------|
| | 460 |
| 610 | VLT ++ (0.22) |

All measurements are in mm. () = Effective daylight area, m² [] = Geometric free area, m²

Glazing features

| Glazing 00H | |  |
|---|---|---|
|  | Heat insulation The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort. | $U_g = 3.0$ |
|  | Solar gain In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods. | 0.79 |
|  | Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods. | ★★☆☆ |
|  | Security Thicker laminated inner glass increases resistance to manual attack (burglary). | N/A |
|  | Safety lamination Prevents glass from falling into the room in case of accidental breakage. | |
|  | Toughened glass Adds strength to the outer glass surface to protect from wayward balls and extreme weather such as heavy storms and hail. | |
|  | UV filter Protects your interior furnishings from fading due to the sun's harmful UV rays. | |
|  | Rain noise reduction Rain noise reduction creates a barrier between the window and the weather outside for undisturbed moments during rainy days – or nights. | |
|  | Easy-to-clean Dirt-repellent coating lets you spend less time cleaning and more time enjoying the view. | |
|  | Anti-dew The anti-dew coating significantly reduces the days with dew on the outer glass and thus gives you a clear view. | |

Glazing structure

| Glazing unit | Composition (from inside to outside) |
|---------------|---|
| Double-glazed | 3 mm float glass - 10 mm Air - 3 mm float glass |

Interior finish

| Material Description | Black maintenance free Finished with polyurethane lacquer. |
|--|---|
| Colour code NCS, inner surface | S 9000-N |
| Colour code nearest RAL, inner surface | 9005 |

Exterior covers

| Material Description | Aluminium, dark grey Dark grey |
|--|-----------------------------------|
| Colour code NCS, outer surface | S 7500-N |
| Colour code nearest RAL, outer surface | 7043 |

Guarantee period

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.