



VELUX Skylight installed in new metal roofing.

1. The sheets are fitted 100 mm from the bottom frame
2. The flashing is mounted
3. Fit the metal sheets

BASIS OF DESIGN:
VELUX Fixed
Skylight (FS)

Underlayment

60-150 mm

EDW Head Flashing

Lining

Trimmer/Header

VELUX Skylight installed in to existing metal roofing. ELEVATIONS

1. The metal sheet is cut to allow for the flashing apron.
The cut must stop on top of a profile
(min 270 mm from the side frame)
2. The filler piece is placed so it fits the cut
(can be fixed to the existing metal sheets with rivets)
(Shape the filler piece from the cut-out sheets of
the skylight)

EDW Bottom Flashing

Underlayment

Batten

Lining

SECTION A-A

Insulation

Ventilation

Insulation

Finish material

BASIS OF DESIGN:
VELUX Fixed
Skylight (FS)

30-60 mm

Underlayment

Tight joint between finish
groove and finish material

Lining

Rafter

SECTION B-B

30-60 mm

EDW-flashing gutter

Mounting bracket

VELUX

Sky-Product Management

AUSTRALIA PTY. LTD

+612 8565 6000

FS - Fixed Skylight and EDW Flashing in Profiled Metal Roof

Name	Date
Drawn by	Oct 09
Checked by	Oct 09
Drawing No.	