



- ① VELUX flashing (EDW and ETW 15°-90°)
- ② VELUX window (GDL 35°-53°)
- ③ VELUX underfelt collar (BFX and BFX WK34)
- ④ VELUX insulation frame (BDX and BDX WK34)
- ⑤ VELUX vapour barrier (BBX and BBX WK34)
- ⑥ VELUX vapour barrier tape (BBX)
- ⑦ Gasket on BBX in window rebate
- ⑧ VELUX Lining (LS- and LL-)
- ⑨ Installation batten (Non VELUX)
- ⑩ Trimmer where necessary (Non VELUX)
- ⑪ Felt/breather membrane (Non VELUX)

Roof covering:

**Tiles**  
Max 120 mm

VELUX Products:

- GDL** 35°-53°
- EDW** 15°-90°
- BFX**
- BDX**
- BBX**
- LS-**
- ETW** 15°-90°
- BFX WK34**
- BDX WK34**
- BBX WK34**
- LL-**

VELUX window sizes:

Size	Width (mm)	Size	Height (mm)
MK--	780	-K19	2520
PK--	942		
SK--	1140		

© VELUX GROUP ® VELUX, VELUX logo are registered trademarks

<b>VELUX</b>			
File name: EDW-GDL-VAS-170-0820			
Drawing no.:---		SCo: ---	
Create date: 13.08.2020	Rev. date:	Format: A3	Scale: 1:5

Note: When installing VELUX Roof Windows, flashings and installation products, the manufacturers instructions and current building and fire regulations, where applicable, must be met.